




TRUAX TWO DEPARTURE

SL-198 (FAA)


ATIS
 124.6
 CLNC DEL
 125.45
 GND CON
 121.9
 HOBBY TOWER
 118.7 256.9
 HOUSTON DEP CON
 127.125 269.075

EAGLE LAKE
 116.4 ELA 
 Chan 111

HOBBY
 117.1 HUB 
 Chan 118

SCHOLES
 113.0 VUH 
 Chan 77

YAWNS
 N28°49.39'
 W95°33.96'

TRUAX
 114.0 NGP 
 Chan 87
 N27°41.18' - W97°17.69'
 L-20-21

TAKE-OFF MINIMUMS:
 Rwy 12L/R, 30L/R, 35 standard.
 Rwy 4, 200-1 or standard with minimum climb of 270' per NM to 300'.
 Rwy 17, 200-1 or standard with minimum climb of 827' per NM to 300'.
 Rwy 22, standard with minimum climb of 290' per NM to 1500.

Note: For aircraft filed FL180 and above to Rio Grande Valley area or for aircraft filed FL180 and above overflying NGP VORTAC to international destinations.

NOTE: Chart not to scale.

(NOTES CONTINUED ON FOLLOWING PAGE)

NOTE: Radar Required.



DEPARTURE ROUTE DESCRIPTION

Expect vectors to YAWNS INT, maintain 5000', expect filed altitude 10 minutes after departure. Thence. . . .

. . . . via VUH R-228 and NGP R-047 to NGP VORTAC.

SC-5, 19 NOV 2009 to 17 DEC 2009

SC-5, 19 NOV 2009 to 17 DEC 2009