



INSTRUMENT APPROACH PROCEDURE CHARTS



IFR ALTERNATE AIRPORT MINIMUMS

Standard alternate minimums for non-precision approaches and approaches with vertical guidance [NDB, VOR, LOC, TACAN, LDA, SDF, VOR/DME, ASR, RNAV (GPS) or RNAV (RNP)] are 800-2. Standard alternate minimums for precision approaches (ILS, PAR, or GLS) are 600-2. Airports within this geographical area that require alternate minimums other than standard or alternate minimums with restrictions are listed below. NA - means alternate minimums are not authorized due to unmonitored facility, absence of weather reporting service, or lack of adequate navigation coverage. Civil pilots see FAR 91. IFR Alternate Minimums: Ceiling and Visibility Minimums not applicable to USA/USN/USAF. Pilots must review the IFR Alternate Minimums Notes for alternate airfield suitability.

NAME ALTERNATE MINIMUMS
BRYCE CANYON, UT
BRYCE
CANYON (BCE) ..... RNAV (GPS) Rwy 3
Category A, B, 900-2; Category C, 900-2½.

BULLHEAD CITY, AZ
LAUGHLIN/BULLHEAD
INTL (IFP) ..... RNAV (GPS) Rwy 16¹²
RNAV (GPS) Rwy 34³⁴
VOR/DME Rwy 34¹⁵
¹NA when local weather not available.
²Categories A, B, 1200-2; Categories C, D, 1200-3.
³NA when control tower closed.
⁴Categories A, B, 1100-2; Categories C, D, 1100-3.
⁵Categories A, B, 2200-2; Categories C, D, 2200-3.

CEDAR CITY, UT
CEDAR CITY RGNL (CDC)..... ILS Rwy 20
VOR Rwy 20
Category D, 900-2¾.

ELKO, NV
ELKO RGNL (EKO)..... LDA/DME Rwy 23¹
RNAV (GPS) Rwy 23²
VOR -A³
VOR/DME-B⁴
¹Categories A, B, 900-2; Category C 1000-3;
Category D, 1100-3.
²Categories A, B, 1400-2; Categories C, D, 1400-3.
³Categories A, B, 1500-2; Categories C, D, 1500-3.
⁴Categories A, B, 1200-2; Categories C, D, 1200-3.

ELY, NV
ELY AIRPORT/
YELLAND FIELD (ELY)..... RNAV (GPS) Rwy 18
NA when local weather not available.
Category D 1000-3.

NAME ALTERNATE MINIMUMS
EUREKA, NV
EUREKA (05U) ..... RNAV (GPS) Rwy 18
Category A, B, 1900-2; Categories C, D,
1900-3.

FLAGSTAFF, AZ
FLAGSTAFF
PULLIAM (FLG) ..... ILS or LOC/DME Rwy 21¹²
VOR-A³
¹NA when control tower closed.
²ILS, Categories B, C, D, 700-2.
³Categories A, B, 1300-2; Categories C, D,
1300-3.

FORT HUACHUCA-SIERRA VISTA, AZ
SIERRA VISTA muni-
LIBBY AAF (FHU) ..... ILS or LOC Rwy 26
NDB Rwy 26
RNAV (GPS) Rwy 8
VOR Rwy 26
NA when control tower closed.

GLENDALE, AZ
GLENDALE
MUNI (GEU)..... RNAV (GPS) Rwy 1
RNAV (GPS) Rwy 19
NA when local weather not available.

GRAND CANYON, AZ
GRAND CANYON NATIONAL
PARK (GCN)..... ILS or LOC/DME Rwy 3
NA when control tower closed.
Category D, 700-2.

VALLE (40G)..... VOR/DME Rwy 19
NA except for operators with approved weather
reporting service.

KANAB, UT
KANAB MUNI (KNB) ..... RNAV (GPS) Rwy 1
Category B, 1100-2; Category C, 1400-3.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015







# ALTERNATE MINS

15064

M3



NAME ALTERNATE MINIMUMS

## PHOENIX, AZ (CON'T)

PHOENIX SKY HARBOR

INTL (PHX)..... ILS or LOC/DME Rwy 7L<sup>1</sup>  
 ILS or LOC Rwy 8<sup>4</sup>  
 ILS or LOC Rwy 25L<sup>3</sup>  
 ILS or LOC Rwy 26<sup>6</sup>  
 RNAV (GPS) Y Rwy 7R<sup>2</sup>  
 RNAV (GPS) Y Rwy 7L<sup>2</sup>  
 RNAV (GPS) Y Rwy 8<sup>2</sup>  
 RNAV (GPS) Y Rwy 25L<sup>2</sup>  
 RNAV (GPS) Y Rwy 25R<sup>2</sup>  
 RNAV (GPS) Y Rwy 26<sup>2</sup>

<sup>1</sup>ILS, Categories A, B, C, 700-2; Category D, 800-2½. LOC, Category D, 800-2½.

<sup>2</sup>Category D, 800-2½.

<sup>3</sup>ILS, Categories A, B, C, 700-2; Category D, 800-2.

<sup>4</sup>ILS, Categories A, B, 800-2; Category C, 800-2¼; Category D, 800-2½. LOC, Category C, 800-2¼; Category D, 800-2½.

<sup>5</sup>Category C, 800-2¼; Category D, 800-2½.

<sup>6</sup>ILS, Categories A, B, 700-2; Category C, 800-2 ¼; Category D, 1100-3; LOC, Category C, 800-2 ¼; Category D, 1100-3.

## PRESCOTT, AZ

ERNEST A LOVE

FIELD (PRC) ..... ILS or LOC/DME Rwy 21L<sup>12</sup>  
 RNAV (GPS) Y Rwy 3R<sup>4</sup>  
 RNAV (GPS) Rwy 12<sup>4</sup>  
 RNAV (GPS) Rwy 21L<sup>4</sup>  
 VOR Rwy 13<sup>3</sup>

<sup>1</sup>NA when control tower closed.

<sup>2</sup>ILS, Category B, 700-2; Category C, 1100-3; Category D, 1700-3. LOC, Category C, 1100-3; Category D, 1700-3.

<sup>3</sup>Category D, 900-3.

<sup>4</sup>Category C, 1100-3; Category D, 1700-3.

## PRICE, UT

CARBON COUNTY RGNL/BUCK DAVIS

FIELD (PUC) ..... RNAV (GPS) Rwy 01<sup>12</sup>  
 VOR/DME Rwy 01<sup>3</sup>

<sup>1</sup>NA when local weather not available.

<sup>2</sup>Category C, 900-2½; Category D, 1100-3.

<sup>3</sup>Category B, 1000-2; Category C, 1200-3;

Category D, 2600-3.

## PROVO, UT

PROVO

MUNI (PVU) ..... ILS or LOC/DME Rwy 13

ILS, Category A, B, C, D, 700-2.

ILS, LOC, NA when control tower closed.

NAME

## RENO, NV

RENO/TAHOE

INTL (RNO)..... ILS Rwy 16R, 2100-7<sup>1</sup>  
 ILS or LOC/DME Rwy 34L<sup>2</sup>  
 LOC Rwy 16R<sup>3</sup>  
 RNAV (GPS) X Rwy 34L<sup>4</sup>  
 RNAV (GPS) X Rwy 34R<sup>4</sup>  
 RNAV (GPS) X Rwy 16L<sup>5</sup>  
 RNAV (GPS) X Rwy 16R<sup>6</sup>  
 RNAV (RNP) Y Rwy 16L<sup>9</sup>  
 RNAV (RNP) Y Rwy 16R<sup>9</sup>  
 RNAV (RNP) Z Rwy 16L<sup>7</sup>  
 RNAV (RNP) Z Rwy 16R<sup>7</sup>  
 VOR-D<sup>3</sup>

<sup>1</sup>LOC, NA.

<sup>2</sup>ILS, LOC, Categories A, B, 1000-2; Category C, 1000-2¾.

<sup>3</sup>Categories A, B, 1600-2; Categories C, D, 1600-3; Category E, 2400-3.

<sup>4</sup>Categories A, B, 1000-2; Category C, 1000-2¾; Category D, 1000-3.

<sup>5</sup>Categories A, B, 1400-2; Categories C, D, 1400-3.

<sup>6</sup>Categories A, B, 1800-2; Categories C, D, 1800-3.

<sup>7</sup>Categories A, B, C, 800-2½.

<sup>8</sup>Categories A, B, 1600-2; Categories C, D, 1600-3.

<sup>9</sup>Categories A, B, C, D, 800-2½.

## SAFFORD, AZ

SAFFORD RGNL (SAD) ..... RNAV (GPS) Rwy 12  
 RNAV (GPS) Rwy 30

NA when local weather not available.

## ST. GEORGE, UT

ST. GEORGE

MUNI (SGU)..... LDA/DME Rwy 19<sup>1</sup>  
 RNAV (GPS) Rwy 1<sup>2</sup>  
 RNAV (GPS) Rwy 19<sup>1</sup>  
 VOR/DME-A<sup>3</sup>

<sup>1</sup>Categories A, B, 1100-2, Categories C, D, 1100-3.

<sup>2</sup>Categories A, B, 900-2; Categories C, 900-2¾.

<sup>3</sup>Categories A, B, 900-2; Category C, 900-2½; Category D, 1000-3.

## ST. JOHNS, AZ

ST. JOHNS INDUSTRIAL

AIRPARK (SJV) ..... RNAV (GPS) Rwy 14  
 RNAV (GPS) Rwy 32  
 VOR/DME-A

NA when local weather not available.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015



# ALTERNATE MINS

15064

M3

SW-4





# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS) INSTRUMENT APPROACH PROCEDURE CHARTS

15064

## IFR TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

### Civil Airports and Selected Military Airports

ALL USERS: Airports that have Departure Procedures (DPs) designed specifically to assist pilots in avoiding obstacles during the climb to the minimum enroute altitude, and/or airports that have civil IFR takeoff minimums other than standard, are listed below. Takeoff Minimums and Departure Procedures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in MSL.

DPs specifically designed for obstacle avoidance are referred to as Obstacle Departure Procedures (ODPs) and are textually described below, or published separately as a graphic procedure. If the ODP is published as a graphic procedure, its name will be listed below, and it can be found in either this volume (civil), or the applicable military volume, as appropriate. Users will recognize graphic obstacle DPs by the term "(OBSTACLE)" included in the procedure title; e.g., TETON TWO (OBSTACLE). If not specifically assigned an ODP, SID, or radar vector as part of an IFR clearance, an ODP may be required to be flown for obstacle clearance, even though not specifically stated in the IFR clearance. When doing so in this manner, ATC should be informed when the ODP being used contains a specified route to be flown, restrictions before turning, and/or altitude restrictions.

Some ODPs, which are established solely for obstacle avoidance, require a climb in visual conditions to cross the airport, a fix, or a NAVAID in a specified direction, at or above a specified altitude. These procedures are called Visual Climb Over Airport (VCOA). To ensure safe and efficient operations, the pilot must verbally request approval from ATC to fly the VCOA when requesting their IFR clearance.

At some locations where an ODP has been established, a diverse vector area (DVA) may be created to allow radar vectors to be used in lieu of an ODP. DVA information will state that headings will be as assigned by ATC and climb gradients, when applicable, will be published immediately following the specified departure procedure.

Graphic DPs designed by ATC to standardize traffic flows, ensure aircraft separation and enhance capacity are referred to as "Standard Instrument Departures (SIDs)". SIDs also provide obstacle clearance and are published under the appropriate airport section. ATC clearance must be received prior to flying a SID.

CIVIL USERS NOTE: Title 14 Code of Federal Regulations Part 91 prescribes standard takeoff rules and establishes takeoff minimums for certain operators as follows: (1) Aircraft having two engines or less - one statute mile. (2) Aircraft having more than two engines - one-half statute mile. These standard minima apply in the absence of any different minima listed below.

MILITARY USERS NOTE: Civil (nonstandard) takeoff minima are published below. For military takeoff minima, refer to appropriate service directives.

NAME	TAKEOFF MINIMUMS
------	------------------

### BATTLE MOUNTAIN, NV

BATTLE MOUNTAIN (BAM)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 3 09127 (FAA)

TAKEOFF MINIMUMS: **Rwy 3**, std. w/ a min climb of 282' per NM to 7300 or 4700-3 for climb in visual conditions. **Rwy 12**, std. w/ a min climb of 386' per NM to 7600 or 4700-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 3**, climb heading 032° to 8200 before proceeding on course or climb in visual conditions to cross Battle Mountain Airport at or above 9100 before proceeding on course.

**Rwy 12**, climb heading 122° and BAM R-076 to 10000 before proceeding on course or climb in visual conditions to cross Battle Mountain Airport at or above 9100 before proceeding on course. **Rwy 21**, climb direct BAM VORTAC and BAM R-205 to 10100 before proceeding on course. **Rwy 30**, climb heading 302° and BAM R-324 to 9100 before proceeding on course.

NAME	TAKEOFF MINIMUMS
------	------------------

### BEAVER, UT

BEAVER MUNI (U52)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 07242 (FAA)

TAKEOFF MINIMUMS: **Rwys 7, 25**, NA-obstacles. **Rwys 13, 31**, 2600-234 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwys 13, 31**, climb in visual conditions to cross Beaver Muni Airport Northwest bound at or above 8300 then climb to 10100 via MLF VORTAC R-102 to MLF VORTAC. Do not exceed 210 KIAS until established on cross VORTAC R-102.

### BLANDING, UT

BLANDING MUNI (BDG)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1A 14037 (FAA)

TAKEOFF MINIMUMS: **Rwy 35**, 800-1 or std. with a min. climb of 350 feet per NM to 6700.

DEPARTURE PROCEDURE: **Rwy 17**, turn left, thence... **Rwy 21**, turn right, thence...

...climb to 9000 on heading 090° and DVC R-223 to DVC VORTAC, then continue climb on course to MEA. **Rwy 35**, turn right climb to 9000 via heading 090° and DVC R-223 to DVC VORTAC, then continue climb on course to MEA.

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## BRIGHAM CITY, UT

### BRIGHAM CITY (BMC)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 6A 11349 (FAA)

TAKEOFF MINIMUMS: **Rwy 35**, NA

DEPARTURE PROCEDURE: **Rwy 17**, climbing right turn heading 207° and OGD R-331 to OGD VORTAC before proceeding on course.

NOTE: **Rwy 17**, poles 266' from DER, 558' right of centerline, 30' AGL/4258' MSL.

## BRYCE CANYON, UT

### BRYCE CANYON (BCE)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 11069 (FAA)

DEPARTURE PROCEDURE: use BRYCE DEPARTURE.

## BULLHEAD CITY, AZ

### LAUGHLIN/BULLHEAD INTL (IFP)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 09183 (FAA)

TAKEOFF MINIMUMS: **Rwy 16**, std. w/ a min. climb of 370' per NM to 1800, or 1700-3 for climb in visual conditions. **Rwy 34**, std. w/ a min. climb of 495' per NM to 5500, or 1700-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 16**, climb via heading 164° and EED VORTAC R-334 to EED VORTAC, or for climb in visual conditions: cross Laughlin/Bullhead Intl airport at or above 2300, then continue climbing via heading 155° and EED VORTAC R-335 to EED VORTAC. **Rwy 34**, climb via heading 344° to 1600, then climbing right turn direct EED VORTAC, or for climb in visual conditions: cross Laughlin/Bullhead Intl airport at or above 2300, then continue climbing via heading 155° and EED VORTAC R-335 to EED VORTAC. **All Aircraft** climb in EED VORTAC holding pattern (East, right turn, 257° inbound) to cross EED VORTAC at or above MEA for direction of flight before proceeding on course.

NOTE: **Rwy 16**, multiple bushes beginning 3600' from DER, left of centerline, up to 12' AGL/1029' MSL. **Rwy 34**, multiple poles beginning 2211' from DER, right of centerline, up to 105' AGL/821' MSL.

## CARSON CITY, NV

### CARSON (CXP)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

ORIG 08325 (FAA)

TAKEOFF MINIMUMS: **Rwy 27**, NA-obstacles.

DEPARTURE PROCEDURE: **Rwy 9**, use JIMPA DEPARTURE.

## CASA GRANDE, AZ

### CASA GRANDE MUNI (CGZ)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1B 14037 (FAA)

TAKEOFF MINIMUMS: **Rwy 5**, 300-1 or std. w/ min. climb of 354' per NM to 1700.

DEPARTURE PROCEDURE: **Rwy 5**, climbing right turn direct TFD VORTAC, thence...

**Rwy 23**, climb direct TFD VORTAC, thence...

...continue climb in holding pattern (SW, right turns, 048° inbound) to MEA for direction of flight.

NOTE: **Rwy 5**, pole 4034' from DER, 805' left of centerline, 109' AGL/1593' MSL.

## CEDAR CITY, UT

### CEDAR CITY RGNL (CDC)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 2A 14037 (FAA)

TAKEOFF MINIMUMS: **Rwy 8**, 300-3 or std. with a min. climb of 450' per NM to 10000.

DEPARTURE PROCEDURE: **Rwys 2, 8**, turn left, thence...

**Rwys 20, 26**, turn right, thence...

...climb direct to CDC VOR/DME, continue climb to 9000 on CDC R-348. Northbound continue on course. All others reverse course, climb to cross CDC VOR/DME at or above MCA for direction of flight.

## CHANDLER, AZ

### CHANDLER MUNI (CHD)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 14261 (FAA)

DEPARTURE PROCEDURE: **Rwys 4L, 4R**, climbing left turn heading 220° to intercept TFD VORTAC R-350 southbound to TFD VORTAC. **Rwys 22L, 22R**, climbing left turn heading 190° to intercept TFD VORTAC R-350 southbound to TFD VORTAC.

NOTE: **Rwy 4L**, antenna on building 69' from DER, 515' left of centerline, 25' AGL/1281' MSL. Tower 981' from DER, 615' left of centerline, 80' AGL/1319' MSL. Trees and poles beginning 1100' from DER, 458' left of centerline, up to 30' AGL/1272' MSL. **Rwy 4R**, poles beginning 1298' from DER, 56' left of centerline, up to 36' AGL/1283' MSL. **Rwy 22L**, tree 336' from DER, 511' right of centerline, 15' AGL/1250' MSL. Tree 988' from DER, 756' left of centerline, 30' AGL/1266' MSL. **Rwy 22R**, building 30' from DER, 441' right of centerline, 24' AGL/1254' MSL. Vehicles beginning 199' from DER, 271' right of centerline, up to 15' AGL/1246' MSL. Poles and trees beginning 471' from DER, 45' left of centerline, up to 36' AGL/1290' MSL. Trees and poles beginning 1088' from DER, 50' right of centerline, up to 36' AGL/1274' MSL.

## STELLAR AIRPARK (P19)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

DEPARTURE PROCEDURE: **Rwy 17**, turn left, climb via heading 150°. **Rwy 35**, turn right. **All aircraft** climb via TFD R-350 direct TFD VORTAC.

NOTE: **Rwy 17**, tower and signs beginning 574' from DER, 183' right of centerline, up to 50' AGL/1124' MSL. Sign 611' from DER, 365' left of centerline, 42' AGL/1214' MSL.

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## CLIFTON/MORENCI, AZ

GREENLEE COUNTY (CFT)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 10210 (FAA)  
DEPARTURE PROCEDURE: Use SAN SIMON  
DEPARTURE.

## COLORADO CITY, AZ

COLORADO CITY MUNI (AZC)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 95089 (FAA)  
TAKEOFF MINIMUMS: **Rwy 2, NA.**  
DEPARTURE PROCEDURE: **Rwy 11**, turn right. **Rwys 20, 29**, turn left. **All aircraft** climb to 7400 via the 160° bearing from AZC NDB then continue climb on course.

## COOLIDGE, AZ

COOLIDGE MUNI (P08)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 96284 (FAA)  
DEPARTURE PROCEDURE: **Rwys 5,35**, climbing left turn heading 280° to intercept TFD R-063, then via R-063 to TFD VORTAC before proceeding on course.  
**Rwy 17**, climbing right turn heading 240° to intercept TFD R-090, then via R-090 to TFD VORTAC before proceeding on course.  
**Rwy 23**, climb runway heading to intercept TFD R-090, then via R-090 to TFD VORTAC before proceeding on course.

## DAVIS-MONTHAN AFB (KDMA),

TUCSON, AZ  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 14205  
TAKE-OFF MINIMUMS: **Rwy 12**, 5300-3, or standard with minimum climb of 234 ft/NM to 9700.  
DEPARTURE PROCEDURE: **Rwy 12**, climb to 10,000 on track 125°, intercept DMA R-120 for RADAR vectors. **Rwy 30**, climb to 6500 on track 305°, intercept DMA R-312 for RADAR vectors.  
TAKE-OFF OBSTACLES: **Rwy 12**: Terrain 2707' MSL, 37' from DER, 415' left of centerline. Terrain 2707' MSL, 8' from DER, 424' left of centerline. Terrain 2707' MSL, 0' from DER, 500' left of centerline. Pole 45' AGL/2776' MSL, 3511' from DER, 1052' left of centerline. Vehicle 10' AGL/2727' MSL, 1710' from DER, 195' right of centerline. Vehicle 10' AGL/2727' MSL, 1498' from DER, 787' left of centerline. Aircraft tail 39' AGL/2748' MSL, 81' from DER, 572' left of centerline. **Rwy 30**: Terrain 2590' MSL, 34' from DER, 220' left of centerline. Terrain 2592' MSL, 0' from DER, 500' right of centerline. Terrain 2592' MSL, 13' from DER, 493' right of centerline. Pylon 86' AGL/2645' MSL, 3601' from DER, 1209' left of centerline. Pylon 98' AGL/2672' MSL, 4455' from DER, 332' left of centerline. Pylon 98' AGL/2665' MSL, 3771' from DER, 882' left of centerline. Pylon 98' AGL/2664' MSL, 4112' from DER, 606' left of centerline. Pylon 98' AGL/2665' MSL, 3416' from DER, 1169' left of centerline. Pylon 86' AGL/2658' MSL, 3296' from DER, 1373' left of centerline. Terrain 2591' MSL, 0' from DER, 500' left of centerline. Aircraft tail 39' AGL/2635' MSL, 34' inward of DER, 510' right of centerline.

## DELTA, UT

DELTA MUNI (DTA)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 05356 (FAA)  
TAKEOFF MINIMUMS: **Rwy 17**, std. with a min. climb of 412' per NM to 6600, or 1800-3 for climb in visual conditions. Climb in visual conditions NA at night. **Rwy 12**, NA-terrain. **Rwy 30**, NA-airspace.  
DEPARTURE PROCEDURE: **Rwy 17**, climb via DTA VORTAC R-347 to DTA VORTAC, or climb in visual conditions to cross DER southbound at or above 6400, then via DTA VORTAC R-347 to DTA VORTAC, thence...**Rwy 35**, climb via heading 346° to 5800, then climbing left turn via heading 180° and DTA VORTAC R-310 to DTA VORTAC, thence...  
...climb in holding pattern (hold south, left turn, 004° inbound) to cross DTA VORTAC at or above airway MEA for route of flight.  
NOTE: **Rwy 17**, trees 1598' from DER, 62' right of centerline, 60' AGL/4799' MSL.

## DOUGLAS BISBEE, AZ

BISBEE- DOUGLAS INTL (DUG)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 12040 (FAA)  
DEPARTURE PROCEDURE: **Rwys 8,17**, climbing right turn on heading 330° to intercept DUG VORTAC R-286 to 9500. **Rwy 26**, climbing right turn to intercept DUG VORTAC R-286 to 9500. **Rwy 35**, climbing left turn to intercept DUG VORTAC R-286 to 9600.  
NOTE: **Rwy 8**, trees and terrain beginning 145' from DER, 51' left of centerline, up to 8' AGL/4220' MSL. Trees and terrain beginning 22' from DER, 247' right of centerline, up to 13' AGL/4197' MSL. **Rwy 17**, trees and terrain beginning 91' from DER, 76' left of centerline, up to 5' AGL/4118' MSL. Trees and terrain beginning 12' from DER, 146' right of centerline, up to 5' AGL/4115' MSL. **Rwy 26**, tree and terrain beginning 16' from DER, 233' left of centerline, up to 5' AGL/4167' MSL. Trees and terrain beginning 17' from DER, 32' right of centerline, up to 7' AGL/4167' MSL. **Rwy 35**, trees and terrain beginning 118' from DER, 15' left of centerline, up to 6' AGL/4190' MSL. Tree and terrain beginning 75' from DER, 100' right of centerline, up to 11' AGL/4200' MSL.

## DUCHESNE, UT

DUCHESNE MUNI (U69)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 77223 (FAA)  
DEPARTURE PROCEDURE: Climb direct to MTU VORTAC to depart at or above 7200 eastbound or 10000 westbound.

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## ELKO, NV

### ELKO RGNL (EKO)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 5A 11013 (FAA)

TAKEOFF MINIMUMS: **Rwys 12,30**, NA-terrain. **Rwy 5**, std. w/ min. climb of 495' per NM to 8000. **Rwy 23**, 2500-3 or std. w/ min. climb of 340' per NM to 8000.

DEPARTURE PROCEDURE: **Rwy 5**, climb heading 053° to 6000, then climbing right turn direct BQU VOR/DME, then. . . **Rwy 23**, (V32 Southwest) climb heading 233° to 6000, then climbing left turn heading 200° to intercept BQU R-241 (V32). **Rwy 23**, (all others), climb heading 233° to 6000, then climbing left turn direct BQU VOR/DME, then. . .

climb in BQU VOR/DME holding pattern (South, left turns, 340° inbound) to cross BQU VOR/DME at the MEA/MCA/MOCA for direction of flight.

NOTE: **Rwy 5**, trees, poles, and antennas beginning 412' from DER, 131' left of centerline, up to 107' AGL/5207' MSL. Trees poles, antennas and lights beginning 497' from DER, 84' right of centerline, up to 91' AGL/5191' MSL. **Rwy 23**, pole 1244' from DER, 663' left of centerline, 45' AGL/5085' MSL. Signs, poles, road, silo and tree beginning 673' from DER, 171' right of centerline, up to 68' AGL/5132' MSL.

## ELY, NV

### ELY AIRPORT-YELLAND FIELD (ELY)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2 11181 (FAA)  
DEPARTURE PROCEDURE: use ELY DEPARTURE.

## EUREKA, NV

### EUREKA (05U)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 13234 (FAA)

TAKEOFF MINIMUMS: **Rwy 18**, NA-Terrain.  
DEPARTURE PROCEDURE: use MINES (RNAV)  
DEPARTURE.

## FALLON, NV

### FALLON MUNI (FLX)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 10154 (FAA)

DEPARTURE PROCEDURE: **Rwy 21**, climbing right turn. **Rwys 3, 13, 31**, climbing left turn...

...to 9300 direct HZN VORTAC, continue climb in HZN VORTAC holding pattern (West, left turns, 075° inbound) cross HZN VORTAC at or above 9300 before proceeding on course, continue climb to MEA or assigned altitude.

NOTE: **Rwy 3**, vehicle on road 39' from DER, 306' right of centerline, 15' AGL/3971' MSL. Tree 111' from DER, 424' left of centerline 25' AGL/3988' MSL. Tree 364' from DER, 272' right of centerline, 25' AGL/3988' MSL. **Rwy 13**, trees beginning 3' from DER, 494' right of centerline, up to 25' AGL/4021' MSL. Vehicle on road beginning 22' from DER, 80' left of centerline, up to 15' AGL/3978' MSL. **Rwy 21**, vehicle on road 477' from DER, 241' left of centerline, 15' AGL/3984' MSL. Tree 710' from DER, 75' left of centerline, 25' AGL/3994' MSL. **Rwy 31**, trees beginning 52' from DER, 159' right of centerline, up to 25' AGL/3975' MSL. Trees beginning 111' from DER, 140' left of centerline, up to 25' AGL/3981' MSL.

## FALLON NAS(VAN VOORHIS FLD)(KNFL)

FALLON, NV  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
15008

TAKE-OFF MINIMUMS: **Rwy 13L/R**, Diverse departures authorized 131° CW 311°, standard with minimum climb rate of 245 ft/NM to 7200. **Rwy 31L/R**, Diverse departures authorized 131° CW 083°, standard with minimum climb rate of 252 ft/NM to 9800. **Rwy 7**, Diverse departures authorized, standard with minimum climb rate of 295 ft/NM to 12,200. **Rwy 25**, Diverse departures authorized 132° CW 073°, standard with minimum climb rate of 250 ft/NM to 12,200.

TAKE-OFF OBSTACLES: **Rwy 31R**, tower 766' from DER, 459' left of centerline, 18' AGL/3950' MSL.

## FILLMORE, UT

### FILLMORE MUNI (FOM)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 10322 (FAA)

TAKEOFF MINIMUMS: **Rwy 4**, std. w/ min. climb of 250' per NM to 6200, or 1800-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 4**, climbing left turn to 9600 on DTA R-141 to DTA VORTAC, climb in DTA VORTAC holding pattern (South, left turns, 004° inbound) to cross DTA VORTAC at or above MEA for route of flight or for climb in visual conditions cross Fillmore Muni airport Northwest bound at or above 6600, then climb to 9600 on DTA R-146 to DTA VORTAC. Continue climb in DTA VORTAC holding pattern (South, left turns, 004° inbound) to cross DTA VORTAC at or above MEA for route of flight. **Rwy 22**, climbing right turn to 9600 on DTA R-152 to DTA VORTAC, climb in DTA VORTAC holding pattern (South, left turns, 004° inbound) to cross DTA VORTAC at or above MEA for route of flight.

NOTE: **Rwy 4**, light 60' from DER, 393' left of centerline, 8' AGL/4987' MSL. Windssock 129' from DER, 301' left of centerline, 21' AGL/5000' MSL. Rising terrain 132' from DER, 385' right of centerline, 4989' MSL. Fence beginning 138' from DER, 174' right of centerline, up to 15' AGL/4996' MSL. Buildings beginning 259' from DER, 455' right of centerline, up to 13' AGL/5012' MSL. Beacon 311' from DER, 505' left of centerline, 52' AGL/5031' MSL. Trees beginning 333' from DER, 242' left of centerline, up to 37' AGL/5034' MSL. Vehicle on road beginning 472' from DER, 608' left to 1093' right of centerline, up to 35' AGL/5073' MSL. Pole 488' from DER, 620' left of centerline, 38' AGL/5037' MSL. Windmeter, 623' from DER, 342' left of centerline, 9' AGL/5008' MSL. Building 873' from DER, 196' left of centerline, 17' AGL/5016' MSL. **Rwy 22**, fence 97' from DER, 302' left of centerline, 15' AGL/4916' MSL. Vehicle on road beginning 228' from DER, 398' left of centerline, up to 9' AGL/4928' MSL.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## FLAGSTAFF, AZ

FLAGSTAFF PULLIAM (FLG)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2A 14037 (FAA)

DEPARTURE PROCEDURE: **Rwy 3**, turn right.

**Rwy 21**, turn left. Aircraft departing FLG R-160 CW R-175 climb on course. All others climb southbound on FLG R-172 to 9000, then climbing left turn direct FLG VOR/DME.

NOTE: **Rwy 21**, trees beginning 73' from DER, left and right of centerline, up to 85' AGL/7065' MSL.

## FORT HUACHUCA-SIERRA VISTA, AZ

SIERRA VISTA MUNI-LIBBY AAF (FHU)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 3 13346 (FAA)

TAKEOFF MINIMUMS: **Rwy 21**, NA - Terrain. **Rwy 26**, std. w/min. climb of 330' per NM to 7300.

DEPARTURE PROCEDURE: **Rwys 3,8,12**, climbing left turn, thence...

**Rwys 26,30**, climbing right turn, thence...

... **All aircraft**, intercept FHU VOR/DME R-021 or bearing 018° from DAO NOB to TOMBS INT, continue climb in TOMBS holding pattern (hold N, left turns, 201° inbound to FHU VOR/DME or 198° inbound to DAO NDB) to 9500 before proceeding on course.

NOTE: **Rwy 3**, trees 253' from DER, 130' left of centerline, 10' AGL/4595' MSL. Tree 199' from DER, 271' right of centerline, 10' AGL/4595' MSL. **Rwy 8**, reflector 121' from DER, 174' right of centerline, 4' AGL/4603' MSL. **Rwy 12**, terrain beginning 22' from DER, 93' right of centerline, up to 4639' MSL. **Rwy 26**, reflector and terrain beginning 102' from DER, 173' left of centerline, up to 4' AGL/4747' MSL. Reflector 101' from DER 173' right of centerline, 4' AGL/4723' MSL. **Rwy 30**, multiple bushes beginning 334' from DER, 112' left of centerline, up to 15' AGL/4626' MSL. Bush 132' from DER, 198' right of centerline, 16' AGL/4627' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)  
ORIG 14317 (FAA)

**Rwys 3,12**, heading as assigned by ATC. **Rwy 8**, heading as assigned by ATC. Requires minimum climb of 300' per NM to 8600. **Rwy 26**, heading as assigned by ATC. Requires minimum climb of 330' per NM to 8100. **Rwy 30**, heading as assigned by ATC. Requires minimum climb of 330' per NM to 8700.

## GLENDALE, AZ

GLENDALE MUNI (GEU)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 14317 (FAA)

DEPARTURE PROCEDURE: Use DRAKE (RNAV)  
DEPARTURE.

## GLOBE, AZ

SAN CARLOS APACHE (P13)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2 08101 (FAA)  
DEPARTURE PROCEDURE: Use IZTIR DEPARTURE.

## GOODYEAR, AZ

PHOENIX GOODYEAR (GYR)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 14317 (FAA)  
DEPARTURE PROCEDURE: Use POTER (RNAV)  
DEPARTURE.

## GRAND CANYON, AZ

GRAND CANYON NATIONAL PARK (GCN)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 07242 (FAA)  
TAKEOFF MINIMUMS: **Rwy 3**, NA-environmental.  
DEPARTURE PROCEDURE: **Rwy 21**, use GRAND  
DEPARTURE.

## VALLE (40G)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 14621 (FAA)  
DEPARTURE PROCEDURE: **Rwy 1**, Climb on a heading between 188° CW to 091° from DER. **Rwy 19**, climb on a heading between 170° CW to 008° from DER.

## HEBER, UT

HEBER CITY MUNI-RUSS MCDONALD  
FIELD (36U)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 3A 14149 (FAA)

TAKEOFF MINIMUMS: **Rwys 4, 22**, 5800-3 for climb in visual conditions. Climb in visual conditions NA at night. DEPARTURE PROCEDURE: **Rwy 4**, for climb in visual conditions, cross Heber City Muni-Russ McDonald Field at or above 11300 MSL before proceeding on course. When executing VCOA, notify ATC prior to departure.

**Rwy 22**, for climb in visual conditions, cross Heber City Muni-Russ McDonald Field at or above 11300 MSL before proceeding on course. When executing VCOA, notify ATC prior to departure.

NOTE: **Rwy 4**, multiple trees, bushes, poles, buildings, vehicles, terrain, sign, fence, and wind sock beginning 20' from DER, left and right of centerline, up to 100' AGL/5708' MSL. **Rwy 22**, multiple trees beginning 608' from DER, left and right of centerline, up to 100' AGL/6411' MSL. Multiple bushes, poles, terrain and fence beginning 12' from DER, 225' left of centerline, up to 25' AGL/6344' MSL.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## HILL AFB (KHIF)

OGDEN, UT

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

Diverse departures not authorized, use radar vectors or published Departure Procedures (DP) for obstacle avoidance.

## HUNTINGTON, UT

HUNTINGTON MUNI (69V)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 2A 09295 (FAA)

TAKEOFF MINIMUMS: **Rwys 18, 26, 36**, NA. **Rwy 30**, 1700-3 or std. with a min. climb of 300' per NM to 8100.

DEPARTURE PROCEDURE: **Rwys 8, 12**, climbing left turn direct PUC VOR/DME...

**Rwy 30**, climbing right turn direct PUC VOR/DME....

...continue climb in PUC VOR/DME holding pattern (hold S, right turns, 009° inbound) to MEA for direction of flight.

NOTE: **Rwy 8**, tree 2663' from DER, 922' left of centerline, 40' AGL/5979' MSL. **Rwy 12**, tree 333' from DER, 132' right of centerline, 40' AGL/5919' MSL. **Rwy 30**, tree 2065' from DER, 875' left of centerline, 40' AGL/5999' MSL.

## KANAB, UT

KANAB MUNI (KNB)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 3 10042 (FAA)

TAKEOFF MINIMUMS: **Rwy 1**, std. with min. climb of 742' per NM to 6600, or 1100-3 with min. climb of 535' per NM to 6900, or 2400-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 19**, climb heading 171° to 6800 before turning. **Rwy 1**, climb heading 006° to 6100 before turning, or for climb in visual conditions, cross Kanab Muni airport at or above 7100 before proceeding on course.

NOTE: **Rwy 1**, vent on building 554' from DER, 370' left of centerline, 16' AGL/4884' MSL. Trees beginning 1138' from DER, 302' left of centerline, up to 100' AGL/5939' MSL. Rising terrain and trees beginning 1.68 NM from DER, 247' right of centerline, up to 100' AGL/5239' MSL. Rising terrain and trees beginning 1.76 NM from DER, 766' left of centerline, up to 100' AGL/5599' MSL. Rising terrain beginning 3.5 NM from DER, left and right of centerline, up to 6359' MSL. **Rwy 19**, trees beginning 271' from DER, 506' right of centerline, up to 100' AGL/4899' MSL.

## KINGMAN, AZ

KINGMAN (IGM)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

TAKEOFF MINIMUMS: **Rwys 3,17,21,35**, 800-1 or std. with a min. climb of 210' per NM to 7000.

DEPARTURE PROCEDURE: Climb northbound on IGM R-010 until reaching 6000; reverse course to the left and continue climb to 9000 direct to IGM. If unable to cross IGM at 9000 continue climb in IGM holding pattern (SW, left turns, 027° inbound).

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

## LAGUNA AAF (LGF)

YUMA PROVING GROUND, AZ (03247)

**Rwy 6, 18, 36**, turn right, climb to 3600 direct BZA VORTAC.

**Rwy 24**, climb to 3600 direct to BZA VORTAC.

TAKEOFF OBSTACLES:

**Rwy 18, 386'** (6' AGL) windssock, 818' from DER, 194' left of centerline.

## LAKE HAVASU CITY, AZ

LAKE HAVASU CITY (HII)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 2 12152 (FAA)

TAKEOFF MINIMUMS: **Rwy 14**, std. w/min. climb of 465' per NM to 4800, or 1500-3 for climb in visual conditions.

**Rwy 32**, 600-1¾ w/ min. climb of 492' per NM to 1100, or 1500-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 14**, climbing right turn heading 300° to intercept EED VORTAC R-155 to EED VORTAC, continue climb in EED VORTAC holding pattern (East, right turns, 257° inbound) to cross EED VORTAC at or above 6100 before proceeding on course or ...

**Rwy 32**, climbing left turn heading 290° to intercept EED VORTAC R-155 to EED VORTAC, continue climb in EED VORTAC holding pattern (East, right turns, 257° inbound) to cross EED VORTAC at or above 6100 before proceeding on course or ...

**Rwys 14, 32**, ... For climb in visual conditions: cross Lake Havasu City airport northwest bound at or above 2300, then Intercept EED VORTAC R-138 to EED VORTAC, continue climb in EED VORTAC holding pattern (East, right turns, 257° inbound) to cross EED VORTAC at or above 6100 before proceeding on course. When executing VCOA, notify ATC prior to departure.

NOTE: **Rwy 14**, pole 3327' from DER, 46' right of centerline, 107' AGL/868' MSL. Poles 3468' from DER, 195' left of centerline, up to 107' AGL/890' MSL. Trees/bushes 976' from DER, 380' left of centerline, up to 46' AGL/829' MSL. Terrain 143' from DER, 346' left of centerline, up to 804' MSL. **Rwy 32**, trees 1544' from DER, 416' right of centerline, up to 44' AGL/793' MSL.

## LAS VEGAS, NV

HENDERSON EXECUTIVE (HND)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

ORIG 05132 (FAA)

TAKEOFF MINIMUMS: **Rwy 17L/R**, Cat A/B std. with a min. climb of 491' per NM to 6000, or 2100-3 for climb in visual conditions, Cat C/D NA. **Rwy 35L/R**, Cat A/B std. with a min. climb of 312' per NM to 4700, or 2100-3 for climb in visual conditions, Cat C/D NA.

DEPARTURE PROCEDURE: **Rwy 17L/R**, climbing right turn via LAS R-157 to LAS VORTAC before proceeding on course, or for climb in visual conditions: Cross Henderson Executive Airport eastbound at or above 4500, then via BLD R-249 to BLD VORTAC. **Rwy 35L/R**, climbing right turn via BLD R-257 to BLD VORTAC before proceeding on course, or for climb in visual conditions: Cross Henderson Executive Airport eastbound at or above 4500, then via BLD R-249 to BLD VORTAC.

NOTE: **Rwy 17L**, tree 5610' from DER, 82' left of centerline, 100' AGL/2739' MSL. Tree 1.9 miles from DER, 1495' left of centerline, 100' AGL/2859' MSL. **Rwy 17R**, tree 4041' from DER, 859' left of centerline, 100' AGL/2739' MSL.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## LAS VEGAS, NV (CON'T)

### MCCARRAN INTL (LAS)

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 6 10210 (FAA)

TAKEOFF MINIMUMS: **Rwys 19L/R**, std. w/ min. climb of 210' per NM to 2600. **Rwy 25R**, 300-2 or standard with a minimum climb of 230' per NM to 2600.

DEPARTURE PROCEDURE: **Rwys 1L/R**, climbing right turn direct BLD VORTAC before proceeding on course.

**Rwys 7L/R**, climb heading 075° to 3700, then climbing right turn direct BLD VORTAC before proceeding on course. **Rwys 25 L/R**, climb heading 255° to 2800, then climbing right turn direct BLD VORTAC before proceeding on course. **Rwys 19 L/R**, climbing left turn via heading 120° and BLD R-257 direct BLD VORTAC before proceeding on course.

NOTE: **Rwy 1L**, building 1508' from DER, 463' left of centerline, 71' AGL/2146' MSL. Pole 453' from DER, 283' left of centerline, 38' AGL/2118' MSL. Sign 1042' from DER, 694' left of centerline, 35' AGL/2124' MSL. **Rwys 7L/R**, sign 1331' from DER, 448' right of centerline, 60' AGL/2120' MSL. Vents 604' from DER, 539' right of centerline, up to 17' AGL/2095' MSL. **Rwy 7L**, trees 761' from DER, left and right of centerline, up to 42' AGL/2074' MSL. Pole 747' from DER, 442' right of centerline, 25' AGL/2057' MSL. **Rwy 7R**, tower 1457' from DER, 847' right of centerline, 65' AGL/2096' MSL. **Rwy 19L**, multiple buildings, trees and poles 1394' from DER, 251' right of centerline, up to 96' AGL/2284' MSL. Sign 2181' from DER, 1062' right of centerline, 36' AGL/2236' MSL. **Rwy 19R**, trees 1563' from DER, 329' left of centerline, up to 55' AGL/ 2236' MSL. Multiple buildings, signs and poles 197' from DER, 59' right of centerline, up to 75' AGL/2291' MSL. **Rwy 25L**, multiple poles, sign and buildings 1003' from DER, 145' left of centerline, up to 97' AGL/2291' MSL. Tree 2837' from DER, 1008' left of centerline, 72' AGL/2230' MSL. Railroad 2564' from DER, 773' left of centerline, 66' AGL/2223' MSL.

**Rwy 25R**, multiple poles and trees 533' from DER, 1' left of centerline, up to 271' AGL/2457' MSL. Building 1822' from DER, 652' left of centerline, 59' AGL/2238' MSL. Roads 669' from DER, 17' right of centerline, up to 29' AGL/2208' MSL.

## NORTH LAS VEGAS (VGT)

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 3 08045 (FAA)

DEPARTURE PROCEDURE: Use BOULDER CITY DEPARTURE.

## LOGAN, UT

### LOGAN-CACHE (LGU)

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 8 09351 (FAA)

TAKEOFF MINIMUMS: **Rwys 10,28**, NA-obstacles. DEPARTURE PROCEDURE: **Rwys 17, 35**, use ORNEY DEPARTURE.

## LOVELOCK, NV

### DERBY FIELD (LOL)

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

ORIG-B 11349 (FAA)

TAKEOFF MINIMUMS: **Rwy 2**, 2300-2 or std. with a min. climb of 300' per NM to 2600. **Rwy 8**, 1100-1 or std. with a min. climb of 250' per NM to 5000. **Rwys 20, 26**, 2300-2 or std. with a min. climb of 260' per NM to 6200. DEPARTURE PROCEDURE: **Rwy 2**, turn right.

**Rwys 8,20,26**, turn left, climb direct LLC VORTAC. Aircraft departing 330° CW 359° climb via LLC R-333 to ROBUD INT; 360° CW 089° climb in LLC VORTAC holding pattern (hold NW, left turns, 153° inbound) to depart LLC VORTAC at or above 8600; 090° CW 219° climb on course; 220° CW 329° climb in LLC VORTAC holding pattern to depart LLC VORTAC at or above 8600. Continue climb on course to MEA or assigned altitude.

## LUKE AFB (KLUF),

### GLENDALE, AZ

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 4 14009

DEPARTURE PROCEDURE: **Rwy 3L, 3R**, Climb heading 030° to LUF 4 DME, then climbing left turn on a heading between 320° CW to 360° from DER. Expect RADAR vectors on course from Luke RAPCON. **Rwy 21L, 21R**, Climb heading 210° to LUF 8 DME, then climb on a heading between 180° CW to 222° from DER. Expect RADAR vectors on course from Luke RAPCON.

TAKE-OFF OBSTACLES: **Rwy 3L**: Taxiing aircraft, 19' AGL/1123' MSL, 1221' from DER, 782' left of centerline. Taxiing aircraft, 19' AGL/1123' MSL, 1407' from DER, 609' left of centerline. **Rwy 21L**: Taxiing aircraft, 38' AGL/1117' MSL, 1428' from DER, 774' left of centerline.

## MARANA, AZ

### MARANA RGNL(AVQ)

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

ORIG-A 13234 (FAA)

TAKEOFF MINIMUMS: **Rwys 3, 12**, N/A-Obstacles DEPARTURE PROCEDURE: **Rwy 21**, climb to 6500 via heading 360° and TUS R-308 to TOTEC Int/TUS 57 DME, then as filed. **Rwy 30**, climb to 6500 via heading 303° intercept TUS R-308 above 3500, to TOTEC INT/ TUS 57 DME, then as filed.

NOTE: **Rwy 21**, road 53' from DER, 413' left of centerline, 15' AGL/2035' MSL. Tree 800' from DER, 695' left of centerline, 32' AGL/2043' MSL. Multiple trees and poles beginning 518' from DER, 190' right of centerline, up to 38' AGL/2049' MSL. **Rwy 30**, multiple trees beginning 148' from DER, 275' right of centerline, up to 19' AGL/2020' MSL.

## MESA, AZ

### FALCON FIELD (FFZ)

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 4 10210 (FAA)

DEPARTURE PROCEDURE: use MESA DEPARTURE.

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

**MICHAEL AAF (KDPG),  
DUGWAY PROVING  
GROUND, UT  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2 12236**

DEPARTURE PROCEDURES: **Rwy 12**, Climb heading 122° to 5700, then climbing right turn on a heading between 202° CW to 302° to 10,000 before proceeding on course. **Rwy 30**, Climbing left turn on a heading between 267° CW to 300° to 10,000 before proceeding on course.

## MILFORD, UT

**MILFORD MUNI/BEN AND JUDY  
BRISCOE FIELD (MLF)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2 12096 (FAA)**

TAKEOFF MINIMUMS: **Rwy 34**, std. w/min. climb of 487' per NM to 6500 or 1500-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 16**, climb direct MLF VORTAC, thence ...

... Aircraft departing on V235 or V21 southbound proceed on course.

... All other aircraft climb to 11000 on MLF VORTAC R-168, then right turn direct MLF VORTAC. Continue climb-in-hold, right turns, 348° inbound to cross MLF VORTAC at or above MEA/MCA for route of flight. **Rwy 34**, climbing left turn to intercept MLF VORTAC R-310 to MLF VORTAC, thence...

... Aircraft departing on V235 or V21 southbound; proceed on course.

... All other aircraft, climb-in-hold, MLF VORTAC, right turns, 348° inbound to cross MLF VORTAC at or above MEA/MCA for Route of flight.

... or climb in visual conditions to cross Milford Muni/Ben and Judy Briscoe Field airport southbound at or above 6400, then climb on MLF VORTAC R-345 to MLF VORTAC. Aircraft departing on V235 and V21 southbound; proceed on course. All other aircraft climb to 11000 on MLF VORTAC R-168, then, right turn direct MLF VORTAC. Continue climb-in-hold, right turns, 348° inbound to cross MLF VORTAC at or above MEA/MCA for route of flight.

NOTE: **Rwy 16**, trees beginning 440' from DER, 332' right of centerline, up to 100' AGL/5159' MSL. Trees beginning 4912' from DER, 1451' right of centerline, up to 100' AGL/5179' MSL. **Rwy 34**, vehicles on roadway 231' from DER, across centerline, up to 15' AGL/5054' MSL. Trees beginning 3177' from DER, 508' left of centerline, up to 100' AGL/5119' MSL.

## MINDEN, NV

**MINDEN-TAHOE (MEV)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2 11349 (FAA)**

TAKEOFF MINIMUMS: **Rwys 12,16,30**, NA - Obstacles.

DEPARTURE PROCEDURE: **Rwy 34**, use MINDEN (RNAV) DEPARTURE.

## MOAB, UT

**CANYONLANDS FIELD (CNY)  
TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE  
PROCEDURES  
AMDT 3A 14037 (FAA)**

TAKEOFF MINIMUMS: **Rwy 3**, std. with a min. climb of 320' per NM to 5800. **Rwy 21**, std. with a min. climb of 330' per NM to 5400.

DEPARTURE PROCEDURE: **Rwy 3**, turn left, thence... **Rwy 21**, turn right, thence...

...climb to 6700 on OAB R-293, then climbing right turn direct OAB VOR/DME. Climb in OAB holding pattern (NW, left turns, 113° inbound) to 10000 then proceed on course.

NOTE: **Rwy 3**, tree 4383' from DER, 1507' right of centerline, 50' AGL/4729' MSL. Road 1749' from DER, 905' left of centerline, 15' AGL/4635' MSL. Tree 3914' from DER, 1166' right of centerline, 50' AGL/4690' MSL. Tree 1.25 NM from DER, 400' right of centerline, 50' AGL/4758' MSL. **Rwy 21**, pole 2061' from DER, 78' right of centerline, 80' AGL/4625' MSL. Pole 2061' from DER, 40' right of centerline, 80' AGL/4625' MSL. Pole 2095' from DER, 857' right of centerline, 80' AGL/4623' MSL. Pole 1980' from DER, 344' right of centerline, 80' AGL/4602' MSL.

## NELLIS AFB (KLSV)

**LAS VEGAS, NV TAKEOFF MINIMUMS AND  
(OBSTACLE) DEPARTURE PROCEDURES  
ORIG 12320**

Rwy 3L/R, 10,200-3\* SR-SS

Rwy 21L/R, 10,200-3\* SR-SS

Diverse departure not authorized.

**MILITARY:** Use published DP, if unable to comply with DP climb gradient file appropriate DP for intended destination and notify clearance delivery and request RADAR Vectors (Climb Gradient of 300' per NM until 12,000 for RADAR Vectors). If unable to comply with RADAR Vector climb gradient, A/C must depart VFR.

\* **CIVIL:** Use published DP, if unable to comply with DP climb gradient file appropriate DP for intended destination and notify clearance delivery and request RADAR Vectors (Climb Gradient of 330' per NM until 12,000 for RADAR Vectors). If unable to comply with RADAR Vectors climb gradient, A/C may use published weather minimums or depart VFR.

TAKE-OFF OBSTACLES: **RWY 3L:** Terrain 0' AGL/1869' MSL, 0' from DER, 303' left of centerline. Terrain 0' AGL/1870' MSL, 0' from DER, 500' left of centerline. Road 15' AGL/1914' MSL, 1322' from DER, 801' left of centerline. **RWY 3R:** C-5 on taxiway 65' AGL/1934' MSL, 1346' from DER, 821' right of centerline. Road 15' AGL/1994' MSL, 3930' from DER, 1403' right of centerline. **RWY 21L:** Trees 90' AGL/1929' MSL, 4596' from DER, 1595' right of centerline. Trees 90' AGL/1929' MSL, 4942' from DER, 540' right of centerline. Trees 60' AGL/1879' MSL, 931' from DER, 725' left of centerline. Trees 52' AGL/1881' MSL, 2069' from DER, 693' left of centerline. Trees 42' AGL/1863' MSL, 1642' from DER, 744' left of centerline. Trees 45' AGL/1861' MSL, 1377' from DER, 737' left of centerline. Trees 35' AGL/1855' MSL, 1011' from DER, 662' left of centerline. Trees 47' AGL/1868' MSL, 1846' from DER, 844' left of centerline. Trees 38' AGL/1858' MSL, 826' from DER, 760' left of centerline. Trees 60' AGL/1879' MSL, 948' from DER, 627' left of centerline. Trees 60' AGL/1879' MSL, 2722' from DER, 342' left of centerline. **RWY 21R:** Terrain 0' AGL/1834' MSL, 23' from DER, 471' right of centerline. Trees 90' AGL/1929' MSL, 4596' from DER, 596' right of centerline. Building 45' AGL/1884' MSL, 2276' from DER, 1036' right of centerline. Road 15' AGL/1854' MSL, 1406' from DER, 465' right of centerline. Terrain 0' AGL/1835' MSL, 0' from DER, 500' right of centerline. Building 38' AGL/1868' MSL, 2160' from DER, 1077' right of centerline. Tower 100' AGL/1938' MSL, 1462' from DER, 1135' right of centerline. Tower 100' AGL/1939' MSL, 1157' from DER, 1135' right of centerline.

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## NEPHI, UT

NEPHI MUNI (U14)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 11293 (FAA)  
DEPARTURE PROCEDURE: Use NEPHI  
DEPARTURE.

## NOGALES, AZ

NOGALES INTL (OLS)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2 09351 (FAA)  
TAKEOFF MINIMUMS: Use NOGALES DEPARTURE.

## OGDEN, UT

OGDEN-HINCKLEY (OGD)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2 08101 (FAA)  
TAKEOFF MINIMUMS: **Rwys 7,16**, NA- Obstacles.  
DEPARTURE PROCEDURE: **Rwys 3, 21, 25, 34**, Use  
EMONT DEPARTURE.

## PAGE, AZ

PAGE MUNI (PGA)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 2 08045 (FAA)  
TAKEOFF MINIMUMS: **Rwys 7, 25**, NA – obstacles  
**Rwy 15**, 300-1 or std. w/ min. climb of 252' per NM to  
6500, or 1900-3 for climb in visual conditions.  
DEPARTURE PROCEDURE: **Rwy 15**, climb via 157°  
heading to 6000, then climbing right turn to PGA VOR/  
DME, cross PGA VOR/DME at or above 7700.  
Continue climb in PGA VOR/DME holding pattern  
(hold NW, right turns, 147° inbound) to airway MEA, or  
climb in visual conditions: cross Page airport at or  
above 6100, before proceeding on course. **Rwy 33**,  
climb via 337° heading to 6000, then climbing left turn  
to PGA VOR/DME. Cross PGA VOR/DME at or above  
7700. Continue climb in PGA VOR/DME holding  
pattern (hold NW, right turns, 147° inbound) to airway  
MEA.

NOTE: **Rwy 15**, terrain 192' from DER, 274' right of  
centerline, 4323' MSL, tree 1.07 NM from DER, 167'  
left of centerline, 4519 MSL, transmission lines 1.96  
NM from DER, 825' left of centerline, 100' AGL/4519'  
MSL, power line 4.00 NM from DER, 3606' right of  
centerline, 75' AGL/4819' MSL, power line 4.35 NM  
from DER, 3968' right of centerline, 75' AGL/4919'  
MSL, power line 5.36 NM from DER, 5039' right of  
centerline, 75' AGL/5119' MSL, power line 4.51 NM  
from DER, 4136' right of centerline, 75' AGL/5019'  
MSL, tree 4.52 NM from DER, 1508' right of centerline,  
100' AGL/5173' MSL, AAO 4.58 NM from DER, 1617'  
right of centerline, 200' AGL/5187' MSL, AAO 5.15  
NM from DER, 4456' left of centerline, 200' AGL/5190'  
MSL, tree 5.56 NM from DER, 4097' right of centerline,  
30' AGL/5249' MSL, AAO 5.98 NM from DER, 653' left  
of centerline, 200' AGL/5440' MSL.

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

## PANGUITCH, UT

PANGUITCH MUNI (U55)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 11153 (FAA)  
TAKEOFF MINIMUMS: **Rwy 18**, std. w/min. climb of 350'  
per NM to 9200 or 2200-3 for climb in visual conditions.  
**Rwy 36**, std. w/min. climb of 450' per NM to 9500 or 2200-  
3 for climb in visual conditions.  
DEPARTURE PROCEDURE: **Rwy 18**, climb heading 185°  
to 9200 then left turn to intercept BCE VORTAC R-274,  
continue climb to 12000 to BCE VORTAC, or for climb in  
visual conditions: cross Panguitch Muni Airport southeast  
bound at or above 8800' MSL then via BCE R-320 to BCE  
VORTAC thence ... **Rwy 36**, climb heading 005° to 9500  
then left turn to intercept BCE VORTAC R-323 (V257),  
continue climb to 12000 to BCE VORTAC, or for climb in  
visual conditions: cross Panguitch Muni Airport southeast  
bound at or above 8800' MSL then via BCE R-320 to BCE  
VORTAC thence...  
...continue climb in BCE VORTAC holding pattern (hold  
southwest, right turn, 045° inbound) to cross BCE  
VORTAC at or above MEA for route of flight.

NOTE: **Rwy 36**, terrain 64' from DER, 426' right of  
centerline, 6775' MSL. Terrain 426' from DER, 565' right of  
centerline, 6779' MSL. **Rwy 18**, terrain beginning 114'  
from DER, 306' left of centerline, 6758' MSL. Terrain 26'  
from DER, 229' left of centerline 6756' MSL. Terrain 388'  
from DER, 91' left of centerline 6766' MSL. Terrain 316'  
from DER, 321' left of centerline 6766' MSL.

## PARKER, AZ

AVI SUQUILLA (P20)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 14261 (FAA)  
TAKEOFF MINIMUMS: **Rwy 1**, std. w/min. climb of 275' per  
NM to 2700 or 1800-2½ for VCOA.  
DEPARTURE PROCEDURE: **Rwy 1**, climb heading 012°  
to 1400 then climbing right turn to intercept PKE VORTAC  
R-067 to PKE VORTAC. **Rwy 19**, climbing right turn to  
intercept PKE VORTAC R-067 to PKE VORTAC.  
VCOA: **Rwy 1**, obtain ATC approval for VCOA when  
requesting IFR clearance. Climb in visual conditions to  
cross Avi Suquilla airport at or above 2100 then proceed  
on PKE R-067 to PKE VORTAC.

## PAYSON, AZ

PAYSON (PAN)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1A 12320 (FAA)  
TAKEOFF MINIMUMS: **Rwy 6**, std. w/ min. climb of 360'  
per NM to 9300, or 2500-3 for climb in visual conditions.  
**Rwy 24**, std. w/ min. climb of 375' per NM to 9300, or  
2500-3 for climb in visual conditions.  
DEPARTURE PROCEDURE: **Rwys 6, 24**, for climb in  
visual conditions: Cross Payson Airport at or above 7500  
MSL before proceeding on course. When executing  
VCOA, notify ATC prior to departure.  
NOTE: **Rwy 6**, tree 197' from DER, 118' right of centerline,  
up to 12' AGL/5170' MSL. Bush 83' from DER, 99' right of  
centerline, up to 3' AGL/5161' MSL. **Rwy 24**, bush 15'  
from DER, 133' right of centerline, 6' AGL/5148' MSL.  
Tree 320' from DER, 183' right of centerline, 12'  
AGL/5154' MSL. Fence 85' from DER, 84' left of  
centerline, 4' AGL/5141' MSL. Tree 164' from DER, 126'  
left of centerline, 9' AGL/5147' MSL.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## PHOENIX, AZ

PHOENIX-DEER VALLEY (DVT)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 5 05300 (FAA)  
DEPARTURE PROCEDURE: Use DEER VALLEY  
DEPARTURE.

DIVERSE VECTOR AREA (RADAR VECTORS)  
ORIG 14317 (FAA)

**Rwys 25L, 25R**, heading as assigned by ATC; requires  
minimum climb of 370' per NM to 4600.

## PHOENIX SKY HARBOR INTL (PHX)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 6 14261 (FAA)

TAKEOFF MINIMUMS: **Rwy 26**, 600-2¾ or std. w/min. climb  
of 326' per NM to 1900.

DEPARTURE PROCEDURE: **Rwys 7L, 7R, 8**, climb  
heading 078° to 3000, then climbing right turn direct PXR  
VORTAC. **Rwys 25L, 25R**, climb heading 258° to 1900  
then climbing right turn to join PXR R-260 (V16)  
westbound, climb to 5000. **Rwy 26**, climb heading 258° to  
1550, then join PXR R-260 (V16) westbound, climb to  
5000. Westbound departures continue climb on PXR R-  
260. All others, climbing right turn direct PXR VORTAC.

NOTE: **Rwy 7R**, transmission towers and power lines, 3201'  
from DER, 1122' right of centerline, up to 131' AGL/1260'  
MSL. **Rwy 8**, multiple light poles, beginning 2539' from  
DER, 900' left of centerline, up to 82' AGL/1234' MSL. Light  
pole, 1639' from DER, 793' right of centerline, 46'  
AGL/1177' MSL. **Rwy 25L**, multiple light poles, beginning  
681' from DER, 521' left of centerline, up to 63' AGL/1166'  
MSL. Sign, 902' from DER, 711' left of centerline, 64'  
AGL/1170' MSL. Multiple light poles, beginning 1519' from  
DER, 535' left of centerline, up to 99' AGL/1201' MSL.  
Multiple light poles, beginning 1919' from DER, 598' left of  
centerline, up to 90' AGL/1192' MSL. **Rwy 26**, pole, 42'  
from DER, 440' left of centerline, 26' AGL/1135' MSL.  
Fence, 176' from DER, 547' left of centerline, 11'  
AGL/1120' MSL. Pole, 315' from DER, 499' left of  
centerline, 11' AGL/1120' MSL. Tree, 763' from DER, 642'  
left of centerline, 24' AGL/1135' MSL. Pole, 1959' from  
DER, 923' left of centerline, 59' AGL/1163' MSL. Pole,  
2312' from DER, 318' left of centerline, 66' AGL/1169' MSL.  
Pole, 2336' from DER, 578' left of centerline, 67' AGL/1170'  
MSL. Pole, 78' from DER, 456' right of centerline, 32'  
AGL/1142' MSL. Pole, 82' from DER, 64' right of centerline,  
18' AGL/1127' MSL. Tree, 118' from DER, 294' right of  
centerline, 22' AGL/1133' MSL. Tree, 239' from DER, 214'  
right of centerline, 22' AGL/1133' MSL. Tree, 414' from  
DER, 522' right of centerline, 24' AGL/1135' MSL. Sign,  
520' from DER, 567' right of centerline, 16' AGL/1125'  
MSL. Pole, 2301' from DER, 193' right of centerline, 69'  
AGL/1171' MSL. Pole, 2302' from DER, 661' right of  
centerline, 68' AGL/1171' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 2 14317 (FAA)

**Rwys 7L, 7R, 8**, heading as assigned by ATC. **Rwy 25L**,  
heading as assigned by ATC; requires minimum climb of  
305' per NM to 6000. **Rwy 25R**, heading as assigned by  
ATC; requires minimum climb of 325' per NM to 6000. **Rwy**  
**26**, heading as assigned by ATC; requires minimum climb  
of 300' per NM to 6000.

## PHOENIX, AZ (CON'T)

PHOENIX-MESA GATEWAY (IWA)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 10042 (FAA)  
DEPARTURE PROCEDURE: use PHOENIX  
DEPARTURE.

## PRESCOTT, AZ

ERNEST A LOVE FIELD (PRC)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 4 14093 (FAA)  
DEPARTURE PROCEDURE: Use PRESCOTT  
DEPARTURE.

## PRICE, UT

CARBON COUNTY RGNL/BUCK DAVIS  
FIELD (PUC)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 5 15064 (FAA)

TAKEOFF MINIMUMS: **Rwy 1**, std. w/min. climb of  
400' per NM to 6800 or 3300-3 for climb in visual  
conditions. **Rwy 3, NA** - obstacles. **Rwy 33**, std. w/  
min. climb of 370' per NM to 6700 or 3300-3 for climb  
in visual conditions.

DEPARTURE PROCEDURE: **Rwy 1**, climb to 6400  
then climbing right turn on a heading between 144°  
CW to 187°, maintain 210 KIAS until completion of  
turn, thence . . .

**Rwy 15**, climb on a heading between 129° CW to  
196°, thence . . .

**Rwy 19**, climb on a heading between 195° CCW to  
128°, thence . . .

**Rwy 26**, climb on a heading between 179° CCW to  
127°, thence . . .

**Rwy 33**, climb to 6300 then climbing left turn on a  
heading between 178° CCW to 148°, thence . . .  
. . . continue climb to assigned altitude for direction of  
flight.

VCOA: **Rwys 1, 33**, obtain ATC approval for VCOA  
when requesting IFR clearance. Climb in visual  
conditions to cross Carbon County RGNL airport/  
Buck Davis Field at or above 9100 before proceeding  
on course.

NOTE: **Rwy 1**, multiple trees and poles beginning 164'  
from DER, left and right of centerline, up to 64'  
AGL/6207' MSL.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## PROVO, UT

### PROVO MUNI (PVU)

DEPARTURE PROCEDURE: Use PROVO  
DEPARTURE.

## RENO, NV

### RENO/STEAD (RTS)

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 3A 09183 (FAA)

TAKEOFF MINIMUMS: CAT A,B only, CAT C,D NA.

**Rwys 8,14**, 1300-2 or std. with a min. climb of 400' per NM to 6500. **Rwy 26**, 1900-2 or std. with a min. climb of 410' per NM to 7200. **Rwy 32**, 2300-2 or std. with a min. climb of 420' per NM to 7200.

DEPARTURE PROCEDURE: **Rwys 8,32**, climbing right turn heading 100° and FMG VORTAC R-314 to FMG VORTAC. **Rwy 14**, left turn climb direct FMG VORTAC. **Rwy 26**, climbing right turn heading 050° and FMG VORTAC R-314 to FMG VORTAC. **All aircraft** climb in FMG VORTAC holding pattern (NE, right turns, 221° inbound) to depart FMG VORTAC; R-260 CW R-170 at or above 10000; R-171 CW R-195 at or above 10500; R-196 CW R-259 at or above 12000.

## RENO, NV (CON'T)

### RENO/TAHOE INTL (RNO)

#### TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 4 07354 (FAA)

TAKEOFF MINIMUMS: **Rwy 7**, NA-terrain. **Rwy 16L**, std. w/ min. climb of 730' per NM to 8000, or 600-1/4 w/ min. climb of 480' per NM to 8000, or 2700-3 for climb in visual conditions. **Rwy 16R**, std. w/ the following minimum climb requirements: 210 knots or less, 385' per NM to 8000; more than 210 knots, 420' per NM to 8900, or 2700-3 for climb in visual conditions. Resume normal speed after passing FMG VORTAC. **Rwy 25**, std. w/ min. climb of 470' per NM to 7800, or 2700-3 for climb in visual conditions. **Rwy 34L**, std. w/ min. climb of 320' per NM to 7000, or 2700-3 for climb in visual conditions. **Rwy 34R**, std. w/ min. climb of 480' per NM to 7000, or 500-1/2 w/ min. climb of 320' per NM to 7000, or 2700-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwys 16L/R**, climb heading 164° to 6600 then climbing left turn direct FMG VORTAC, thence. . . or for climb in visual conditions: cross Reno/ Tahoe Intl Airport at or above 7000 via heading 054° and FMG R-234 to FMG VORTAC, thence. . . **Rwy 25**, climb heading 254° to 5000 then climbing right turn direct FMG VORTAC, thence. . . or for climb in visual conditions: cross Reno/Tahoe Intl Airport at or above 7000 via heading 054° and FMG R-234 to FMG VORTAC, thence. . . **Rwys 34L/R**, climb heading 344° to 7000 then climbing right turn direct FMG VORTAC, thence. . . or for climb in visual conditions: cross Reno/Tahoe Intl Airport at or above 7000 via heading 054° and FMG R-234 to FMG VORTAC, thence. . .

. . . **All aircraft**: continue climb in FMG VORTAC holding pattern (northeast, left turn, 221° inbound) to cross FMG VORTAC at or above MEA/MCA for route of flight.  
NOTE: **Rwy 16L**, multiple poles, trees, bushes and terrain beginning 618' from DER, 133' left of centerline, up to 20' AGL/4961' MSL.

**Rwy 16R**, multiple trees 2784' from DER, 171' right of centerline, up to 20' AGL/4510' MSL. Multiple trees and terrain beginning 746' from DER, 380' left of centerline, up to 20' AGL/4703' MSL. **Rwy 25**, multiple trees and poles beginning 829' from DER, 201' right of centerline, up to 103' AGL/4523' MSL. Building 6023' from DER, 456' right of centerline, 152' AGL/4608' MSL. Fence 222' from DER, 270' right of centerline, up to 5' AGL/4415' MSL. Multiple trees and poles beginning 500' from DER, 31' left of centerline, up to 20' AGL/4506' MSL. **Rwy 34L**, multiple trees and poles beginning 1229' from DER, 180' right of centerline, up to 20' AGL/4498' MSL. Multiple trees beginning 1193' from DER, 331' left of centerline, up to 20' AGL/4489' MSL. **Rwy 34R**, multiple trees and poles beginning 1067' from DER, 172' right of centerline, up to 20' AGL/4497' MSL. Multiple trees and poles beginning 1230' from DER, 350' left of centerline, up to 20' AGL/4498' MSL. Building 1.2 NM from DER, 1730' right of centerline, 363' AGL/4780' MSL.

## DIVERSE VECTOR AREA (RADAR VECTORS)

ORIG 15008 (FAA)

**Rwy 25**, heading as assigned by ATC; requires minimum climb of 500' per NM to 8100. **Rwy 34L**, heading as assigned by ATC; requires minimum climb of 460' per NM to 7700. **Rwy 34R**, heading as assigned by ATC; requires minimum climb of 410' per NM to 8100.

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## RICHFIELD, UT

RICHFIELD MUNI (RIF)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 08157 (FAA)  
DEPARTURE PROCEDURE: **Rwy 1**, use RICHFIELD  
(RNAV) DEPARTURE. **Rwy 19**, use HAMET (RNAV)  
DEPARTURE.

## ROOSEVELT, UT

ROOSEVELT MUNI (74V)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 02108 (FAA)  
TAKEOFF MINIMUMS: **Rwy 25**, 700-3 or std. with a  
min. climb of 300' per NM to 6100.  
DEPARTURE PROCEDURE: **Rwy 7**, turn right.  
**Rwy 25**, turn left. **All aircraft**, climb direct MTU  
VORTAC. Aircraft departing MTU VORTAC R-040  
CW R-150, climb on course. All others continue climb  
in MTU holding pattern (NE, right turns, 213° inbound)  
to cross MTU VORTAC; R-151 CW R-290 at or above  
8000; R-291 CW R-039 at or above 10,000. Then  
climb on course.

## SAFFORD, AZ

SAFFORD RGNL (SAD)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1 10210 (FAA)  
TAKEOFF MINIMUMS: **Rwys 8, 26**, NA - Airspace.  
DEPARTURE PROCEDURE: **Rwys 12, 30**, use  
SAFFORD RNAV DEPARTURE.

## ST. GEORGE, UT

ST. GEORGE MUNI (SGU)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
ORIG 11013 (FAA)  
DEPARTURE PROCEDURE: Use JITKA DEPARTURE.

## ST. JOHNS, AZ

ST. JOHNS INDUSTRIAL AIR PARK (SJV)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 1A 08241 (FAA)  
TAKEOFF MINIMUMS: **Rwy 21**, 400-2 or std. with a  
min. climb of 205' per NM to 6200.  
DEPARTURE PROCEDURE: **Rwys 3, 32**, climbing right  
turn, **Rwys 14, 21**, climbing left turn. **All aircraft**,  
climb direct SJN VORTAC. Aircraft departing SJN  
VORTAC R-240 CW R-080 climb on course. All others  
continue climb in SJN VORTAC holding pattern (Hold  
NE, right turns, 239° inbound) to cross SJN VORTAC at  
or above 9000.  
NOTE: **Rwy 14**, 5790' tower 350' right abeam DER.

## SALT LAKE CITY, UT

SALT LAKE CITY INTL (SLC)  
TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 11 10042 (FAA)  
TAKEOFF MINIMUMS: **Rwy 32**, 400-1 or std. w/ min.  
climb of 498' per NM to 4700.  
DEPARTURE PROCEDURE: **Rwy 14**, climb to 10000 via  
heading 189° and FFU R-341 to FFU VORTAC before  
proceeding on course. **Rwy 16R**, climb to 10000 via  
heading 161° and FFU R-341 to FFU VORTAC before  
proceeding on course. **Rwy 16L**, climb to 10000 via  
heading 161° and FFU R-341 to FFU VORTAC before  
proceeding on course. **Rwy 17**, climb to 10000 via  
heading 166° and FFU R-341 to FFU VORTAC before  
proceeding on course. **Rwy 32**, climb to 9,000 via  
heading 359° and OGD R-153 to OGD VORTAC before  
proceeding on course. **Rwy 34L**, climb to 9000 via  
heading 341° and OGD R-153 to OGD VORTAC before  
proceeding on course. **Rwy 34R**, climb to 9000 via  
heading 341° and OGD R-153 to OGD VORTAC before  
proceeding on course. **Rwy 35**, climb to 9000 via  
heading 336° and OGD R-153 to OGD VORTAC before  
proceeding on course.

NOTE: **Rwy 14**, antenna 1349' from DER, 544' left of  
centerline, 42' AGL/4263' MSL. **Rwy 16L**, vehicle on  
road 124' from DER, 14' right of centerline, 15'  
AGL/4239' MSL. Light pole 988' from DER, 726' right of  
centerline, 34' AGL/4254' MSL. Pole 1024' from DER,  
689' right of centerline, 34' AGL/4254' MSL. **Rwy 17**,  
vehicles on road beginning 335' from DER, on centerline,  
up to 17' AGL/4241' MSL. **Rwy 32**, ATC tower 5266' from  
DER, 1767' left of centerline, 335' AGL/4549' MSL.  
Crane 5196' from DER, 1630' left of centerline, 240'  
AGL/4463' MSL. Flag on obstruction light 5153' from  
DER, 1619' left of centerline, 249' AGL/4463' MSL.  
Aircraft beginning 989' from DER, 722' left of centerline,  
up to 79' AGL/4306' MSL. **Rwy 34R**, post 13' from DER,  
349' right of centerline, 3' AGL/4227' MSL. **Rwy 35**, post  
56' from DER, 249' left of centerline, 2' AGL/4220' MSL.

## SOUTH VALLEY RGNL (U42)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES  
AMDT 5 11069 (FAA)  
TAKEOFF MINIMUMS: **Rwy 16**, std. w/ a min. climb of  
300' per NM to 10700. **Rwy 34**, std. with a min. climb of  
330' per NM to 9000.  
DEPARTURE PROCEDURE: **Rwy 16**, climbing left turn  
to 10700 on FFU R-341 to FFU VORTAC, continue climb  
in hold in FFU VORTAC holding pattern (hold South,  
right turns, 008° inbound) to cross FFU VORTAC at or  
above MEA for route of flight. **Rwy 34**, climbing right  
turn to 9000 on TCH R-161 to TCH VORTAC, continue  
climb in hold in TCH VORTAC holding pattern (hold  
Northwest, right turns, 120° inbound) to cross TCH  
VORTAC at or above MEA for route of flight.  
NOTE: **Rwy 16**, bush 671' from DER, 490' right of  
centerline, up to 25' AGL/4629' MSL. Vehicles on road  
692' from DER, right and left of centerline, up to 17'  
AGL/4626' MSL. Poles beginning 1000' from DER, 465'  
right of centerline, up to 30' AGL/4638' MSL.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## SCOTTSDALE, AZ

SCOTTSDALE (SDL)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 8 10042 (FAA)

DEPARTURE PROCEDURE: **Rwys 3, 21**, use  
MARI COPA DEPARTURE.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 14317 (FAA)

**Rwy 3**, heading as assigned by ATC; requires minimum  
climb of 445' per NM to 4600. **Rwy 21**, heading as  
assigned by ATC; do not exceed 210 KTS until  
established on assigned heading.

## SEDONA, AZ

SEDONA (SEZ)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 08101 (FAA)

TAKEOFF MINIMUMS: **Rwy 3**, NA- Obstacles.  
DEPARTURE PROCEDURE: **Rwy 21**, Use OATES  
RNAV DEPARTURE.

## SHOW LOW, AZ

SHOW LOW RGNL (SOW)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 11013 (FAA)

DEPARTURE PROCEDURE: **Rwy 3**, climb on heading  
360° to 7800 before proceeding on course. **Rwy 6**,  
climb on heading 360° to 8100 before proceeding on  
course. **Rwy 21**, climb on heading 255° to 7700  
before proceeding on course. **Rwy 24**, climb on  
heading 243° to 7600 before proceeding on course.NOTE: **Rwy 3**, trees beginning 89' from DER, 429' left  
of centerline, up to 33' AGL/6413' MSL. **Rwy 21**,  
trees, tank, terrain, poles and buildings beginning 94'  
from DER, 5' left of centerline, up to 76' AGL/6519'  
MSL. Trees and terrain beginning 124' from DER, 25'  
right of centerline, up to 20' AGL/6431' MSL. **Rwy 24**,  
poles and catenary beginning 704' from DER, 4' left of  
centerline, up to 59' AGL/6439' MSL. Poles, catenary,  
electrical system, and terrain beginning 53' from DER,  
78' right of centerline, up to 58' AGL/6438' MSL.

## SPRINGVILLE, AZ

SPRINGVILLE MUNI (JTC)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

ORIG 96228 (FAA)

TAKEOFF MINIMUMS: **Rwy 21**, 1000-2 or std. with a  
min. climb of 360' per NM to 8400.DEPARTURE PROCEDURE: **Rwys 3, 11**, climbing left  
turn to 8400 via heading 360° before proceeding on  
course. **Rwys 21, 29**, climbing right turn to 8400 via  
360° before proceeding on course.

## TAYLOR, AZ

TAYLOR MUNI (TYL)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 11125 (FAA)

TAKEOFF MINIMUMS: **Rwy 21**, 300-1 or std. w/min. climb  
of 290' per NM to 6100.DEPARTURE PROCEDURE: **Rwy 3**, climb heading 030°  
to 8000 before turning on course. **Rwy 21**, climb heading  
210° to 8000 before turning on course.NOTE: **Rwy 3**, vehicles on road beginning 1823' from  
DER, 698' right of centerline, up to 17' AGL/5726' MSL.  
Power lines crossing departure course 1000' from DER.  
**Rwy 21**, trees beginning 1132' from DER, 316' right of  
centerline, up to 12' AGL/5871' MSL.

## TONOPAH, NV

TONOPAH (TPH)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 88350 (FAA)

TAKEOFF MINIMUMS: **Rwys 11, 29**, NA. **Rwys 15, 33**,  
2600-2 or std. with a min. climb of 260' per NM to 8000.DEPARTURE PROCEDURE: **Rwy 15**, turn left. **Rwy 33**,  
turn right. Climb direct TPH VORTAC. Continue climb in  
holding pattern (NE, right turns, 246° inbound) to depart  
TPH VORTAC at or above 8000. Climb on course to  
MEA or assigned altitude.

## TONOPAH TEST RANGE (KTNX)

TONOPAH , NV

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 12096

DEPARTURE PROCEDURE: **Rwy 14**: 1000-3 with  
minimum climb of 320 ft/NM to 10,700 or 2700-3 for  
Climb in Visual Conditions. Climb on a heading between  
325° CW to 155° from DER or Climb in Visual Conditions  
to cross KZ - KTNX airport at or above 8100 MSL before  
proceeding on course. **Rwy 32**: 1000-3 with minimum  
climb of 260 ft/NM to 5900 or 2700-3 for Climb in Visual  
Conditions. Climb on a heading between 295° CW to  
005° from DER or Climb in Visual Conditions to cross KZ-  
KTNX airport at or above 8100 MSL before proceeding  
on course. TAKEOFF OBSTACLES: **Rwy 14**, Terrain,  
5582' MSL, 1204' from DER, 823' right of centerline.  
Terrain, 5565' MSL, 63' from DER, 517' right of  
centerline. Terrain, 5564' MSL, 46' from DER, 480' right  
of centerline. Terrain, 5561' MSL, 0' from DER, 353' right  
of centerline. Terrain, 5558' MSL, 62' from DER, 200'  
right of centerline. Terrain, 5561' MSL, 14' from DER,  
292' right of centerline. Terrain, 5561' MSL, 0' from DER,  
287' right of centerline. Terrain, 5559' MSL, 0' from DER,  
222' right of centerline. Surveyed terrain, 5560' MSL,  
215' from DER, 427' right of centerline. **Rwy 32**, Terrain,  
5476' MSL, 0' from DER, 500' left of centerline. Terrain,  
5476' MSL, 19' from DER, 465' left of centerline. Terrain,  
5476' MSL, 110' from DER, 529' left of centerline.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

**TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND  
DIVERSE VECTOR AREA (RADAR VECTORS)**

15064

**TOOELE, UT****BOLINDER FIELD-TOOELE VALLEY (TVY)****TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES**

AMDT 3 13234 (FAA)

TAKEOFF MINIMUMS: **Rwy 17**, std. w/min. climb of 348' per NM to 9000 or 5600-3 for climb in visual conditions. **Rwy 35**, std. w/min. climb of 380' per NM to 9000 or 5600-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 17**, climbing right turn to 9000 on heading 337° and OGD VORTAC R-197 to STACO INT, or for climb in visual conditions: cross Bolinder Field-Tooele Valley airport at or above 9800' MSL before proceeding on course. When executing VCOA, notify ATC prior to departure.

**Rwy 35**, climbing left turn to 9000 on heading 300° and OGD VORTAC R-197 to STACO INT, or for climb in visual conditions: cross Bolinder Field-Tooele Valley airport at or above 9800' MSL before proceeding on course. When executing VCOA, notify ATC prior to departure.

NOTE: **Rwy 17**, tree 230' from DER, 255' right of centerline, 35' AGL/4335' MSL. Tree 342' from DER, 363' right of centerline, 35' AGL/4360' MSL. Trees beginning 601' from DER, 486' right of centerline, up to 35' AGL/4399' MSL. Pole 1000' from DER, 409' left of centerline, 42' AGL/4363' MSL. Pole 1092' from DER, 118' right of centerline, 42' AGL/4363' MSL. Tree 1369' from DER, 393' right of centerline, 35' AGL/4381' MSL. Tree 2018' from DER, 257' right of centerline, 35' AGL/4384' MSL.

**TUCSON, AZ****RYAN FIELD (RYN)****TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES**

AMDT 3 10210 (FAA)

TAKEOFF MINIMUMS: **Rwys 6L, 15, 24R, 33**, NA, ATC. DEPARTURE PROCEDURE: **Rwys 6R, 24L**, use ALMON DEPARTURE.

**TUCSON INTL (TUS)****TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES**

AMDT 5 12208 (FAA)

TAKEOFF MINIMUMS: **Rwy 3**, 300-2 or std. w/min. climb of 228' per NM to 3000.

DEPARTURE PROCEDURE: **Rwys 3, 29L/R**, climbing right turn direct to TUS VORTAC...

**Rwy 21**, climbing left turn direct to TUS VORTAC ... **Rwy 11L/R**, climb heading 123° to 4000 then climbing left turn direct TUS VORTAC ...

... Climb in TUS VORTAC holding pattern (hold NW, right turns, 128° inbound) to 9000 before proceeding on course.

NOTE: **Rwy 3**, multiple trees and sign beginning 1385' from DER, 127' left of centerline, up to 41' AGL/2611' MSL. Tree 2062' from DER, 332' right of centerline, 46' AGL/2626' MSL. **Rwy 11L**, vents 115' from DER, 147' left and right of centerline, 6' AGL/2646' MSL. Multiple bushes beginning 449' from DER, 395' left of centerline, up to 24' AGL/2674' MSL. Multiple bushes beginning 188' from DER, 328' right of centerline, up to 13' AGL/2663' MSL. **Rwy 11R**, tree 584' from DER, 176' right of centerline, 25' AGL/2645' MSL. **Rwy 21**, bush 104' from DER, 256' left of centerline, 12' AGL/2572' MSL. RR 248' from DER, right to left of centerline, 23' AGL/2582' MSL. Bush 549' from DER, 384' left of centerline, 33' AGL/2583' MSL. Tree 701' from DER, 144' left of centerline, 37' AGL/2587' MSL. Pole 950' from DER, 166' left of centerline, 38' AGL/2588' MSL. Pole 1028' from DER, 89' left of centerline, 46' AGL/2599' MSL. Pole 1298' from DER, 594' left of centerline, 66' AGL/2616' MSL. Electrical system 1445' from DER, 319' left of centerline, 55' AGL/2605' MSL. Bush 141' from DER, 330' right of centerline, 24' AGL/2574' MSL. Bush 454' from DER, 138' right of centerline, 26' AGL/2576' MSL. Electrical system 1176' from DER, 37' right of centerline, 48' AGL/2598' MSL.

**Rwy 29L**, aircraft on ramp 2723' from DER, 348' left of centerline, up to 30' AGL/2680' MSL. **Rwy 29R**, aircraft on ramp 2779' from DER, 1056' left of centerline, up to 30' AGL/2680' MSL.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

15064

**TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND  
DIVERSE VECTOR AREA (RADAR VECTORS)**

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

15064

## VERNAL, UT

### VERNAL RGNL (VEL)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

TAKEOFF MINIMUMS: **Rwy 16**, 1500-2 or std with a min. climb of 250' per NM to 7000'. **Rwy 25**, 1500-2 or std. with a min. climb of 390' per NM to 7000. **Rwy 34**, 1600-2 pr std. with a min. climb of 330' per NM to 7000'.

DEPARTURE PROCEDURE: **Rwys 7,34**, turn right. **Rwys 16,25**, turn left. All aircraft climb direct VEL. Aircraft departing V391 S-bound climb on course. All others climb in holding pattern (SE, right turns, 322° inbound). Aircraft SW-bound V208 depart VEL at or above 8400', all others depart VEL at or above 9500'. Continue climb on course to MEA or assigned altitude.

## WENDOVER, UT

### WENDOVER (ENV)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 6 14317 (FAA)

TAKEOFF MINIMUMS: **Rwy 26**, std. w/min. climb of 300' per NM to 5900. **Rwy 30**, NA-ATC.  
DEPARTURE PROCEDURE: **Rwys 8,12, 26**, climbing left turn direct BVL VORTAC, thence...  
...continue climb in holding pattern (hold NE, right turns, 247° inbound) to appropriate MEA for route of flight.

NOTE: **Rwy 8**, vehicles on road, beginning 827' from DER, left and right of centerline, 18' AGL/4318' MSL

## WILLCOX, AZ

### COCHISE COUNTY (P33)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 13122 (FAA)

TAKEOFF MINIMUMS: Use COCHISE DEPARTURE.

## WINDOW ROCK, AZ

### WINDOW ROCK (RQE)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 03191 (FAA)

TAKEOFF MINIMUMS: **Rwy 2**, 700-2 or std. with a min. climb of 500' per NM to 8000. **Rwy 20**, 600-2 or std. with a min. climb of 260' per NM to 8200.

DEPARTURE PROCEDURE: **Rwy 2**, turn right. **Rwy 20**, turn left direct to GUP VORTAC before proceeding on course.

NOTE: **Rwy 2**, terrain 3832' from DER, 1025' right of centerline, 6926' MSL. Poles 5220' from DER, 245' right of centerline, 180' AGL/6922' MSL. Tower 7067' from DER, 3072' left of centerline, 71' AGL/7316' MSL. Terrain 7449' from DER, 1612' left of centerline, 6991' MSL. Terrain 8776' from DER, 1851' left of centerline, 7109' MSL. Tree 9665' from DER, 1326' right of centerline, 7340' MSL. Tree 11326' from DER, 355' left of centerline, 7351' MSL. **Rwy 20**, trees 1018' from DER, 620' left of centerline, 30' AGL/6768' MSL.

## WINNEMUCCA, NV

### WINNEMUCCA MUNI (WMC)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

AMDT 1 87295 (FAA)

TAKEOFF MINIMUMS: **Rwy 2**, 2500-2 or std. with a min. climb of 450' per NM to 6800. **Rwys 14,20**, 3200-2 or std. with a min. climb of 520' per NM to 7500.

DEPARTURE PROCEDURE: **Rwys 14,20**, turn right. **Rwy 2**, turn left. **Rwy 32**, climb straight ahead. All aircraft climb via INA R-326 to 6700 or above within 12 NM, then climbing left turn return to INA VOR/DME via R-326. Continue climb in INA VOR/DME holding pattern (hold NW, right turns, 146° inbound) to depart INA VOR/DME at or above 11000. Southbound aircraft continue via INA R-146 direct Fesko Int. Northbound aircraft continue via INA R-326 and SDO R-144 direct SDO VORTAC.

## WINSLOW, AZ

### WINSLOW-LINDBERGH RGNL (INW)

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

ORIG 14345 (FAA)

DEPARTURE PROCEDURE: **Rwy 22**, climb to 6000, then right turn direct INW VORTAC and hold, thence . . . **Rwy 4**, climb to 6000, then left turn direct INW VORTAC and hold, thence . . .

**Rwys 11, 29**, climb to 6000, then direct INW VORTAC and hold, thence . . .

. . . continue climb-in-hold (hold West, right turns, 068° inbound) to 8900 before proceeding on course.

NOTE: **Rwy 11**, vehicle on road beginning 389' from DER, 329' right of centerline, 15' AGL/4894' MSL. Trees beginning 120' from DER, 398' right of centerline, 100' AGL/4901' MSL. Tank 3681' from DER, 1304' right of centerline, 129' AGL/5014' MSL. Grain silo 2901' from DER, 25' right of centerline, up to 4957' MSL. Obstruction light on hopper 2908' from DER, 27' right of centerline, up to 4955' MSL. Chimney 2899' from DER, 28' right of centerline, up to 4953' MSL. Light support structure 13' from DER, 55' left of centerline, up to 4871' MSL. Light support structure 13' from DER, 56' right of centerline, up to 4871' MSL. Vertical point 234' from DER, 14' left of centerline, up to 4876' MSL. **Rwy 29**, tree 332' from DER, 589' left of centerline 100' AGL/4915' MSL. Trees beginning 385' from DER, 124' right of centerline, 100' AGL/4923' MSL. Vehicle on road beginning 31' from DER, 389' right of centerline 15' AGL/4920' MSL. REIL abeam DER, 139' left of centerline, up to 4904' MSL. Bush 38' from DER, 179' right of centerline, up to 4903' MSL. Pole 2132' from DER, 1052' right of centerline, up to 4956' MSL. Vertical point 241' from DER, 318' right of centerline, up to 4907' MSL. Ground 71' from DER, 456' left of centerline, up to 4902' MSL. **Rwy 4**, light 4' from DER, 425' left of centerline, up to 4920' MSL. Obstruction light on lighted windsock 12' from DER, 424' left of centerline, up to 4918' MSL. Tree 34' from DER, 263' left of centerline, 100' AGL/4901' MSL. Tower 2740' from DER, 1086' left of centerline, up to 4968' MSL. Ground 42' from DER, 455' left of centerline, up to 4892' MSL. **Rwy 22**, poles beginning 1575' from DER, 360' right of centerline, up to 5010' MSL. Antenna 1867' from DER 360' right of centerline up to 5019' MSL. Vehicle on road beginning 198' from DER, 12' right of centerline, 15' AGL/4994' MSL. Vehicle on road beginning 499' from DER, 93' left of centerline, 15' AGL/4962' MSL. Tree 1746' from DER, 581' right of centerline, 100' AGL/4993' MSL. Vertical point 31' from DER, 479' left of centerline, up to 4946' MSL. Building 525' from DER, 528' right of centerline, up to 4956' MSL. Light support structures 10' from DER, 54' right of centerline, up to 4942' MSL.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

15064

# TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)


**TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND**

  
**DIVERSE VECTOR AREA (RADAR VECTORS)**

15064

**YUMA MCAS/ YUMA INTL (KNYL)**

YUMA, AZ

TAKEOFF MINIMUMS AND (OBSTACLE)  
DEPARTURE PROCEDURES

09323

Diverse departures not authorized between 360° CW  
055° from 25 NM to 30 NM.**Rwy 3L:** Cross DER at or above 35' AGL/228' MSL.  
Diverse departures auth. Fr 083° CW 107°, std with  
minimum climb of 225'/NM to 3500'.**Rwy 3R:** Cross DER at or above 35' AGL/242' MSL.  
Diverse departures auth. Fr 083° CW 107°, std with  
minimum climb of 225'/NM to 3500'.**Rwy 21L:** Cross DER at or above 35' AGL/223' MSL.  
Diverse departures auth.**Rwy 21R:** Cross DER at or above 35' AGL/227' MSL.  
Diverse departures auth.**Rwy 8:** Cross DER at or above 35' AGL/231' MSL.  
Diverse departures auth. Fr 069° CW 123°, std with  
minimum climb of 230'/NM to 3500'.**Rwy 26:** Cross DER at or above 35' AGL/230' MSL.  
Diverse departures auth.**Rwy 17:** Cross DER at or above 35' AGL/217' MSL.  
Diverse departures auth. Fr 068° CW 109°, std with  
minimum climb of 220'/NM to 3500'.**Rwy 35:** Cross DER at or above 35' AGL/231' MSL.  
Diverse departures auth.

05 MAR 2015 to 02 APR 2015

05 MAR 2015 to 02 APR 2015

15064


**TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND**

  
**DIVERSE VECTOR AREA (RADAR VECTORS)**