

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

INSTRUMENT APPROACH PROCEDURE CHARTS

17005

IFR TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

Civil Airports and Selected Military Airports

ALL USERS: Airports that have Departure Procedures (DPs) designed specifically to assist pilots in avoiding obstacles during the climb to the minimum enroute altitude, and/or airports that have civil IFR takeoff minimums other than standard, are listed below. Takeoff Minimums and Departure Procedures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in MSL.

DPs specifically designed for obstacle avoidance are referred to as Obstacle Departure Procedures (ODPs) and are textually described below, or published separately as a graphic procedure. If the ODP is published as a graphic procedure, its name will be listed below, and it can be found in either this volume (civil), or the applicable military volume, as appropriate. Users will recognize graphic obstacle DPs by the term "(OBSTACLE)" included in the procedure title; e.g., TETON TWO (OBSTACLE). If not specifically assigned an ODP, SID, or radar vector as part of an IFR clearance, an ODP may be required to be flown for obstacle clearance, even though not specifically stated in the IFR clearance. When doing so in this manner, ATC should be informed when the ODP being used contains a specified route to be flown, restrictions before turning, and/or altitude restrictions.

Some ODPs, which are established solely for obstacle avoidance, require a climb in visual conditions to cross the airport, a fix, or a NAVAID in a specified direction, at or above a specified altitude. These procedures are called Visual Climb Over Airport (VCOA). To ensure safe and efficient operations, the pilot must verbally request approval from ATC to fly the VCOA when requesting their IFR clearance.

At some locations where an ODP has been established, a diverse vector area (DVA) may be created to allow radar vectors to be used in lieu of an ODP. DVA information will state that headings will be as assigned by ATC and climb gradients, when applicable, will be published immediately following the specified departure procedure.

Graphic DPs designed by ATC to standardize traffic flows, ensure aircraft separation and enhance capacity are referred to as "Standard Instrument Departures (SIDs)". SIDs also provide obstacle clearance and are published under the appropriate airport section. ATC clearance must be received prior to flying a SID.

CIVIL USERS NOTE: Title 14 Code of Federal Regulations Part 91 prescribes standard takeoff rules and establishes takeoff minimums for certain operators as follows: (1) For aircraft, other than helicopters, having two engines or less – one statute mile visibility. (2) For aircraft having more than two engines – one-half statute mile visibility. (3) For helicopters – one-half statute mile visibility. These standard minima apply in the absence of any different minima listed below.

MILITARY USERS NOTE: Civil (nonstandard) takeoff minima are published below. For military takeoff minima, refer to appropriate service directives.

NAME	TAKEOFF MINIMUMS	NAME	TAKEOFF MINIMUMS
ALTURAS, CA		ARCATA-EUREKA, CA	
ALTURAS MUNI (AAT)		ARCATA (ACV)	
TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES		TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES	
AMDT 2 08101 (FAA)		AMDT 7 12040 (FAA)	
DEPARTURE PROCEDURE: Use BACHS DEPARTURE.		TAKEOFF MINIMUMS: Rwy 1 , Std. w/min. climb of 355' per NM to 1100 or 1000-2½ for climb in visual conditions. Rwy 14 , 500-2 1/8 or std. w/min. climb of 445' per NM to 900. DEPARTURE PROCEDURE: Rwy 1 , climbing left turn thence ..., or for climb in visual conditions: cross Arcata Airport westbound at or above 1100. When executing VCOA, notify ATC prior to departure. Thence ... Rwys 14, 19 , climbing right turn thence ... Rwy 32 , climbing left turn thence On ACV R-250 to HOCUT INT and continue climb to MEA on V27.	
AMEDEE AAF (KAHC),		NOTE: Rwy 1 , trees beginning 222' from DER, 391' right of centerline, up to 200' AGL/799' MSL. Trees beginning 321' from DER, 343' left of centerline, up to 200' AGL/839' MSL. Rwy 14 , trees beginning 1086' from DER, 716' right of centerline, up to 100' AGL/286' MSL. Trees beginning 4708' from DER, 1558' left of centerline, up to 200' AGL/679' MSL. Rwy 19 , trees beginning 543' from DER, 298' right of centerline, up to 31' AGL/218' MSL. Vegetation 16' from DER, 270' right of centerline, 4' AGL/191' MSL. Rwy 32 , trees beginning 4' from DER, 334' left of centerline, up to 20' AGL/202' MSL. Trees beginning 1037' from DER, 644' right of centerline, up to 85' AGL/267' MSL. Fence 268' from DER, 476' right of centerline, 15' AGL/197' MSL. NAVAID 581' from DER, 258' right of centerline, 20' AGL/202' MSL.	
HERLONG, CA			
TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES			
AMDT 1, 09239			
Rwy 8, 26: 4000-3 for climb in visual conditions. Rwy 8, 26: Cross Amedee AAF at or above 7900 before proceeding on course.			

17005

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

ATWATER, CA

CASTLE (MER)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1A 11349 (FAA)

TAKEOFF MINIMUMS: **Rwy 13**, std. w/ min. climb of 250' per NM to 2500 or 2200-3 for climb in visual conditions.
DEPARTURE PROCEDURE: **Rwy 13**, climb heading 126° to 2500 before turning left. For climb in visual conditions, cross Castle Airport at or above 2200 before proceeding on course. **Rwy 31**, climb heading 306° to 1100 before turning right.

NOTE: **Rwy 13**, tree 2539' from DER, 1005' right of centerline, 89' AGL/261' MSL. **Rwy 31**, tree 1274' from DER, 829' left of centerline, 20' AGL/224' MSL. Trees beginning 2909' from DER, 542' right of centerline, 65' AGL/269' MSL.

AUBURN, CA

AUBURN MUNI (AUN)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1A 11349 (FAA)

TAKEOFF MINIMUMS: **Rwy 7**, 300-1 w/ min. climb of 387' per NM to 2500, or 1100-3 for climb in visual conditions.
DEPARTURE PROCEDURE: **Rwy 7**, climbing left turn to 5000 heading 310°, and MYV VOR/DME R-083 to MYV VOR/DME, then via MYV VOR/DME R-263 to YUBBA INT before proceeding on course, or for climb in visual conditions: cross Auburn Muni airport at or above 2500, continue climb to 5000 via heading 275° and MYV VOR/DME R-094 to MYV VOR/DME, then via MYV VOR/DME R-263 to YUBBA INT before proceeding on course. **Rwy 25**, climbing right turn to 5000 via heading 310° and MYV VOR/DME R-083 to MYV VOR/DME, then via MYV VOR/DME R-263 to YUBBA INT before proceeding on course.

NOTE: **Rwy 7**, trees beginning 1117' from DER, 504' right of centerline, up to 40' AGL/1708' MSL. Pole 1365' from DER, 600' right of centerline, 59' AGL/1679' MSL. Tree 3791' from DER, 700' right of centerline, 40' AGL/1639' MSL. **Rwy 25**, tree 37' from DER, 479' left of centerline, 40' AGL/1528' MSL. Tree 86' from DER, 461' right of centerline, 40' AGL/1532' MSL. Fence 301' from DER, 244' right of centerline, 8' AGL/1508' MSL. Trees beginning 660' from DER, 249' right of centerline, up to 40' AGL/1559' MSL.

BEALE AFB (KBAB)

MARYSVILLE, CA

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 2, 14149

DEPARTURE PROCEDURE: **Rwy 15**, Climb on a heading between 100° CW to 325° from DER.

Rwy 33, Climb on a heading between 146° CW to 344° from DER.

TAKE-OFF OBSTACLES: **Rwy 33**, terrain 118' MSL, 62' from DER, 500' right of centerline. Terrain 118' MSL, 63' from DER, 517' right of centerline. Aircraft tail 16' AGL/134' MSL, 39' from DER, 533' right of centerline. Aircraft tail 16' AGL/134' MSL, 129' from DER, 525' right of centerline.

BECKWOURTH, CA

NERVINO (O02)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
ORIG-A 13290 (FAA)

TAKEOFF MINIMUMS: **Rwys 8, 26**, 3500-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwys 8, 26**, for climb in visual conditions: cross Nervino Airport at or above 8300 before proceeding on course.

NOTE: **Rwy 8**, road 58' from DER, 469' right of centerline, 15' AGL/4920' MSL. Pole 310' from DER, 522' right of centerline, 49' AGL/4925' MSL. Pole 528' from DER, 522' right of centerline, 39' AGL/4924' MSL. Tree 1.47 NM from DER, 727' right of centerline, 100' AGL/5193' MSL. Tree 1.9 NM from DER, 2534' right of centerline, 100' AGL/5499' MSL. Bush 2.03 NM from DER, 2126' right of centerline, 4' AGL/5406' MSL. **Rwy 26**, tree 5856' from DER, 1984' right of centerline, 100' AGL/5339' MSL. Tree 1.25 NM from DER, 2439' right of centerline, 100' AGL/5420' MSL. Tree 2.07 NM from DER, 3302' left of centerline, 100' AGL/5570' MSL.

BISHOP, CA

BISHOP (BIH)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 3B 16259 (FAA)

TAKEOFF MINIMUMS: **Rwys 7,12,17**, NA-terrain. **Rwy 25**, std. w/ min. climb of 280' per NM to 10300. **Rwys 30, 35**, std. w/ min. climb of 285' per NM to 10300.

DEPARTURE PROCEDURE: **Rwys 25, 30**, climbing right turn on heading 360, thence...

Rwy 35, climb left turn on heading 290°, thence...
...all aircraft intercept BIH R-322 to NIKOL INT/BIH 38.46 DME.

NOTE: **Rwy 25**, trees and bushes beginning 69' from DER, 32' right of centerline, up to 100' AGL/4234' MSL... Trees beginning 709' from DER, 31' left of centerline, up to 47' AGL/4167' MSL. **Rwy 30**, rising terrain 58' from DER, 422' right of centerline, 4143' MSL. Trees beginning 763' from DER, 155' right of centerline, up to 100' AGL/4207' MSL. Trees beginning 1598' from DER, 21' left of centerline, up to 100' AGL/4205' MSL. **Rwy 35**, trees beginning 83' from DER, 31' right of centerline, up to 60' AGL/4146' MSL. Rising terrain 311' from DER, 348' left of centerline, 4118' MSL. Trees beginning 95' from DER, 141' left of centerline, up to 60' AGL/4146' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

BYRON, CA

BYRON (C83)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

AMDT 1 06047 (FAA)

TAKEOFF MINIMUMS: **Rwy 23**, NA-obstacles.

Rwy 30, 200-1 or std. with a min. climb of 240' per NM to 300. Alternatively, with standard TAKEOFF minimums and a normal 200'/NM climb gradient, TAKEOFF must occur no later than 2000' prior to DER.

DEPARTURE PROCEDURE: **Rwy 5**, climbing right turn via

heading 120° and ECA VORTAC before proceeding on course. **Rwy 12**, climbing left turn via heading 050° and

ECA VORTAC R-250 to ECA VORTAC before proceeding on course. **Rwy 30**, climbing right turn via heading 130° and ECA VORTAC R-250 to ECA VORTAC before proceeding on course.

NOTE: **Rwy 5**, bush 17' from DER, 67' right of centerline, 6'

AGL/52' MSL. **Rwy 12**, multiple trees and bush beginning

240' from DER, 286' right of centerline, up to 39' AGL/76'

MSL. **Rwy 30**, multiple poles, building, and terrain

beginning 66' from DER, 228' left of centerline, up to 65'

AGL/225' MSL. Multiple poles beginning 949' from DER,

28' right of centerline, up to 42' AGL/103' MSL.

CHICO, CA

CHICO MUNI (CIC)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

AMDT 6A 13346 (FAA)

DEPARTURE PROCEDURE: **Rwy 13L/R**, climbing right

turn to intercept CIC R-205, thence ... **Rwy 31L/R**,

climbing left turn heading 140° to intercept CIC R-205.

Thenceall aircraft climb via CIC R-205 to JINGO

INT. Aircraft departing JINGO INT 030° CW 345° climb on

course. All others climb in JINGO INT holding pattern (hold

SE, right turns, 320° inbound) to depart JINGO INT at or

above 3800.

NOTE: **Rwy 13L**, terrain 298' from DER, 534' left of

centerline, 216' MSL. Pole 957' from DER, 735' left of

centerline, 35' AGL/232' MSL. Trees beginning 948' from

DER, 559' left of centerline, up to 51' AGL/241' MSL. **Rwy**

13R, plane on tarmac 582' from DER, 647' left of

centerline, up to 40' AGL/255' MSL. **Rwy 31L**, plane on

tarmac 570' from DER, 647' right of centerline, up to 40'

AGL/279' MSL. Tower 611' from DER, 349' right of

centerline, 35' AGL/267' MSL. **Rwy 31R**, trees beginning

1124' from DER, right and left of centerline, up to 60'

AGL/282' MSL.

CLOVERDALE, CA

CLOVERDALE MUNI (O60)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

AMDT 1 11349 (FAA)

TAKEOFF MINIMUMS: **Rwy 14**, 700-3 w/min. climb of 390' per NM to 1200 or std. w/min. climb of 744' per NM to 1000, or 3600-3 for climb in visual conditions. **Rwy 32**, NA - Obstacles.

DEPARTURE PROCEDURE: **Rwy 14**, climb direct STS VOR/DME, thence...

Or climb in visual conditions to cross Cloverdale Muni

airport at or above 3700 before proceeding on course.

...Climb in STS VOR/DME holding pattern (hold NW, right

turns, 140° inbound) to cross STS VOR/DME at or above

MEA/MCA for direction of flight.

NOTE: **Rwy 14**, trees beginning 19' from DER, 23' right of

centerline, up to 100' AGL/404' MSL. Trees beginning 1.6

NM from DER, 491' right of centerline, up to 100'

AGL/959' MSL. Trees beginning 258' from DER, on

centerline, up to 100' AGL/296' MSL. Trees beginning 21'

from DER, 7' left of centerline, up to 100' AGL/442' MSL.

Trees beginning 1.7 NM from DER, 34' left of centerline,

up to 100' AGL/679' MSL. Buildings 1524' from DER, 110'

right of centerline, up to 427' MSL. Buildings 4605' from

DER, 532' left of centerline, up to 408' MSL.

COLUMBIA, CA

COLUMBIA (O22)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

ORIG 99364 (FAA)

TAKEOFF MINIMUMS: **Rwy 17**, 300-1 with a min. climb

rate of 300' per NM to 3000. **Rwy 35**, NA.

DEPARTURE PROCEDURE: **Rwy 17**, use FICHU RNAV

DEPARTURE. **Rwy 35**, NA.

NOTE: **Rwy 17**, 51' AGL pole 502' from DER, 368' right of

centerline, 90' AGL tree 483' from DER, 535' right of

centerline; 100 AGL tree 1258' from DER, 494' left of

centerline; 167' AGL tree 1644' from DER, 924' right of

centerline.

COLUSA, CA

COLUSA COUNTY (O08)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

ORIG-A 16315 (FAA)

TAKEOFF MINIMUMS: **Rwy 31**, 300-1 or std. w/min. climb

of 310' per NM to 400.

DEPARTURE PROCEDURE: **Rwy 31**, climbing left turn

direct ILA VORTAC before proceeding on course. **Rwy**

13, climbing right turn direct ILA VORTAC before

proceeding on course.

NOTE: **Rwy 13**, fence 1' from DER, 234 right of centerline,

49' MSL. Tree 138' from DER, 346' left of centerline, 77'

MSL. Bldg 255' from DER, 496' right of centerline, 62'

MSL. Trees beginning 543' from DER, 146' right of

centerline, up to 85' MSL. Bldg 1476' from DER, 428' left

of centerline, 61' AGL/107' MSL. **Rwy 13**, tower 1396'

from DER, 92' right of centerline, 55' AGL/105' MSL.

Tower 4958' from DER, 1806' right of centerline, 190'

AGL/240' MSL.

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

17005

CONCORD, CA

BUCHANAN FIELD (CCR)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 07354 (FAA)

TAKEOFF MINIMUMS: **Rwys 1L/R**, std. w/ min. climb of 360' per NM to 1100, or 2200-3 for climb in visual conditions.

Rwys 14L/R, std. w/ min. climb of 420' per NM to 2700, or 2200-3 for climb in visual conditions. **Rwys 19L/R**, std. w/ min. climb of 490' per NM to 4000, or 2200-3 for climb in visual conditions. **Rwys 32L/R**, std. w/ min. climb of 320' per NM to 500, or 2200-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwys 1L/R**, climb direct CCR VOR/DME, or climb in visual conditions to cross Buchanan Airport northbound at or above 2100 via CCR R-173 to CCR VOR/DME, thence...**Rwys 14L/R, 19L/R** climbing left turn direct CCR VOR/DME, or climb in visual conditions to cross Buchanan Airport northbound at or above 2100 via CCR R-173 to CCR VOR/DME, thence...**Rwys 32L/R**, climbing right turn direct CCR VOR/DME, or climb in visual conditions to cross Buchanan Airport northbound at or above 2100 via CCR R-173 to CCR VOR/DME, thence...

...aircraft departing CCR VOR/DME R-150 clockwise R-110 climb on course. All others climb in CCR VOR/DME holding pattern (north, left turns, 191° inbound) to cross CCR VOR/DME at or above 2700 before proceeding on course.

NOTE: **Rwy 1L**, multiple trees and bushes beginning 675' from DER, 9' left of centerline, up to 48' AGL/98' MSL. Multiple poles, light poles and antennas on buildings beginning 639' from DER, 120' left of centerline, up to 50' AGL/72' MSL. Fence 117' from DER, 2' right of centerline, 12' AGL/29' MSL. Sign 1996' from DER, 812' left of centerline, 45' AGL/78' MSL. Flagpole 1520' from DER, 753' left of centerline, 40' AGL/71' MSL. **Rwy 1R**, multiple trees and poles beginning 1552' from DER, 98' right of centerline, up to 52' AGL/131' MSL. **Rwy 19R**, multiple trees beginning 604' from DER, 82' left of centerline, up to 70' AGL/108' MSL. Light pole 1392' from DER, 749' right of centerline, 51' AGL/71' MSL. Obstruction light on building 2451' from DER, 911' left of centerline, 73' AGL/97' MSL. Fence 123' from DER, 503' left of centerline, 6' AGL/30' MSL. **Rwy 19L**, multiple trees beginning 2132' from DER, 282' left of centerline, up to 70' AGL/106' MSL. **Rwy 32L**, road/vehicle 561' from DER, on centerline, 15' AGL/49' MSL. Light on tank 6617' from DER, 1926' right of centerline, 114' AGL/213' MSL. Hangar 259' from DER, 300' left of centerline, 21' AGL/37' MSL. Transmission tower 6015' from DER, 1338' left of centerline, 145' AGL/173' MSL. Tree 825' from DER, 136' left of centerline, 25' AGL/40' MSL, building 633' from DER, 254' right of centerline, 20' AGL/35' MSL. **Rwy 32R**, train 6345' from DER, 1948' left of centerline, 23' AGL/102' MSL, obstruction light on hopper 2110' from DER, 601' right of centerline, 79' AGL/99' MSL. Obstacle light on tank 6617' from DER, 1426' right of centerline, 193' AGL/213' MSL. Flagpole 655' from DER, 300' right of centerline, 35' AGL/43' MSL. Sign 697' from DER, 248' right of centerline, 25' AGL/41' MSL. Road/vehicle 561' from DER, on centerline, 15' AGL/49' MSL. Building 633' from DER, 246' left of centerline, 20' AGL/35' MSL, tree 825' from DER, 635' left of centerline, 25' AGL/40' MSL, transmission tower 6015' from DER, 1839' left of centerline, 145' AGL/173' MSL. **Rwy 14R**, obstacle lights, obstacle lights on buildings, obstacle lights on windsocks, buildings and trees beginning 412' from DER, 167' right of centerline, up to 104' AGL/136' MSL. **Rwy 14L**, multiple trees beginning 841' from DER, 61' left of centerline, up to 78' AGL/102' MSL, building 1071' from DER, 35' left of centerline, 30' AGL/58' MSL. Fence 225' from DER, 29' left of centerline, 12' AGL/33' MSL.

CRESCENT CITY, CA

JACK MC NAMARA FIELD (CEC)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 15288 (FAA)

TAKEOFF MINIMUMS: **Rwy 18**, 300-1 or std. w/min. climb of 294' per NM to 300. **Rwy 36**, 300-1 or std. w/min. climb of 443' per NM to 300.

DEPARTURE PROCEDURE: **Rwys 12, 18**, climbing right turn, thence...

Rwys 30, 36, climbing left turn, thence...

...climb direct CEC VORTAC, aircraft departing CEC R-144 CW R-350 climb on course. All others continue climb in CEC VORTAC holding pattern (hold South, left turns, 346° inbound) to cross CEC VORTAC at or above: R-351 CW R-048, 2900; R-049 CW R-113, 4300; R-114 CW R-143, 2900.

NOTE: **Rwy 12**, trees and vegetation 77' from DER, 265' left of centerline, up to 32' AGL/82' MSL. Tree 174' from DER, 301' right of centerline, 22' AGL/77' MSL. Trees beginning 507' from DER, 207' left of centerline, up to 58' AGL/108' MSL. Trees beginning 354' from DER, 396' right of centerline, up to 66' AGL/116' MSL. Trees beginning 811' from DER, 569' left of centerline, up to 105' AGL/158' MSL. Trees beginning 1124' from DER, left and right of centerline, up to 90' AGL/140' MSL. Tree 1129' from DER, 734' right of centerline, 102' AGL/152' MSL. Trees and pole beginning 1398' from DER, left and right of centerline, up to 144' AGL/187' MSL. **Rwy 18**, trees and vegetation beginning 27' from DER, 274' right of centerline, up to 14' AGL/64' MSL. Runway end ident light 35' from DER, 115' left of centerline, 4' AGL/53' MSL. Runway end ident light 115' right of centerline, 5' AGL/53' MSL. Vehicles on road beginning 329' from DER, left and right of centerline, up to 15' AGL/60' MSL. Ground 4976' from DER, 1720' right of centerline, 239' MSL. **Rwy 30**, trees and vegetation abeam DER, 359' left of centerline, up to 21' AGL/71' MSL. Trees and vegetation beginning 18' from DER, 370' right of centerline, up to 22' AGL/67' MSL. **Rwy 36**, trees and bushes abeam DER, 258' left of centerline, up to 32' AGL/82' MSL. Ground, bushes, and terrain beginning 140' from DER, left and right of centerline, up to 15' AGL/76' MSL. Ground, bushes, and trees beginning 58' from DER, 364' right of centerline, up to 50' AGL/100' MSL. Ground, bushes, trees and vegetation beginning 406' from DER, left and right of centerline, up to 47' AGL/97' MSL. Trees and vegetation beginning 968' from DER, left and right of centerline, up to 86' AGL/136' MSL. Trees beginning 1549' from DER, 148' left of centerline, up to 122' AGL/172' MSL. Trees beginning 2136' from DER, 252' right of centerline, up to 156' AGL/206' MSL. Tree 2787' from DER, 672' right of centerline, 165' AGL/215' MSL.

DAVIS, CA

UNIVERSITY (EDU)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 3 09127 (FAA)

DEPARTURE PROCEDURE: **Rwy 17**, climbing right turn via heading 200° and ILA R-151 to EMBER INT/ILA 48 DME before proceeding on course. **Rwy 35**, climbing left turn via heading 320° and ILA R-145 to ILA VORTAC before proceeding on course.

NOTE: **Rwy 17**, trees beginning 1353' from DER, 31' right of centerline, up to 40' AGL/109' MSL. **Rwy 35**, tree 24' from DER, 433' left of centerline, 40' AGL/104' MSL. Vehicle 288' from DER, on centerline, 15' AGL/74' MSL.

17005

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

DAVIS/WOODLAND/WINTERS, CA

YOLO COUNTY (DWA)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1 09127 (FAA)

DEPARTURE PROCEDURE: **Rwy 16**, climb heading 164° to 2100 before turning right. **Rwy 34**, climb heading 344° to 1500 before turning left.

NOTE: **Rwy 16**, multiple trees beginning 595' from DER, 308' right of centerline, up to 120' AGL/206' MSL. Multiple trees beginning 1046' from DER, 257' left of centerline, up to 120' AGL/195' MSL. **Rwy 34**, multiple trees beginning 417' from DER, 361' right of centerline, up to 120' AGL/206' MSL. Trees beginning 683' from DER, 491' left of centerline, up to 120' AGL/206' MSL. Pole 859' from DER, 548' left of centerline, 47' AGL/137' MSL.

EUREKA, CA

MURRAY FIELD (EKA)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 4 09239 (FAA)

TAKEOFF MINIMUMS: **Rwy 12**, std. w/ min. climb of 465' per NM to 1800 or 3800-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 12** climbing right turn heading 265° to intercept V27. For climb in visual conditions: cross Eureka airport at or above 3700 before proceeding on course. **Rwy 30**, climbing left turn heading 265° to intercept V27.

NOTE: **Rwy 12**, bush 50' from DER, 82' left of centerline, 6' AGL/16' MSL. Multiple trees beginning 1.5 NM from DER, 2993' left of centerline. Multiple trees beginning 1.6 NM from DER, 2318' right of centerline. **Rwy 30**, multiple trees, beginning 443' from DER, 389' right of centerline, up to 93' AGL/103' MSL. Tree 664' from DER, 587' left of centerline, 46' AGL/56' MSL. Pole 753' from DER, 155' right of centerline 27' AGL/ 37' MSL. Railroad 786' from DER, 4' left of centerline 23' AGL/31' MSL. Road beginning 602' from DER, 4' left of centerline up to 15' AGL/23' MSL. Bush 566' from DER, 69' left of centerline, 8' AGL/18' MSL.

FIREBAUGH, CA

FIREBAUGH (F34)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 12264 (FAA)

DEPARTURE PROCEDURE: **Rwy 12**, climbing right turn heading 134° to intercept the PXN VORTAC R-061 to MENDO INT. Aircraft departing MENDO INT heading 230° CW 150°, climb on course. All others, climb in MENDO INT holding pattern (hold NE, right turns, 241° inbound) to cross MENDO INT at or above 3000 before proceeding on course. **Rwy 30**, climbing left turn heading 180° to intercept PXN VORTAC R-061 to PXN VORTAC, continue climb in PXN VORTAC holding pattern (SW, right turns, 049° inbound) to cross PXN VORTAC at or above airway MEA/MCA for route of flight.

NOTE: **Rwy 30**, poles beginning 921' from DER, 525' left of centerline, up to 65' AGL/203' MSL. Elevator 1941' from DER, 739' right of centerline, 97' AGL/242' MSL.

FORTUNA, CA

ROHNERVILLE (FOT)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 3 86296 (FAA)

TAKEOFF MINIMUMS: **Rwy 11**, NA.

DEPARTURE PROCEDURE: Climb direct FOT VORTAC.

Continue climb in holding pattern (hold N, right turns, 161° inbound) to cross FOT VORTAC at or above 3000.

FRESNO, CA

FRESNO-CHANDLER EXECUTIVE (FCH)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 09015 (FAA)

DEPARTURE PROCEDURE: **Rwy 12**, climb heading 111° to 2000 then climbing right turn to 6300 via heading 200° and CZQ VORTAC R-167 before proceeding on course.

Rwy 30, climb heading 291° to 2000 then climbing left turn to 5500 via heading 140° and CZQ VORTAC R-167 before proceeding on course.

NOTE: **Rwy 12**, multiple trees, poles, and terrain beginning 84' from DER, 16' left of centerline, up to 92' AGL/371' MSL. Multiple trees, poles, road, fence and terrain beginning 53' from DER, 94' right of centerline, up to 62' AGL/341' MSL. **Rwy 30**, multiple trees, poles, bushes and terrain beginning 125' from DER, 46' left of centerline, up to 111' AGL/389' MSL. Multiple poles, road, and fence beginning 236' from DER, 23' right of centerline, up to 42' AGL/320' MSL.

FRESNO YOSEMITE INTL (FAT)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 8A 16147 (FAA)

DEPARTURE PROCEDURE: **Rwy 11L, 11R**, climbing left turn heading 291°, thence ...

Rwy 29L, 29R, climb heading 291°, thence ...

... Continue climb via heading 291° and FRA VORTAC R-202 to NIVEE INT/FRA 8 DME, Continue climb-in-hold (hold South, right turns, 022° inbound) to cross NIVEE at or above 5000.

NOTE: **Rwy 11L**, sign 1693' from DER, 863' right of centerline, 51' AGL/383' MSL. Tree 1420' from DER, 667' right of centerline, 375' MSL. Terrain 128' from DER, 506' right of centerline, 338' MSL. Pole 1228' from DER, 664' right of centerline, 33' AGL/365' MSL. Terrain 175' from DER, 271' left of centerline, 338' MSL. Pole 648' from DER, 542' left of centerline, 16' AGL/349' MSL. Electrical system 1223' from DER, 662' right of centerline, 30' AGL/363' MSL. **Rwy 11R**, poles beginning 1205' from DER, 394' right of centerline, up to 54' AGL/384' MSL. Electrical system 1598' from DER, 294' right of centerline, 57' AGL/386' MSL. Tower 664' from DER, 274' left of centerline, 34' AGL/362' MSL. Poles beginning 1598' from DER, 263' right of centerline, up to 55' AGL/385' MSL. Pole 329' from DER, 279' left of centerline, 21' AGL/349' MSL. **Rwy 29L**, trees beginning 998' from DER, 14' left of centerline, up to 396' MSL. Trees beginning 1659' from DER, 81' right of centerline, up to 379' MSL. Pole 1638' from DER, 427' right of centerline, 42' AGL/375' MSL. Pole 998' from DER, 620' left of centerline, 47' AGL/377' MSL. **Rwy 29R**, poles beginning 993' from DER, 547' right of centerline, up to 32' AGL/365' MSL. Tree 2315' from DER, 874' left of centerline, 395' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

**TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND
DIVERSE VECTOR AREA (RADAR VECTORS)**

GRASS VALLEY, CA

NEVADA COUNTY AIR PARK (GOO)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 98001 (FAA)
TAKEOFF MINIMUMS: **Rwy 7, NA.**
DEPARTURE PROCEDURE: **Rwy 25**, climb via MYV R-058 to 6000 then continue climb on course.

GROVELAND, CA

PINE MOUNTAIN LAKE (E45)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 16315 (FAA)
TAKEOFF MINIMUMS: **Rwy 9**, 600-2 $\frac{3}{4}$ or std. w/min. climb of 400' per NM to 4000.
DEPARTURE PROCEDURE: **Rwy 9**, turn right. **Rwy 27**, turn left. **All aircraft** climb direct LIN VOR/DME. Cross LIN VOR/DME at or above 5000.

HALF MOON BAY, CA

HALF MOON BAY (HAF)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 16259 (FAA)
TAKEOFF MINIMUMS: **Rwy 12**, 2600-2 or std. with a min. climb of 306' per NM to 3400. **Rwy 30, NA.**
DEPARTURE PROCEDURE: **Rwy 12**, climb runway heading to 3000, then climb direct OSI VOR/DME, to cross OSI VOR/DME at or above 3500 before proceeding on course.
NOTE: **Rwy 12**, tree 2556' from DER, 212' left of centerline, 90' AGL/104' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

ORIG 14289 (FAA)
Rwy 12, heading as assigned by ATC.

HANFORD, CA

HANFORD MUNI (HJO)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1A 16259 (FAA)
DEPARTURE PROCEDURE: **Rwy 14**, climbing left turn heading 050° to intercept V-23. **Rwy 32**, climbing right turn heading 050° to intercept V-23.
NOTE: **Rwy 14**: fence 9' from DER, 298' left of centerline, 244' MSL. Catenary 1293' from DER, 1293' left of centerline, 39' AGL/287' MSL. Poles beginning 1679' from DER, crossing centerline, up to 52' AGL/296' MSL. Trees beginning 2224' from DER, 391' left of centerline up to 313' MSL. **Rwy 32**: fence 168' from DER, 9' left of centerline, 245' MSL. Pole 588' from DER, 588' left of centerline, 25' AGL/278' MSL. Sign 614' from DER, 151' right of centerline, 9' AGL/261' MSL. Trees and poles beginning 592' from DER, 3' left of centerline, up to 300' MSL. Poles beginning 1127' from DER, 222' right of centerline, up to 40' AGL/293' MSL. Tree 2159' from DER, 434' right of centerline, 299' MSL.

HAYWARD, CA

HAYWARD EXECUTIVE (HWD)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 11013 (FAA)
DEPARTURE PROCEDURE: **Rwys 10L, 10R**, Climbing right turn direct OSI VORTAC. **Rwys 28L, 28R**, Climbing left turn direct OSI VORTAC.
NOTE: **Rwy 10L**, hangars, trees and buildings beginning 625' from DER, 67' left of centerline, up to 100' AGL/155' MSL. Trees beginning 2050' from DER, 1' right of centerline, up to 60' AGL/107' MSL. **Rwy 10R**, trees, poles, and buildings beginning 21' from DER, 61' left of centerline, up to 100' AGL/155' MSL. Windsock, blast fence, trees, buildings and pole beginning 23' from DER, 38' right of centerline, up to 74' AGL/119' MSL. **Rwy 28L**, trees beginning 899' from DER, 141' left of centerline, up to 93' AGL/108' MSL. Antennas, road, and trees beginning 108' from DER, 68' right of centerline, up to 87' AGL/102' MSL. **Rwy 28R**, antenna and trees beginning 728' from DER, 28' left of centerline, up to 87' AGL/102' MSL. Trees beginning 391' from DER, 4' right of centerline, up to 95' AGL/125' MSL.

**HAYWARD EXECUTIVE (HWD)
DIVERSE VECTOR AREA (RADAR VECTORS)**

AMDT 1 16007 (FAA)
Rwy 10L/R, Heading as assigned by ATC. **Rwy 28L/R**, Heading as assigned by ATC; requires minimum climb of 310' per NM to 4600.

HOLLISTER, CA

HOLLISTER MUNI (CVH)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 08157 (FAA)
TAKEOFF MINIMUMS: **Rwy 6, NA**-obstacles. **Rwy 24, NA**-ATC. **Rwy 13**, std. w/ min. climb of 391' per NM to 3500, or 3100-3 for climb in visual conditions. **Rwy 31**, std. w/ min climb of 209' per NM to 2300, or 3100-3 for climb in visual conditions.
DEPARTURE PROCEDURE: **Rwy 13**, climbing right turn to heading 332° and via SJC R-121 direct SJC VOR/DME to 6000 before proceeding on course or for climb in visual conditions: cross Hollister Muni Airport at or above 3100 MSL before proceeding on course. **Rwy 31**, climb heading 307° and via SJC R-121 direct SJC VOR/DME to 6000 before proceeding on course or for climb in visual conditions: cross Hollister Muni Airport at or above 3100 MSL before proceeding on course.
NOTE: **Rwy 13**, terrain beginning 992' from DER, 348' left of centerline, up to 289' MSL. Terrain beginning 2467' from DER, 154' right of centerline, up to 309' MSL, trees beginning 1277' from departure end of runway, 348' left of centerline, up to 309' MSL, trees beginning 2467' from DER, 153' right of centerline, up to 270' MSL. **Rwy 31**, terrain beginning 76' from DER, 392' left of centerline, up to 247' MSL. Terrain beginning 14' from DER, 179' right of centerline, up to 231' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017


TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND


DIVERSE VECTOR AREA (RADAR VECTORS)

17005

JACKSON, CA

WESTOVER FIELD AMADOR COUNTY (JAQ)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1 16315 (FAA)

DEPARTURE PROCEDURE: **Rwy 1**, turn left. **Rwy 19**, turn right. **All aircraft** climb direct LIN VOR/DME, continue climb on course.

LAKEPORT, CA

LAMPSON FIELD (1O2)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1 10098 (FAA)

TAKEOFF MINIMUMS: **Rwy 10**, std. with a min. climb of 400' per NM to 4500, do not exceed 210 Knots until intercepting the ENI R-073 or 3200-3 for climb in visual conditions. **Rwy 28**, NA-Rapidly rising terrain.

DEPARTURE PROCEDURE: **Rwy 10**, climbing left turn to 6000 via heading 310° and ENI R-073 to ENI VORTAC before proceeding on course, or for climb in visual conditions: cross Lampson Field at or above 4400 MSL before proceeding on course.

NOTE: **Rwy 10**, vehicle on road 347' from DER, 7' right of centerline, 15' AGL/1394' MSL. Trees beginning 280' from DER, 201' left of centerline, up to 100' AGL/1479' MSL. Trees beginning 494' from DER, 219' right of centerline, up to 100' AGL/1479' MSL.

LEMOORE NAS (REEVES FIELD) (KNLC)

LEMOORE, CA

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

07270

Rwy 14L, Cross DER at or above 15' AGL/235' MSL.

Rwy 14R, Cross DER at or above 15' AGL/245' MSL.

Rwy 32L, Cross DER at or above 15' AGL/ 234' MSL,

Departure headings 142° CW 283°, minimum military climb 220 ft/NM to 6400, minimum civil climb 220 ft/NM to 6600.

Rwy 32R, Cross DER at or above 15' AGL/239' MSL,

Departure headings 142° CW 281° minimum military climb 220 ft/NM to 6400, minimum civil climb 220 ft/NM to 6600.

LINCOLN, CA

LINCOLN RGNL/KARL HARDER FIELD (LHM)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 3 95201 (FAA)

DEPARTURE PROCEDURE: **Rwy 15**, climbing right turn.

Rwy 33, climbing left turn. **All aircraft** climb direct MYV VOR/DME, then climb on course.

DIVERSE VECTOR AREA (RADAR VECTORS)

ORIG 15036 (FAA)

Rwys 15,33, headings as assigned by ATC.

LITTLE RIVER, CA

LITTLE RIVER (LLR)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

ORIG 10154 (FAA)

DEPARTURE PROCEDURE: Use LITTLE RIVER DEPARTURE.

LIVERMORE, CA

LIVERMORE MUNI (LVK)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

TAKEOFF MINIMUMS: **Rwys 7L, 7R**, 1500-2 or std. with a min. climb of 260' per NM to 2200. **Rwys 25L, 25R**, 2300-2 or std. with a min. climb of 375' per NM to 3100.

DEPARTURE PROCEDURE: **Rwys 7L, 7R**, climb direct REIGA LOM, then climbing left turn via the 030° bearing from REIGA LOM to intercept V109, then proceed on course. **Rwys 25L, 25R**, climb runway heading to 1200, then climbing right turn via heading 020° and OAK R-060 to ALTAM Int, then proceed on course.

DIVERSE VECTOR AREA (RADAR VECTORS)

ORIG 15092 (FAA)

Rwys 7L, 7R, 25L, 25R, heading as assigned by ATC; requires minimum climb of 375' per NM to 5000.

LODI, CA

LODI (1O3)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2A 16315 (FAA)

TAKEOFF MINIMUMS: **Rwys 12, 30**, NA-Environmental. DEPARTURE PROCEDURE: **Rwy 8**, climb heading 076° to 600 then climbing right turn on LIN R-290 to LIN VOR/DME, thence... **Rwy 26**, climb heading 256° to 800 climbing right turn on heading 080° to intercept LIN R-290 to LIN VOR/DME, thence... ..continue climb in hold (hold Southeast, right turns, 326° inbound) to MCA or MEA for route of flight.

NOTE: **Rwy 8**, hangars, buildings, and vehicles on roadways beginning at DER, left and right of centerline, up to 25' AGL/84' MSL. Power lines beginning at 4.9 NM from DER, left and right of centerline, up to 160' AGL/220' MSL. **Rwy 26**, vehicles on roadway beginning 7' from DER, 265' right of centerline, up to 15' AGL/69' MSL. Trees beginning 15' from DER, left and right of centerline, up to 100' AGL/154' MSL. Power lines beginning at 4.6 NM from DER, left and right of centerline, up to 160' AGL/220' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

17005


TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND


DIVERSE VECTOR AREA (RADAR VECTORS)

**TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND
DIVERSE VECTOR AREA (RADAR VECTORS)**

LOS BANOS, CA

LOS BANOS MUNI (LSN)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 09351 (FAA)

DEPARTURE PROCEDURE: **Rwy 14**, climb on a heading between 318° CW to 151° from DER, or minimum climb of 320' per NM to 5100 for all other courses. **Rwy 32**, climb on a heading between 260° CW to 137° from DER, or minimum climb of 273' per NM to 5200 for all other courses.

NOTE: **Rwy 14**, multiple trees, poles, buildings beginning 3' from DER, 24' left of centerline, up to 73' AGL/194' MSL. Multiple trees, poles, buildings beginning 20' from DER, 21' right of centerline, up to 85' AGL/206' MSL. **Rwy 32**, multiple trees beginning 220' from DER, 453' right of centerline, up to 40' AGL/160' MSL. Multiple poles, beginning 1120' from DER, 173' left of centerline, up to 60' AGL/181' MSL.

MADERA, CA

MADERA MUNI (MAE)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 4 16203 (FAA)

TAKEOFF MINIMUMS: **Rwy 8, 26**, NA-Environmental. DEPARTURE PROCEDURE: **Rwy 12**, climbing left turn heading 334° and FRA R-243 to BEREN INT/FRA 18.6 DME before proceeding on course. **Rwy 30**, climbing right turn to intercept FRA R-243 to BEREN INT/FRA 18.6 DME before proceeding on course.

MAMMOTH LAKES, CA

MAMMOTH YOSEMITE (MMH)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 15064 (FAA)

DEPARTURE PROCEDURE: Use NIKOL DEPARTURE.

MARINA, CA

MARINA MUNI (OAR)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 10042 (FAA)

TAKEOFF MINIMUMS: **Rwy 11**, std. with a min. climb of 307' per NM to 4500, or 2000-2½ for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 11**, climb heading 108° and SNS VORTAC R-252 to SNS VORTAC, thence..., or for climb in visual conditions: cross Marina Muni Airport at or above 2100, then proceed on SNS VORTAC R-261 to SNS VORTAC, thence... **Rwy 29**, climb via heading 288° to 1200', then climbing right turn direct SNS VORTAC, thence...

All aircraft continue climb in SNS holding pattern (West, left turns, 084° inbound) to cross SNS VORTAC at or above MEA/MCA for direction of flight before proceeding on course.

NOTE: **Rwy 11**, windsock 32' from DER, 386' left of centerline, 8' AGL/148' MSL. **Rwy 29**, bush 158' from DER, 272' right of centerline, 10' AGL/142' MSL.

MARIPOSA, CA

MARIPOSA-YOSEMITE (MPI)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

ORIG 05020 (FAA)

TAKEOFF MINIMUMS: **Rwy 8**, N/A-Obstacles

DEPARTURE PROCEDURE: **Rwy 26**, climb via heading 265° to 3000, then climbing left turn to 7000 direct FRA VORTAC before proceeding on course.

NOTE: **Rwy 26**, tree 10' from DER, 313' left of centerline, 100' AGL/2265' MSL. Tree 1146' from DER, 303' left of centerline, 100' AGL/2298' MSL.

MARYSVILLE, CA

YUBA COUNTY (MYV)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1A 13178 (FAA)

DEPARTURE PROCEDURE: All runways, climb direct ILA VORTAC.

NOTE: **Rwy 5**, tree 750' from DER, 239' right of centerline, 44' AGL/109' MSL. Tower 986' from DER, 258' left of centerline, 46' AGL/108' MSL. Tree 1737' from DER, 191' left of centerline, 70' AGL/134' MSL. Tree 2792' from DER, 607' left of centerline, 81' AGL/145' MSL. **Rwy 23**, railroad 822' from DER, 1' right of centerline, 23' AGL/85' MSL. Building 903' from DER, 387' right of centerline, 29' AGL/89' MSL. **Rwy 32**, pole 1040' from DER, 717' left of centerline, 32' AGL/94' MSL. Tree 2487' from DER, 586' left of centerline, 75' AGL/134' MSL. Tree 3135' from DER, 672' right of centerline, 93' AGL/157' MSL.

MERCED, CA

MERCED RGNL/MACREADY FIELD (MCE)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 5B 15344 (FAA)

DEPARTURE PROCEDURE: **Rwy 12**, climbing right turn to 3000 via heading 330° and MOD R-120 to MOD. **Rwy 30**, climb to 3000 via heading 300° and MOD R-120 to MOD.

NOTE: **Rwy 12**, tree 1321' from DER, 785' left of centerline, 50' AGL/190' MSL. **Rwy 30**, bush 183' from DER, 490' right of centerline, 20' AGL/161' MSL. Bush 486' from DER, 604' left of centerline, 20' AGL/170' MSL. Tree 2457' from DER, 263' left of centerline, 50' AGL/220' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

MODESTO, CA

MODESTO CITY-COUNTY HARRY SHAM
FIELD (MOD)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 5A 13010 (FAA)

DEPARTURE PROCEDURE: **Rwys 28L, 28R**, climb on a heading between 256° CW to 109° from DER, or minimum climb of 230' per NM to 5000 for all other courses.

NOTE: **Rwy 10R**, trees beginning 169' from DER, 37' right of centerline, up to 91' AGL/195' MSL. Sign 57' from DER, 211' right of centerline, 15' AGL/89' MSL. Sign 16' from DER, 135' left of centerline, 4' AGL/87' MSL. Trees beginning 823' from DER, 79' left of centerline, up to 89' AGL/148' MSL. **Rwy 10L**, trees beginning 15' from DER, 65' right of centerline, up to 68' AGL/172' MSL. Vehicles on road beginning 178' from DER, 17' left of centerline, up to 15' AGL/96' MSL. Trees beginning 1413' from DER, 184' left of centerline, up to 63' AGL/126' MSL. **Rwy 28R**, vehicles on road beginning 47' from DER, 332' right of centerline, up to 15' AGL/114' MSL. Pole 754' from DER, 699' right of centerline, 34' AGL/133' MSL. Building 979' from DER, 697' right of centerline, 29' AGL/128' MSL. Tree 1390' from DER, 516' right of centerline, 37' AGL/136' MSL. Trees beginning 2077' from DER, 379' left of centerline, up to 79' AGL/173' MSL. **Rwy 28L**, multiple poles, trees, and buildings beginning 128' from DER, 34' left of centerline, up to 102' AGL/196' MSL. Vehicles on road beginning 448' from DER, 219' left of centerline, up to 15' AGL/112' MSL. Multiple poles and building beginning 1021' from DER, 350' right of centerline, up to 57' AGL/154' MSL. Trees beginning 1112' from DER, 20' right of centerline, up to 70' AGL/164' MSL.

MONTAGUE, CA

SISKIYOU COUNTY (SIY)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 2A 14009 (FAA)

TAKEOFF MINIMUMS: **Rwy 17**, CAT A,B 2400-2 or std. with a min. climb of 350' per NM to 5500. CAT C,D 4100-2 or std. with a min. climb of 350' per NM to 7400. **Rwy 35**, 4000-2 or std. with a min. climb of 300' per NM to 7000.

DEPARTURE PROCEDURE: **Rwy 17**, climb direct MOG NDB. Continue climb to 10000 in MOG holding pattern (hold N, right turns, 176° inbound). **Rwy 35**, climb to 7000 via runway heading and 356° bearing from MOG NDB, then climbing right turn to 10000 direct MOG NDB. All aircraft depart MOG NDB at or above MEA for route of flight.

MONTEREY, CA

MONTEREY RGNL (MRY)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 8 15344 (FAA)

TAKEOFF MINIMUMS: **Rwy 10L**, std. w/min. climb of 449' per NM to 1800, or 1700-2½ for climb in visual conditions.

Rwy 10R, std. w/min. climb of 459' per NM to 1800, or 1700-2½ for climb in visual conditions. **Rwy 28L**, std. w/min. climb of 218' per NM to 3300, or 1700-2½ for climb in visual conditions. **Rwy 28R**, std. w/min. climb of 205' per NM to 3300, or 1700-2½ for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 10L**, climbing left turn heading 045.00 and SNS VORTAC R-225 to SNS VORTAC, climb in SNS holding pattern (hold W, LT, 084° inbound) to cross SNS VORTAC at or above MEA/MCA for route of flight. **Rwy 10R**, climbing left turn heading 045° and SNS VORTAC R-225 to SNS VORTAC, climb in SNS holding pattern (hold W, LT, 084° inbound) to cross SNS VORTAC at or above MEA/MCA for route of flight.

Rwy 28L, climbing right turn heading 045° and SNS VORTAC R-260 to SNS VORTAC, climb in SNS holding pattern (hold W, LT, 084° inbound) to cross SNS VORTAC at or above MEA/MCA for route of flight. **Rwy 28R**, climbing right turn heading 045.00 and SNS VORTAC R-260 to SNS VORTAC, climb in SNS holding pattern (hold W, LT, 084° inbound) to cross SNS VORTAC at or above MEA/MCA for route of flight.

VCOA: Obtain ATC approval for climb in visual conditions when requesting IFR clearance. Climb in visual conditions to cross Monterey RGNL at or above 1800, then on SNS VORTAC R-231 to SNS VORTAC. Climb in SNS holding pattern (hold W, LT, 084° inbound) to cross SNS VORTAC at or above MEA/MCA for route of flight.

NOTE: **Rwy 10L**, NAVAID 556' from DER, 217' right of centerline, 20' AGL/272' MSL. Bushes beginning 1.6 NM from DER, 1188' left of centerline up to 9' AGL/729' MSL. Trees beginning 1.7 NM from DER, 923' left of centerline up to 102' AGL/764' MSL. Trees beginning 1.6 NM from DER, 1993' right of centerline up to 90' AGL/923' MSL. Bushes beginning 1.9 NM from DER, 2497' right of centerline up to 9' AGL/781' MSL. Tower 2 NM from DER 3305' left of centerline, 27' AGL/767' MSL. **Rwy 10R**, ground 11' from DER, 358' left of centerline 258' MSL. Tree 230' from DER 388' left of centerline 21' AGL/265' MSL. NAVAID 240' from DER, 282' left of centerline, 20' AGL/272' MSL. Bushes beginning 1.5 NM from DER, 2381' left of centerline, up to 9' AGL/648' MSL. Trees beginning 1.7 NM from DER, 388' left of centerline up to 76' AGL/629' MSL. Bushes beginning 1.8 NM from DER, 2005' right of centerline up to 9' AGL/741' MSL. Trees beginning 1.5 NM from DER, 1749' right of centerline up to 90' AGL/843' MSL. **Rwy 28L**, terrain abeam DER, 198' left of centerline, up to 163' MSL. Trees beginning 797' from DER, 678' left of centerline, up to 83' AGL/228' MSL. Tree 1008' from DER, 616' left of centerline, 100' AGL/195' MSL. Pole 1128' from DER, 716' left of centerline, 54' AGL/195' MSL. Tree 1372' from DER, 755' left of centerline, 93' AGL/227' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 16175 (FAA)

Rwy 10L, heading as assigned by ATC; requires minimum climb of 360' per NM to 2900. **Rwy 10R**, heading as assigned by ATC; requires minimum climb of 370' per NM to 2800. **Rwy 28L**, heading as assigned by ATC; requires minimum climb of 310' per NM to 1100. **Rwy 28R**, heading as assigned by ATC; requires minimum climb of 250' per NM to 1100.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

MOUNTAIN VIEW, CA

MOFFETT FEDERAL AFLD (NUQ)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 12292 (FAA)

TAKEOFF MINIMUMS: **Rwys 14L, 14R**, std. w/ min. climb of 550' per NM to 4000 or 1700-2½ for climb in visual conditions. **Rwys 32L, 32R**, std. w/ min. climb of 285' per NM to 3500 or 1700-2½ for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwys 14L, 14R**, climbing right turn direct OSI VORTAC, thence...

or for climb in visual conditions cross Moffett Federal Airfield at or above 1600 then on OSI R-066 to OSI VORTAC, thence...

When executing VCOA notify ATC prior to departure.

Rwys 32L, 32R, climb heading 322° to 700, then climbing left turn heading 230° until receiving OSI VORTAC, then direct OSI VORTAC, thence...

or for climb in visual conditions cross Moffett Federal Airfield at or above 1600 then on OSI R-066 to OSI VORTAC, thence...

When executing VCOA notify ATC prior to departure.

...continue climb in OSI VORTAC holding pattern (hold southeast, left turns, 321° inbound) to cross OSI VORTAC at or above MEA for route of flight.

NOTE: **Rwy 32R**, light support structures abeam DER, 76'

left and 76' right of centerline, up to 3' AGL/7' MSL.

Vehicles on road beginning 5' from DER, 92' left of

centerline, up to 15' AGL/20' MSL. Vehicles on road

beginning 512' from DER, 158' right of centerline, up to 15'

AGL/20' MSL. Fence 134' from DER, left and right of

centerline, up to 8' AGL/12' MSL. **Rwy 32L**, light support

structures abeam DER, 76' left and 76' right of centerline,

up to 1' AGL/5' MSL. Navaid 449' from DER, 315' right of

centerline, up to 17' AGL/21' MSL. Tree 1632' from DER,

934' left of centerline, up to 100' AGL/129' MSL. **Rwy**

14L, light support structure 13' from DER, 126' right of

centerline, up to 4' AGL/34' MSL. Vehicles on road

beginning 770' from DER, 547' right of centerline, 15'

AGL/53' MSL. Rail car on railroad beginning 774' from

DER, 261' right of centerline, up to 23' AGL/60' MSL.

Trees beginning 1191' from DER, 71' right of centerline, up

to 100' AGL/171' MSL. Trees beginning 1922' from DER,

109' left of centerline, up to 100' AGL/153' MSL. **Rwy 14R**,

light support structures abeam DER, 77' right and 77' left

of centerline, up to 3' AGL/37' MSL. Fence, 187' from

DER, 488' right of centerline, up to 8' AGL/45' MSL.

Vehicles on road beginning 207' from DER, 520' right of

centerline, 15' AGL/55' MSL. Rail car on railroad beginning

955' from DER, 342' left of centerline, up to 23' AGL/60'

MSL. Trees beginning 1066' from DER, 34' left of

centerline, up to 100' AGL/153' MSL.

NOVATO, CA

GNOSS FIELD (DVO)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 13122 (FAA)

TAKEOFF MINIMUMS: **Rwy 13**, 400-2¼ or std. w/ min. climb of 580' per NM to 500. **Rwy 31**, 600-2½ w/ min. climb of 285' per NM to 1500 or std. w/ min. climb of 679' per NM to 800 or 2000-2½ for climb in visual conditions...

DEPARTURE PROCEDURE: **Rwy 13**, climb heading 132° to 600 then turn left direct SGD VORTAC before proceeding on course. **Rwy 31**, climbing right turn direct SGD VORTAC before proceeding on course

... For climb in visual conditions, cross Gnoass Field at or above 1900' MSL then proceed direct SGD VORTAC before proceeding on course. When executing VCOA, notify ATC prior to departure.

NOTE: **Rwy 13**, trees beginning 2633' from DER, 627' left of centerline, up to 50' AGL/346' MSL. Trees beginning 3630' from DER, 1274' right of centerline, up to 50' AGL/369' MSL. Power line 1.7 NM from DER, 1980' left of centerline, 121' AGL/360' MSL. **Rwy 31**, trees beginning 3237' from DER, 321' left of centerline, up to 50' AGL/569' MSL.

OAKDALE, CA

OAKDALE (O27)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1 16315 (FAA)

DEPARTURE PROCEDURE: **Rwy 10**, climbing left turn via heading 020° and LIN VOR/DME R-124 to WRAPS INT/ LIN 16.66 DME. Climb in WRAPS holding pattern (Northwest, right turn, 124° inbound) to cross WRAPS INT at or above MEA for direction of flight. **Rwy 28**, climb via heading 276° and LIN VOR/DME R-146 to LIN VOR/DME to cross LIN VOR/DME at or above MEA for direction of flight.

NOTE: **Rwy 10**, terrain beginning 388' from DER, up to 279' MSL. **Rwy 28**, power line 3447' from DER, 407' right of centerline, 115' AGL/329' MSL.

NAPA, CA

NAPA COUNTY (APC)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 4 10154 (FAA)

DEPARTURE PROCEDURE: Use NAPAA DEPARTURE.

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

17005

OAKLAND, CA

METROPOLITAN OAKLAND INTL (OAK)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 7 13290 (FAA)

DEPARTURE PROCEDURE: **Rwys 10L, 10R, 12, 15, 30**, climbing right turn to intercept V107-301, thence ...

Rwys 28L, 28R, climb heading 278° to intercept V107-301, thence ...

Rwy 33, climbing left turn to intercept V107-301, thence...
... to cross COMMO INT at or above 4000, continue climb-in-hold (hold E, right turns, 288° inbound) to 4000 before proceeding on course.

NOTE: **Rwy 10L**, building, hanger and road beginning 225' from DER, 554' left of centerline, up to 37' AGL/42' MSL. Trees beginning 1644' from DER, 309' left of centerline, up to 59' AGL/67' MSL. **Rwy 10R**, Runway lights 9' from DER, 26' left and right of centerline, 1' AGL/9' MSL. Sign 63' from DER, 251' left of centerline, 4' AGL/10' MSL.

Signs, fence and poles beginning 361' from DER, 540' right of centerline up to 35' AGL/44' MSL. Signs and trees beginning 1160' from DER, 177' right of centerline, up to 36' AGL/50' MSL. **Rwy 12**, Runway end and ALS lights beginning 11' from DER, 9' left and right of centerline, 1' AGL/10' MSL. **Rwy 15**, ATCT 3613' from DER, 1017' left of centerline, 88' AGL/101' MSL. Obstruction light on WSK 813' from DER, 577' right of centerline, 24' AGL/27' MSL.

Rwy 28L, rising terrain beginning 8' from DER, crossing centerline, up to 9' MSL. Multiple trees beginning 105' from DER, 35' left of centerline, up to 64' AGL/80' MSL. Traffic lights and poles beginning 895' from DER, 164' left of centerline, up to 29' AGL/37' MSL. Substation 1593' from DER, 871' left of centerline, 37' AGL/53' MSL. Fence 95' from DER, 410' left of centerline, 6' AGL/13' MSL. Multiple trees beginning 994' from DER, 55' right of centerline, up to 91' AGL/96' MSL. **Rwy 28R**, multiple trees beginning 1745' from DER, 23' left of centerline, up to 91' AGL/96' MSL. Multiple trees beginning 2053' from DER, 88' right of centerline, up to 109' AGL/111' MSL. **Rwy 30**, light pole 582' from DER, 483' left of centerline, 16' AGL/26' MSL.

Rwy 33, multiple trees, buildings and poles beginning 256' from DER, 497' left of centerline, up to 41' AGL/45' MSL. Multiple trees, buildings, poles and towers beginning 762' from DER, 267' right of centerline, up to 39' AGL/51' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

ORIG 14289 (FAA)

Rwy 10L, headings as assigned by ATC; requires minimum climb of 340' per NM to 2300. **Rwy 10R**, headings as assigned by ATC; requires minimum climb of 330' per NM to 2300. **Rwys 12, 15**, headings as assigned by ATC.

Rwys 28L, 28R, 30, headings as assigned by ATC; requires minimum climb of 240' per NM to 2400. **Rwy 33**, headings as assigned by ATC; requires minimum climb of 210' per NM to 2400.

ORLAND, CA

HAIGH FIELD (O37)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1 94286 (FAA)

DEPARTURE PROCEDURE: **Rwy 15**, climbing left turn.

Rwy 33, climbing right turn. **All aircraft** climb via CIC R-238 to GONGS Int. Aircraft departing GONGS Int. 070° CW 240° or 290° CW 360° climb on course. All others climb in GONGS holding pattern (NE, right turns, 238° inbound) to depart GONGS Int at or above: 001° CW 069°, 3200; 241° CW 289°, 2300.

OROVILLE, CA

OROVILLE MUNI (OVE)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 3 13122 (FAA)

TAKEOFF MINIMUMS: **Rwy 2**, std. w/ min. climb of 260' per NM to 1700, or 1000-2/2% for climb in visual conditions. **Rwy 31**, 400-1¼ or std. w/ min. climb of 245' per NM to 600.

DEPARTURE PROCEDURE: **Rwy 2**, climbing left turn heading 170°, thence ...

or for climb in visual conditions: cross Oroville Muni airport at or above 1100 then proceed on MXW R-052 to TALUM INT/MXW 16.92 DME before proceeding on course. When executing VCOA, notify ATC prior to departure. **Rwy 31**, climbing left turn heading 170° thence ...

Rwys 13, 20, climbing right turn heading 290° thence ...

... All aircraft climb on MXW R-052 to TALUM INT/MXW 16.92 DME. Continue climb on course.

NOTE: **Rwy 2**, tree 513' from DER, 603' left of centerline, 52' AGL/236' MSL. Light poles beginning 1368' from DER, 537' right of centerline, up to 71' AGL/255' MSL. Windsock 1143' from DER, 350' right of centerline, 19' AGL/215' MSL. Ground 191' from DER, 489' right of centerline, 191' MSL. **Rwy 13**, light on pole 128' from DER, 293' right of centerline, 27' AGL/203' MSL. **Rwy 20**, pole 902' from DER, 655' right of centerline, 36' AGL/217' MSL. Vehicle on road 819' from DER, 376' left of centerline, 15' AGL/203' MSL. **Rwy 31**, obstruction light on transmission tower 1.4 NM from DER, 1825' right of centerline, 250' AGL/442' MSL. Tree 642' from DER, 638' left of centerline, 52' AGL/244' MSL.

PALO ALTO, CA

PALO ALTO (PAO)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

ORIG-B 15288 (FAA)

DEPARTURE PROCEDURE: **Rwy 13**, turn left.

Rwy 31, turn right. **All aircraft** climb direct SJC VOR/DME before proceeding on course.

NOTE: **Rwy 13**, building with ship mast 1325' from DER, 450' left of centerline, 60' AGL/67' MSL.

17005

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

17005

PETALUMA, CA

PETALUMA MUNI (O69)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 2 14317 (FAA)

TAKEOFF PROCEDURES: **Rwy 11**, std. w/min. climb of 235' per NM to 1500. **Rwy 29**, 300-1¼ or std. w/min. climb of 276' per NM to 400.

DEPARTURE PROCEDURE: **Rwy 11**, climb heading 108° to 1500 then continue climb direct SGD VORTAC. **Rwy 29**, climb heading 289° to 1500 then climbing left turn to 3000 direct SGD VORTAC. All aircraft continue climb to MEA for route of flight.

NOTE: **Rwy 11**, tree 1095' from DER, 779' right of centerline, 55' AGL/116' MSL. Sign 69' from DER, 141' right of centerline, 9' AGL/80' MSL. Vertical structure 8' from DER, 248' left of centerline, 10' AGL/81' MSL. Trees 172' from DER, beginning 399' left of centerline, up to 46' AGL/117' MSL. Trees 40' from DER, beginning 465' left of centerline, up to 40' AGL/111' MSL. **Rwy 29**, trees 1091' from DER, beginning 151' right of centerline, up to 91' AGL/172' MSL. Vertical structure 194' from DER, 248' right of centerline, up to 19' AGL/98' MSL. Trees 121' from DER, beginning 282' right of centerline, up to 51' AGL/132' MSL. Trees and buildings 88' from DER, beginning 292' left of centerline, up to 40' AGL/121' MSL. Trees 1363' from DER, 462' left of centerline, up to 96' AGL/177' MSL. Pole 1262' from DER, 90' left of centerline, 41' MSL/ 122' AGL. Poles 2508' from DER, beginning 87' left of centerline, up to 94' AGL/175' MSL.

PLACERVILLE, CA

PLACERVILLE (PVF)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 3 12320 (FAA)

TAKEOFF MINIMUMS: **Rwy 5**, NA-obstacles.

DEPARTURE PROCEDURE: **Rwy 23**, climb to 5000 on HNW R-226 then climbing right turn on HNW R-276 to HNW VOR/DME. Aircraft departing HNW VOR/DME R-180 CW R-303 climb on course; all others climb in HNW VOR/DME holding pattern (hold SW, right turns, 048° inbound) to cross HNW VOR/DME at or above MEA/MCA for direction of flight before proceeding on course.

NOTE: **Rwy 23**, hangar 20' from DER, 340' right of centerline, 27' AGL/2586' MSL.

PORTERVILLE, CA

PORTERVILLE MUNI (PTV)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 2 98057 (FAA)

TAKEOFF MINIMUMS: **Rwy 12**, 200-1 or std. with a min. climb rate of 220' per NM to 600.

DEPARTURE PROCEDURE: **Rwy 12**, climbing right turn. **Rwy 30**, climbing left turn. All aircraft climb direct to TTE VOR/DME. Aircraft departing TTE R-146 CW R-330 climb on course. All others, continue climb in TTE holding pattern (NW, right turns, 143° inbound) to cross: TTE R-331 CW R-060, 8600; R-061 CW R-145, 7000.

NOTE: 559' frost fan 3000' east southeast runway 12.

RED BLUFF, CA

RED BLUFF MUNI (RBL)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 4 11041 (FAA)

DEPARTURE PROCEDURE: **Rwy 15**, climb direct RBL VORTAC, thence... **Rwy 33**, climbing right turn direct RBL VORTAC, thence... ..continue climb in RBL holding pattern (S, right turns, 341° inbound) to cross RBL VORTAC at or above MEA for route of flight.

NOTE: **Rwy 15**, WSK 5' from DER, 258' right of centerline, 18' AGL/361' MSL. Tree 2065' from DER, 879' left of centerline, 100' AGL/449' MSL. **Rwy 33**, trees beginning 468' from DER, 563' left of centerline, up to 54' AGL/387' MSL. Trees beginning 587' from DER, 493' right of centerline, up to 73' AGL/393' MSL.

REDDING, CA

REDDING MUNI (RDD)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 5B 17005 (FAA)

DEPARTURE PROCEDURE: **Rwy 12**, climb on heading 122° and RBL R-344 to RBL VORTAC to 3000 before proceeding on course. **Rwy 16**, climbing left turn heading 110° and RBL R-344 to RBL VORTAC to 3000 before proceeding on course. **Rwy 30, 34**, climbing right turn heading 110° and RBL R-344 to RBL VORTAC to 3000 before proceeding on course.

NOTE: **Rwy 12**, bush 86' from DER, 388' left of centerline, 500' MSL. Fence 281' from DER, 330' left of centerline, 19' AGL/500' MSL. Trees beginning 462' from DER, 327' left of centerline, up to 541' MSL. Trees 1112' from DER, 209' left of centerline, up to 568' MSL. Transmission line towers, 1732' from DER, 677' left of centerline, up to 60' AGL/543' MSL. Trees beginning 1929' from DER, 285' left of centerline, up to 570' MSL. **Rwy 30**, pole and bldg, beginning 289' from DER, 385' left of centerline, up to 30' AGL/529' MSL. Pole 474' from DER, 442' left of centerline, 34' AGL/534' MSL. Pole 850' from DER, 524' right of centerline, 35' AGL/536' MSL. Bldg 1126' from DER, 528' left of centerline, 34' AGL/537' MSL. Trees beginning 1686' from DER, 326' right of centerline, 577' MSL. Trees beginning 1936' from DER, 210' left of centerline, up to 594' MSL. **Rwy 34**, sign 98' from DER, 356' left of centerline, 5' AGL/510' MSL. Tree 588' from DER, 483' left of centerline, 521' MSL. Tower 3311' from DER, 1033' left of centerline, 108' AGL/622' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

17005

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

RIO VISTA, CA

RIO VISTA MUNI (O88)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 12208 (FAA)

DEPARTURE PROCEDURE: **Rwy 7**, climbing left turn direct SAC VORTAC. If required, continue climb in SAC VORTAC holding pattern (hold, S, right turns, 016° inbound) to cross SAC VORTAC at or above MEA/MCA for route of flight. **Rwy 15**, climb to 800 then climbing left turn direct SAC VORTAC. If required, continue climb in SAC VORTAC holding pattern (hold, S, right turns, 016° inbound) to cross SAC VORTAC at or above MEA/MCA for route of flight. **Rwy 25**, climb to 500 then climbing right turn direct SAC VORTAC. If required, continue climb in SAC VORTAC holding pattern (hold, S, right turns, 016° inbound) to cross SAC VORTAC at or above MEA/MCA for route of flight. **Rwy 33**, climbing right turn direct SAC VORTAC. If required, continue climb in SAC VORTAC holding pattern (hold, S, right turns, 016° inbound) to cross SAC VORTAC at or above MEA/MCA for route of flight.

NOTE: **Rwy 7**, trees 11' from DER, 402' right of centerline, up to 20' AGL/39' MSL. Trees 184' from DER, 216' left of centerline, up to 20' AGL/39' MSL. **Rwy 15**, trees 917' from DER, 124' right of centerline, up to 20' AGL/49' MSL. Vehicle on road 168' from DER, 437' right of centerline, up to 15' AGL/44' MSL. Vehicle on road 268' from DER, 234' left of centerline, up to 15' AGL/34' MSL. Buildings 61' from DER, 354' right of centerline, up to 20' AGL/49' MSL. **Rwy 25**, trees 526' from DER, 169' left of centerline, up to 20' AGL/59' MSL. Vehicles on road 179' from DER, 228' left of centerline, up to 15' AGL/44' MSL. Buildings 231' from DER, 546' left of centerline, up to 20' AGL/49' MSL. **Rwy 33**, trees 316' from DER, 138' left of centerline, up to 20' AGL/39' MSL.

SACRAMENTO, CA

SACRAMENTO EXECUTIVE (SAC)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
ORIG 08325 (FAA)

NOTE: **Rwy 2**, multiple trees 1128' from DER, 108' left of centerline, up to 76' AGL/96' MSL. Antenna 1376' from DER, 663' left of centerline, 51' AGL/71' MSL. Trees 1858' from DER, 137' right of centerline, 73' AGL/93' MSL. **Rwy 12**, multiple trees 518' from DER, 26' left of centerline, up to 83' AGL/98' MSL. Light pole 507' from DER, 336' left of centerline, 37' AGL/52' MSL. Transmission pole 3971' from DER 647' left of centerline, 130' AGL/154' MSL. Multiple trees 475' from DER, 476' right of centerline up to 97' AGL/112' MSL. Light poles 711' from DER, 241' right of centerline, 36' AGL/51' MSL. **Rwy 16**, light pole 22' from DER, 481' left of centerline, 38' AGL/53' MSL. Antenna 540' from DER, 516' left of centerline, 53' AGL/67' MSL. Multiple trees beginning 1317' from DER, 36' left of centerline, up to 78' AGL/88' MSL. Multiple trees beginning 588' from DER, 195' right of centerline, up to 67' AGL/77' MSL. **Rwy 20**, multiple trees beginning 850' from DER, 626' left of centerline, up to 92' AGL/107' MSL. Multiple trees beginning 714' from DER, 515' right of centerline, up to 66' AGL/81' MSL. **Rwy 30**, obstruction light on hangers 460' from DER, 360' right of centerline, 25' AGL/43' MSL. Multiple trees beginning 631' from DER, 195' right of centerline, up to 56' AGL/74' MSL. Multiple trees beginning 1331' from DER, 247' left of centerline, up to 90' AGL/110' MSL. Antenna on building 1543' from DER, 442' left of centerline, 47' AGL/67' MSL. **Rwy 34**, trees 1724' from DER, 854' left of centerline, 56' AGL/74' MSL. Tree 2233' from DER, 1062' right of centerline, 79' AGL/99' MSL.

SACRAMENTO, CA (CON'T)

SACRAMENTO INTL (SMF)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 15008 (FAA)

DEPARTURE PROCEDURE: **Rwy 16L**, climb heading 164° to 700 before turning east.

NOTE: **Rwy 16L**, vehicles on road, 225' from DER, crossing runway centerline, 10' AGL/31' MSL. **Rwy 34L**, tree 3656' from DER, 1296' left of centerline, 98' AGL/123' MSL. **Rwy 34R**, pole 1786' from DER, 945' right of centerline, 46' AGL/73' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

ORIG 16175 (FAA)

Rwy 16L, heading as assigned by ATC; requires minimum climb of 220' per NM to 700.

SACRAMENTO MATHER (MHR)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

ORIG 94006 (FAA)

DEPARTURE PROCEDURE: **Rwys 4L,4R**, climbing right turn direct SAC VORTAC. **Rwys 22L,22R** climb direct SAC VORTAC.

SALINAS, CA

SALINAS MUNI (SNS)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 4 11321 (FAA)

TAKEOFF MINIMUMS: **Rwy 8**, std. w/min climb of 243' per NM to 800 or 1800-2½ for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 8**, climbing right turn to intercept SNS VORTAC R-124 to 5500 before proceeding on course or for climb in visual conditions: cross Salinas Muni Airport at or above 1700 then intercept SNS VORTAC R-124 to 5500 before proceeding on course. **Rwy 13**, climbing left turn to intercept SNS VORTAC R-124 to 5500 before proceeding on course. **Rwy 26**, climbing right turn to intercept SNS VORTAC R-264 to 5000 before proceeding on course. **Rwy 31**, climbing left turn to intercept SNS VORTAC R-264 to 5000 before proceeding on course.

NOTE: **Rwy 8**, trees beginning 1967' from DER, 900' left of centerline, up to 100' AGL/199' MSL. **Rwy 26**, tree, light pole and road beginning 109' from DER, 266' left of centerline, up to 38' AGL/98' MSL. Light pole and road beginning 137' from DER, 281' right of centerline, up to 40' AGL/100' MSL. Poles beginning 909' from DER, 232' right of centerline, up to 52' AGL/102' MSL. Antenna on building, tower and tree beginning 1645' from DER, 426' left of centerline, up to 116' AGL/176' MSL. Microwave tower and tree beginning 1909' from DER, 31' right of centerline, up to 85' AGL/145' MSL. **Rwy 31**, building, road, and trees beginning 170' from DER, 1' right of centerline, up to 79' AGL/159' MSL. Road and trees 205' from DER, 200' left of centerline, up to 63' AGL/133' MSL. Pole and trees beginning 1042' from DER, 5' left of centerline up to 102' AGL/172' MSL. Fence, poles and trees 1109' from DER, 202' right of centerline, up to 78' AGL/158' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

17005

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

SALINAS, CA (CON'T)

SALINAS MUNI (SNS)

DIVERSE VECTOR AREA (RADAR VECTORS)

ORIG 15064 (FAA)

Rwys 8, 13, heading as assigned by ATC; requires minimum climb of 330' per NM to 5000.

Rwys 26, 31, heading as assigned by ATC.

SAN ANDREAS, CA

CALAVERAS CO-MAURY RASMUSSEN FIELD (CPU)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1 16315 (FAA)

TAKEOFF MINIMUMS: **Rwy 13**, 1800-5 or std. w/min. climb of 300' per NM to 3700.

DEPARTURE PROCEDURE: **Rwy 13**, climb runway heading to 3100, then climbing right turn via LIN R-085 to LIN VOR/DME. **Rwy 31**, climb via heading 311° to 3000, then climbing left turn via Linden (LIN) VOR/DME R-029 to LIN VOR/DME.

NOTE: **Rwy 13**, windsock 4' from DER, 129' right of centerline, 14' AGL/1341' MSL. Lights 4' from DER, 68' right of centerline, up to 2' AGL/1330' MSL. Bush 24' from DER, 140' right of centerline, 3' AGL/1331' MSL. Tree 43' from DER, 287' right of centerline, up to 8' AGL/ 1336' MSL. Bush 26' from DER, 96' left of centerline, up to 1' AGL/1329' MSL. **Rwy 31**, tree 19' from DER, 242' left of centerline, up to 30' AGL/1335' MSL. Trees 220' from DER, 375' right of centerline, up to 40' AGL/1345' MSL. Pole 667' from DER, 653' left of centerline, 23' AGL/1326' MSL. Trees 1010' from DER, 651' right of centerline, up to 46' AGL/1351' MSL.

SAN CARLOS, CA

SAN CARLOS (SQL)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1 09295 (FAA)

TAKEOFF MINIMUMS: **Rwy 30**, NA.

DEPARTURE PROCEDURE: **Rwy 12**, climbing left turn via heading 120° and SJC VOR/DME R-281 to SJC VOR/DME before proceeding on course.

NOTE: **Rwy 12**, ground 0' from DER, 148' left of centerline, 0' AGL/11' MSL. Building 2' from DER, 167' right of centerline, 27' AGL/30' MSL. Levee beginning 117' from DER, 90' left of centerline, up to 12' AGL/12' MSL. Pole 715' from DER, 294' right of centerline, 34' AGL/38' MSL. Tower 1674' from DER, 741' right of centerline, 106' AGL/111' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

ORIG 16147 (FAA)

Rwy 12, headings as assigned by ATC; requires minimum climb of 470' per NM to 3400.

SAN FRANCISCO, CA

SAN FRANCISCO INTL (SFO)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 9 14205 (FAA)

TAKEOFF MINIMUMS: **Rwys 19L, 19R**, std. w/min. climb of 575' per NM to 2000. **Rwys 28L, 28R**, std. w/min. climb of 351' per NM to 1300.

DEPARTURE PROCEDURE: **Rwys 1L, 1R**, climb heading 014° to 2000, thence ...

Rwys 10L, 10R, climbing left turn heading 053° to intercept SFO R-090 eastbound to 2300; thence ...

Rwys 19L, 19R, climbing left turn heading 053° to intercept SFO R-090 eastbound to 2600, thence ...

Rwys 28L, 28R, climb heading 284° to 2000, thence ... continue climb on course.

NOTE: **Rwy 1L**, ships beginning 1646' from DER, right and left of centerline, up to 150' AGL/150' MSL. **Rwy 1R**, ships beginning 1173' from DER, right and left of centerline, up to 150' AGL/150' MSL. **Rwy 10L**, sign 62' from DER, 300' left of centerline, 4' AGL/15' MSL. Building and rod on building beginning 257' from DER, 560' left of centerline, up to 14' AGL/24' MSL. **Rwy 19L**, multiple poles beginning 548' from DER, 46' left of centerline, up to 20' AGL/48' MSL. Multiple poles and signs beginning 652' from DER, 337' right of centerline, up to 20' AGL/38' MSL. Multiple buildings, transmission towers, poles, trees, signs, electrical system beginning 937' from DER, 11' left of centerline, up to 100' AGL/127' MSL. Multiple buildings, transmission towers, poles, trees, signs, electrical system beginning 887' from DER, 61' right of centerline, up to 100' AGL/128' MSL. Multiple buildings 3831' from DER, 1138' left of centerline, up to 105' AGL/127' MSL. Multiple buildings and trees beginning 3831' from DER, 74' right of centerline up to 100' AGL/167' MSL. **Rwy 19R**, multiple poles, trees, electrical system beginning 454' from DER, 82' right of centerline, up to 40' AGL/60' MSL. Multiple transmission towers, trees beginning 918' from DER, 7' left of centerline, up to 80' AGL/96' MSL. Poles and electrical system 1188' from DER, 1' right of centerline, 44' AGL/50' MSL. Multiple transmission towers, trees beginning 1617' from DER, 16' right of centerline, up to 80' AGL/85' MSL. **Rwy 28L**, sign 19' from DER, 500' right of centerline, 5' AGL/9' MSL. Obstruction lights on DME beginning 277' from DER, 162' left of centerline, up to 16' AGL/26' MSL. Obstruction light on localizer beginning 219' from DER, on centerline, up to 10' AGL/17' MSL. Multiple poles, electrical system beginning 824' from DER, 300' left of centerline, up to 40' AGL/56' MSL. Multiple buildings, transmission towers, tank and pole beginning 1305' from DER, 370' left of centerline, up to 95' AGL/103' MSL. **Rwy 28R**, multiple signs, beginning 23' from DER, 140' right of centerline, up to 5' AGL/10' MSL. Terrain beginning 58' from DER, 146' right of centerline, up to 10' MSL. Sign, 63' from DER, 250' left of centerline 5' AGL/8' MSL. Terrain beginning 130' from DER, 235' left of centerline, up to 10' MSL. Antenna on building, obstruction light on DME, tree, beginning 556' from DER, 268' right of centerline, up to 35' AGL/43' MSL. Multiple poles beginning 918' from DER, 598' left of centerline, up to 22' AGL/35' MSL. Multiple buildings, trees beginning 1467' from DER, 683' right of centerline, up to 60' AGL/68' MSL. Multiple buildings, transmission towers, trees and electrical system beginning 1826' from DER, 123' left of centerline, up to 95' AGL/103' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 15232 (FAA)

Rwy 1L, 1R, headings as assigned by ATC; requires minimum climb of 420' per NM to 2600. **Rwy 10L, 10R**, headings as assigned by ATC.

17005

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

17005

SAN JOSE, CA

NORMAN Y MINETA SAN JOSE INTL (SJC)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 6C 16203 (FAA)

TAKEOFF MINIMUMS: **Rwy12 L/R**, 400-2½ or std. w/min. climb of 261' per NM to 500.DEPARTURE PROCEDURE: **Rwy 12L/R**, climbing right turn to 2000 on Heading 318° and on OAK R-135 to OAK VOR/ DME before proceeding on course. **Rwy 30L/R**, climb via heading 315° to 2000, then via OAK R-132 to OAK VOR/ DME before proceeding on course.

NOTE: Rwy 12L, fence 156' from DER, 57' left of centerline, 14' AGL/73' MSL. Ol on blast fence, 156' from DER, 57' left of centerline, 73' MSL. Pole 191' from DER, 81' left of centerline, 34' AGL/93' MSL. Trees beginning 286' from DER, 161' right of centerline, up to 107' MSL. T-L twr, pole beginning 466' from DER, 228' left of centerline, up to 46' AGL/105' MSL. Tree 1281' from DER, 529' left of centerline, 117' MSL. T-L twr 1731' from DER, 729' left of centerline, 86' AGL/156' MSL. Tree 1799' from DER, 273' left of centerline, 144' MSL. Tree 1887' from DER, 68' right of centerline, 124' MSL. T-L twr 3047' from DER, 543' left of centerline, 73' AGL/147' MSL. Building 1.2 NM from DER, 630' left of centerline, 170' AGL/250' MSL. Building 1.3 NM from DER, 1051' left of centerline, 265' MSL. Building 1.3 NM from DER, 445' left of centerline, 217' AGL/301' MSL. Building 1.3 NM from DER, 51' left of centerline, 228' AGL/309' MSL. Buildings beginning 1.3 NM from DER, 81' left of centerline, up to 312' MSL. Building 1.5 NM from DER, 975' left of centerline, 262' AGL/351' MSL. Building 1.5 NM from DER, 1591' left of centerline, 268' AGL/358' MSL. Buildings beginning 1.5 NM from DER, 82' left of centerline, up to 365' MSL. Buildings beginning 1.6 NM from DER, 280' right of centerline, up to 346' MSL. Buildings beginning 1.6 NM from DER, 350' right of centerline, up to 260' AGL/350' MSL. Building 1.6 NM from DER, 1977' left of centerline, 286' AGL/368' MSL. Buildings beginning 1.6 NM from DER, 640' left of centerline, up to 274' AGL/370' MSL. Building 1.9 NM from DER, 313' right of centerline, 284' AGL/373' MSL. Building 1.9 NM from DER, 282' right of centerline, 281' AGL/372' MSL. **Rwy 12R**, ol on loc 10' from DER, on centerline, 68' MSL. Ol on blast fence 45' from DER, 115' right of centerline, 75' MSL. Fence 45' from DER, 115' right of centerline, 14' AGL/75' MSL. Tree 269' from DER, 149' right of centerline, 100' MSL. Trees, beginning 285' from DER, 193' left of centerline, up to 107' MSL. Rd 338' from DER, 2' right of centerline, 82' MSL. Tree, pole beginning 519' from DER, 279' right of centerline, up to 122' MSL. Trees beginning 1798' from DER, 631' left of centerline, up to 144' MSL. Poles beginning 1948' from DER, 688' right of centerline, up to 59' AGL/128' MSL. Tree 2604' from DER, 551' right of centerline, 133' MSL. T-L twr 3046' from DER, 1243' left of centerline, 73' AGL/147' MSL. Tree 3079' from DER, 873' right of centerline, 142' MSL. Building 1.3 NM from DER, 1145' left of centerline, 217' AGL/301' MSL. Building 1.3 NM from DER, 751' left of centerline, 228' AGL/309' MSL. Buildings beginning 1.3 NM from DER, 781' left of centerline, up to 312' MSL. Building 1.5 NM from DER, 1676' left of centerline, 262' AGL/351' MSL. Building 1.5 NM from DER, 2291' left of centerline, 268' AGL/358' MSL. Buildings beginning 1.5 NM from DER, 134' left of centerline, up to 365' MSL. Building 1.6 NM from DER, 2678' left of centerline, 286' AGL/368' MSL. Buildings beginning 1.6 NM from DER, 1340' left of centerline, up to 274' AGL/370' MSL. Building 1.6 NM from DER, 345' right of centerline, 320' MSL. Building 1.9 NM from DER, 386' left of centerline, 284' AGL/373' MSL. Building 1.9 NM from DER, 417' left of centerline, 281' AGL/372' MSL.

SAN JOSE, CA (CON'T)

Rwy 30L, poles beginning 166' from DER, 494' left of centerline, up to 69' MSL. NAVAIID 174' from DER, on centerline, 7' AGL/44' MSL. Fence 184' from DER, 369' right of centerline, 15' AGL/51' MSL. Tree 308' from DER, 424' left of centerline, 71' MSL. Tree, pole beginning 473' from DER, 118' right of centerline, up to 72' MSL. Poles beginning 711' from DER, 544' right of centerline, up to 75' MSL. NAVAIID 782' from DER, 350' left of centerline, 47' AGL/83' MSL. Pole 1227' from DER, 607' left of centerline, 48' AGL/86' MSL. Pole 1315' from DER, 548' right of centerline, 49' AGL/80' MSL. Pole 1329' from DER, 743' left of centerline, 57' AGL/94' MSL. Tree 1852' from DER, 179' right of centerline, 85' MSL. Tree 2561' from DER, 738' right of centerline, 108' MSL. Trmsn twr, t-l twr, beginning 2616' from DER, 1130' left of centerline, up to 120' MSL. Pole 2806' from DER, 1215' left of centerline, 135' MSL. Pole 2897' from DER, 614' left of centerline, 113' MSL. Pole, t-l twr, beginning 4145' from DER, 1329' left of centerline, up to 152' MSL. **Rwy 30R**, pole 100' from DER, 449' right of centerline, 40' AGL/75' MSL. Fence 138' from DER 243' right of centerline, 13' AGL/47' MSL. Fence 184' from DER, 329' left of centerline, 15' AGL/51' MSL. Tree 411' from DER, 37' left of centerline, 70' MSL. Tree 473' from DER, 319' left of centerline, 72' MSL. Pole 526' from DER, 580' left of centerline, 26' AGL/61' MSL. Pole 657' from DER, 369' right of centerline, 53' AGL/84' MSL. Vehicle on rd beginning 688' from DER, on centerline, up to 68' MSL. Poles beginning 711' from DER, 57' left of centerline, up to 25' AGL/75' MSL. Pole 961' from DER, 133' right of centerline, 56' AGL/88' MSL. Pole 1315' from DER, 150' left of centerline, 49' AGL/80' MSL. Tree 1852' from DER, 519' left of centerline, 85' MSL. Tree 2561' from DER, 39' right of centerline, 108' MSL. Building 3424' from DER, 146' right of centerline, 96' AGL/124' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 16203(FAA)

Rwy 12L/12R, heading as assigned by ATC; requires minimum climb of 470' per NM to 5600. **Rwys 30L/30R**, heading as assigned by ATC; requires minimum climb of 490' per NM to 5600 and do not exceed 210 KTS until established on assigned heading.

REID-HILLVIEW OF SANTA CLARA COUNTY (RHV)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

TAKEOFF MINIMUMS: **Rwys 13L, 13R**, NA - environmental.

DEPARTURE PROCEDURE: Use DECOF DEPARTURE.

17005

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

**TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND
DIVERSE VECTOR AREA (RADAR VECTORS)**

SAN MARTIN, CA

SAN MARTIN (E16)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1A 15288 (FAA)

TAKEOFF MINIMUMS: **Rwy 14**, std. w/min. climb of 324' per NM to 2200 or 1700-2½ for climb in visual conditions.

Rwy 32, std. w/min. climb of 324' per NM to 1600 or 1700-2½ for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 14, all aircraft**, climb to 2100 on heading 141°. Aircraft departing northwest on V485, climbing left turn heading 284° to intercept SJC R-121 (V485) to SJC VOR/DME and proceed on course; aircraft departing southeast on V485, climb on SJC R-121 and proceed on course. For climb in visual conditions: cross San Martin airport northwest bound at or above 1900, then climb on SJC R-121 to SJC VOR/DME. When executing VCOA, notify ATC prior to departure. **Rwy 32, all aircraft**, climb to 1600 on heading 321°. Aircraft departing northwest on V485, climbing left turn heading 270° to intercept SJC R-121 (V485) to SJC VOR/DME and proceed on course; aircraft departing southeast on V485, climbing left turn heading 120° to intercept SJC R-121 (V485) southeast bound to GILRO INT and proceed on course. For climb in visual conditions cross San Martin airport northwest bound at or above 1900, then climb on SJC R-121 to SJC VOR/DME. When executing VCOA, notify ATC prior to departure.

NOTE: **Rwy 14**, multiple trees, poles and vehicles on road beginning 25' from DER, 800' left of centerline, up to 100' AGL/359' MSL. **Rwy 32**, multiple trees, poles and vehicles on road beginning 17' from DER, 1521' left of centerline, up to 100' AGL/399' MSL. Trees beginning 3.9 NM from DER, 1.1 NM right of center, up to 200' AGL/1239' MSL.

SANTA ROSA, CA

CHARLES M SCHULZ-SONOMA COUNTY
(STS)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 7 14317 (FAA)

TAKEOFF MINIMUMS: **Rwy 2**, std. with a min. climb of 319' per NM to 2400, or 1200-2½ for climb in visual conditions.

Rwy 32, std. with a min. climb of 391' per NM to 2500, or 1200-2½ for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwys 2, 32**, climbing left turn heading 164°, thence...

Rwy 14, climbing right turn heading 250°, thence...

Rwy 20, climb on heading 190°, thence...

...intercept and climb on STS R-202 to cross FREES INT at or above MEA for route of flight or continue climb in FREES holding pattern (hold SE, right turns, PYE VORTAC 335° inbound) to MEA for route of flight.

VCOA: **Rwys 2, 32**, obtain ATC approval for climb in visual conditions when requesting IFR clearance. Climb in visual conditions to cross STS VOR/DME southwest bound at or above 1200. Thence...

... Intercept and climb on STS R-202 to cross FREES INT at or above MEA for route of flight or continue climb in FREES holding pattern (hold SE, right turns, PYE VORTAC 335° inbound) to MEA for route of flight.

NOTE: **Rwy 2**, trees beginning 492' from DER, 36' left of centerline, up to 60' AGL/156' MSL. Trees beginning 515' from DER, 114' right of centerline, up to 55' AGL/156' MSL. Trees beginning 1000' from DER, 9' left of centerline, up to 100' AGL/178' MSL. Trees beginning 1109' from DER, 135' right of centerline, up to 100' AGL/184' MSL. Trees beginning 2104' from DER, 342' right of centerline, up to 100' AGL/196' MSL. Tree 2119' from DER, 619' right of centerline, up to 100' AGL/173' MSL. **Rwy 14**, tree 1' from DER, 498' right of centerline, 20' AGL/136' MSL. Light structure 6' from DER, 40' left of centerline, 1' AGL/121' MSL. Trees beginning 409' from DER, 602' left of centerline, up to 50' AGL/147' MSL. Trees beginning 1201' from DER, 275' left of centerline, up to 70' AGL/167' MSL. Tree 2194' from DER, 1034' right of centerline, 60' AGL/180' MSL. **Rwy 20**, tree 108' from DER, 462' right of centerline, 40' AGL/162' MSL. Trees beginning 1596' from DER, 403' left of centerline, up to 100' AGL/187' MSL. Trees beginning 1498' from DER, 566' right of centerline, up to 144' AGL/274' MSL. Trees beginning 2841' from DER, 109' left of centerline, up to 123' AGL/228' MSL. **Rwy 32**, trees beginning 67' from DER, 891' right of centerline, up to 55' AGL/158' MSL. Trees beginning 89' from DER, on centerline, up to 55' AGL/153' MSL. Tree 1492' from DER, 319' left of centerline, up to 60' AGL/158' MSL. Tree 3187' from DER, 140' left of centerline, 167' AGL/257' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)

17005

SOUTH LAKE TAHOE, CA

LAKE TAHOE (TVL)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 7 15008 (FAA)

TAKEOFF MINIMUMS: **Rwy 18**, std. w/min. climb of 804' per NM to 11500, or 1600-3 w/min. climb of 741' per NM to 11500, or 5000-3 for climb in visual conditions. **Rwy 36**, 300-1/4 or std. w/min. climb of 269' per NM to 6500.

DEPARTURE PROCEDURE: **Rwy 18**, climb heading 177° to 7900 then climbing right turn to intercept and climb on SWR R-133 to SWR VOR/DME thence ...

Rwy 36, climb heading 357° to intercept and climb on SWR R-113 to SWR VOR/DME thence ...
... proceed on course.

VCOA: **Rwy 18**, Obtain ATC approval for climb in visual conditions when requesting IFR clearance. Remain within 3 NM, climb in visual conditions to cross South Lake Tahoe airport at or above 11100 MSL then intercept and proceed on SWR-127 to SWR VOR/DME.

NOTE: **Rwy 18**, light pole 10' from DER, 41' left of centerline, 2' AGL/6270' MSL. Sign, pole, tree, and vehicles on road beginning 17' from DER, 229' right of centerline, up to 80' AGL/6349' MSL. Trees beginning 34' from DER, 353' left of centerline, up to 68' AGL/6337' MSL. Trees beginning 158' from DER, crossing centerline, up to 120' AGL/6420' MSL. Pole 263' from DER, 428' right of centerline, 102' AGL/6369' MSL. Buildings and a pole beginning 2654' from DER, 278' left of centerline, up to 43' AGL/6419' MSL. Rapidly rising terrain beginning 2.1 NM from DER, 1534' left of centerline, up to 7092' MSL. Tree 2.57 NM from DER, 1454' left of centerline, 117' AGL/7837' MSL. **Rwy 36**, vehicles on road beginning 18' from DER, 360' left of centerline, up to 15' AGL/6266' MSL. Trees, windsock, obstruction light on LDA antenna, and obstruction light on DME antenna beginning 118' from DER, 18' right of centerline, up to 85' AGL/6405' MSL.

Trees beginning 386' from DER, 170' left of centerline, up to 105' AGL/6345' MSL. Vehicles on road beginning 688' from DER, 69' right of centerline, up to 15' AGL/6341' MSL. Trees beginning 2788' from DER, 590' right of centerline, up to 126' AGL/6406' MSL. Trees beginning 2789' from DER, 1231' left of centerline, up to 122' AGL/6402' MSL.

STOCKTON, CA

STOCKTON METROPOLITAN (SCK)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

ORIG 09015 (FAA)

TAKEOFF MINIMUMS: **Rwy 29R**, 300-1/4 or std. w/ min. climb of 210' per NM to 300 or alternatively, with standard TAKEOFF minimums and a normal 200'/NM climb gradient, TAKEOFF must occur no later than 1300' prior to DER.

NOTE: **Rwy 11L**, truck on road 199' from DER, 439' left of centerline, 15' AGL/49' MSL. Obstruction light on blast fence and antenna on building beginning 294' from DER, 39' right of centerline, up to 20' AGL/50' MSL. **Rwy 29L**, antenna on building 2956' from DER, 1204' left of centerline, 90' AGL/117' MSL. Stack 5562' from DER, 1721' right of centerline, 143' AGL/171' MSL. **Rwy 29R**, obstruction light on grain elevator, 1.0 NM from DER, 1882' left of centerline, 161' AGL/191' MSL. Light tower and rod on field light tower beginning 245' from DER, 1' left of centerline up to 44' AGL/71' MSL. Stacks and light on silo beginning 256' from DER, 381' right of centerline, up to 144' AGL/171' MSL.

SUSANVILLE, CA

SUSANVILLE MUNI (SVE)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

ORIG 03359 (FAA)

DEPARTURE PROCEDURE: Use AMEDEE DEPARTURE.

TRACY, CA

TRACY MUNI (TCY)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 3 09295 (FAA)

TAKEOFF MINIMUMS: **Rwy 26**, 700-3 or std. w/ a min. climb of 320' per NM to 1000.

DEPARTURE PROCEDURE: **Rwy 8**, climb to 3000 via heading 073° and MOD VOR/DME R-264 to MOD VOR/DME before proceeding on course. **Rwy 12**, climbing left turn to 3000 to intercept MOD VOR/DME R-264 to MOD VOR/DME before proceeding on course. **Rwy 26**, climbing right turn to 3000 via heading 150° and MOD VOR/DME R-264 to MOD VOR/DME before proceeding on course.

Rwy 30, climbing right turn to 3000 via heading 150° to intercept MOD VOR/DME R-264 to MOD VOR/DME before proceeding on course.

NOTE: **Rwy 8**, tree 472' from DER, 198' left of centerline, 50' AGL/194' MSL. Fence 167' from DER, 8' right of centerline, 25' AGL/176' MSL. Vehicle on road 241' from DER, 412' left of centerline, 15' AGL/183' MSL. Vehicles on roads starting 241' from DER, 7' right of centerline, up to 15' AGL/189' MSL. Poles starting 403' from DER, 204' left of centerline, up to 54' AGL/208' MSL. Poles starting 727' from DER, 49' right of centerline, up to 54' AGL/212' MSL. **Rwy 12**, trees starting 436' from DER, 251' right of centerline, up to 72' AGL/253' MSL. Conveyor 1995' from DER, 504' left of centerline, 66' AGL/270' MSL. Poles starting 832' from DER, 396' right of centerline, up to 56' AGL/240' MSL. Obstruction light on hopper 1934' from DER, 274' right of centerline, 74' AGL/255' MSL. Vehicles on road starting 133' from DER, 272' left of centerline, up to 15' AGL/206' MSL. Fence 32' from DER 405' left of centerline, 25' AGL/194' MSL. **Rwy 26**, tree 1173' from DER, 180' right of centerline, 35' AGL/234' MSL. Trees starting 1067' from DER, 125' left of centerline, up to 35' AGL/794' MSL. Vehicle on road 236' from DER, 150' left of centerline, 15' AGL/214' MSL. Fence 69' from DER, 1333' left of centerline, 23' AGL/203' MSL. Rising terrain 11105' from DER, 2814' left of centerline, up to 739' MSL.

Rwy 30, trees starting 438' from DER, 30' right of centerline, up to 35' AGL/209' MSL. Tree 1079' from DER, 82' left of centerline, 35' AGL/214' MSL. Obstruction light on hopper 985' from DER, 353' right of centerline, 72' AGL/236' MSL. Bush 195' from DER, 364' left of centerline, 25' AGL/189' MSL. Light pole 1149' from DER, 160' left of centerline, 47' AGL/211' MSL. Obstruction light on building 2289' from DER, 65' right of centerline, 74' AGL/238' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

17005

TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)


TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND


DIVERSE VECTOR AREA (RADAR VECTORS)
TRAVIS AFB (KSUU)

FAIRFIELD, CA

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

11069

All Rwy: Comply with assigned SID or ATC radar vectors.

DEPARTURE PROCEDURE: **Rwy 3L**, Climb on a heading between 344° CW to 137° from DER. **Rwy 3R**, Climb on a heading between 328° CW to 140° from DER. **Rwy 21L/R**, Climb on a heading between 187° CW to 237° from DER.

TAKEOFF OBSTACLES: **Rwy 3L**, Potential vehicle, 15' AGL/72' MSL, 616' from DER, 289' left of centerline. Potential vehicle, 15' AGL/71' MSL, 615' from DER, 267' right of centerline. **Rwy 21L**, Light pole 15' AGL/83' MSL, 148' from DER, 546' left of centerline. Light pole 15' AGL/84' MSL, 346' from DER, 547' left of centerline. Light pole 15' AGL/84' MSL, 521' from DER, 548' left of centerline. Light pole 15' AGL/83' MSL, 702' from DER, 549' left of centerline. Light pole 15' AGL/84' MSL, 880' from DER, 549' left of centerline. Light pole 15' AGL/85' MSL, 926' from DER, 661' left of centerline.

TRUCKEE, CA

TRUCKEE-TAHOE (TRK)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 5 15008 (FAA)

TAKEOFF MINIMUMS: **Rwys 11, 20**, NA - obstacles.

DEPARTURE PROCEDURE: **Rwys 2, 29**, use TRUCK DEPARTURE.

TULARE, CA

MEFFORD FIELD (TLR)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

ORIG 93147 (FAA)

DEPARTURE PROCEDURE: **Rwy 13**, climbing right turn.

Rwy 31, climbing left turn. **All aircraft** climb direct to VIS VOR/DME. Aircraft departing VIS R-001 CW R-140 continue climb in VIS holding pattern (E, right turns, 287° inbound) to cross VIS VOR/DME at or above 4000. All other aircraft climb on course.

UKIAH, CA

UKIAH MUNI (UKI)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 2 14317 (FAA)

TAKEOFF MINIMUMS: **Rwy 15**, std. w/min. climb of 678' per NM to 3100 or 3100-2½ for climb in visual conditions.

Rwy 33, std. w/min. climb of 350' per NM to 5000, or 3100-2½ or climb in visual conditions

DEPARTURE PROCEDURE: **Rwy 15**, climb heading 151° to 3100 before proceeding on course. **Rwy 33**, climb heading 345° to 5000, then left turn direct to cross ENI VORTAC at or above 6000.

VCOA: **Rwys 15, 33**, obtain ATC approval for climb in visual conditions when requesting IFR clearance. Climb in visual conditions to cross UKIAH MUNI airport at or above 3700 before proceeding on course.

NOTE: **Rwy 15**, buildings and signs beginning 34' from DER, 493' right of centerline, up to 30' AGL/629' MSL. Road with vehicles beginning 70' from DER, 245' right of centerline, up to 15' AGL/624' MSL. Road with vehicles beginning 111' from DER, 256' left of centerline, up to 15' AGL/629' MSL. Poles and trees beginning 275' from DER, 357' right of centerline, up to 15' AGL/712' MSL. Trees and poles beginning 527' from DER, 452' left of centerline, up to 100' AGL/698' MSL. Trees beginning 1.2 NM from DER, 2023' right of centerline, up to 100' AGL/1073' MSL. Trees beginning 1.5 NM from DER, 1715' right of centerline, up to 100' AGL/1160' MSL. Trees beginning 2.4 NM from DER, 77' left of centerline, up to 100' AGL/1644' MSL. Trees beginning 3.5 NM from DER, 2704' right of centerline, up to 100' AGL/2331' MSL. **Rwy 33**, poles and trees beginning 27' from DER, 391' right of centerline, up to 100' AGL/679' MSL. Road with vehicles beginning 124' from DER, 147' right of centerline, up to 15' AGL/629' MSL. Trees and poles beginning 461' from DER, 555' right of centerline, up to 100' AGL/679' MSL. Road with vehicles beginning 587' from DER, 313' left of centerline, up to 15' AGL/637' MSL. Trees, poles and signs beginning 888' from DER, 506' left of centerline, up to 100' AGL/709' MSL. Building 1003' from DER, 553' right of centerline, 42' AGL/649' MSL. Tower 5774' from DER, 1155' left of centerline, 124' AGL/770' MSL. Trees beginning 5909' from DER, 1590' left of centerline, up to 100' AGL/769' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017

**TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND
DIVERSE VECTOR AREA (RADAR VECTORS)**

VACAVILLE, CA

NUT TREE (VCB)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 4 09127 (FAA)

TAKEOFF MINIMUMS: **Rwy 20**, std. w/ min. climb of 424' per NM to 1600, or 1200-2½ for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 2**, climbing right turn to intercept SAC R-242 to SAC VORTAC, to 2000 before proceeding on course. **Rwy 20**, climbing left turn to intercept SAC R-242 to SAC VORTAC, to 2000 before proceeding on course, or, for climb in visual conditions: cross Nut Tree Airport eastbound at or above 1300, then climb to 2000 via SAC R-242 to SAC VORTAC, proceed on course.

NOTE: **Rwy 2**, trees beginning 222' from DER, 514' left of centerline up to 106' AGL/225' MSL. Light pole 337' from DER, 534' left of centerline, 28' AGL/147' MSL. **Rwy 20**, pole 161' from DER, 500' left of centerline, 120' AGL/239' MSL. Trees beginning 269' from DER, 335' left of centerline, up to 117' AGL/236' MSL. Pole 777' from DER, 436' left of centerline, 119' AGL/238' MSL. Windssock 6' from DER, 166' right of centerline, 8' AGL/127' MSL. Fence 193' from DER, 202' right of centerline, 3' AGL/122' MSL.

VISALIA, CA

VISALIA MUNI (VIS)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 3 09239 (FAA)

DEPARTURE PROCEDURE: **Rwy 12**, climbing right turn via heading 230° to 2000 to intercept V23. **Rwy 30**, climbing left turn via heading 230° to 2000 to intercept V23.

NOTE: **Rwy 12**, tree 774' from DER, 618' right of centerline, 46' AGL/340' MSL. Tree 1327' from DER, 823' left of centerline, 55' AGL/349' MSL. **Rwy 30**, multiple trees beginning 179' from DER, 260' left of centerline, up to 54' AGL/343' MSL. Antenna on building 285' from DER, 250' right of centerline, 16' AGL/305' MSL. Truck on road 522' from DER, on centerline, 17' AGL/342' MSL. Railroad 690' from DER, 549' left of centerline, 23' AGL/317' MSL. Multiple trees beginning 876' to 3029' from DER, 341' to 461' left of centerline, up to 90' AGL/379' MSL. Multiple trees beginning 1886' from DER, 103' right of centerline, up to 58' AGL/347' MSL.

WATSONVILLE, CA

WATSONVILLE MUNI (WVI)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 5 11013 (FAA)

DEPARTURE PROCEDURE: Use WATSONVILLE DEPARTURE.

WILLITS, CA

ELLS FIELD-WILLITS MUNI (O28)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1 04218 (FAA)

DEPARTURE PROCEDURE: **Rwy 16**, use MENDOCINO RNAV DEPARTURE. **Rwy 34**, use FLUEN RNAV DEPARTURE.

WILLOWS, CA

WILLOWS-GLENN COUNTY (WLW)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 1B 15344 (FAA)

DEPARTURE PROCEDURE: **Rwy 13**, climbing right turn.

Rwy 16, climb heading 161°. **Rwys 31, 34**, climbing left turn. All aircraft climb direct to MXW VORTAC. Aircraft departing MXW Vortac R-330 CW R-220, climb on course. All others continue climb in MXW holding pattern (S, 350° inbound, left turns) to depart MXW Vortac 220° CW 290°, 6500, 291° CW 330°, 5500.

NOTE: **Rwy 16**, poles beginning 14' from DER, 409' right of centerline up to 35' AGL/172' MSL. **Rwy 34**, 55' AGL pole 530' from DER, 430' right of centerline. Pole 917' from DER, 404' right of centerline, 55' AGL/193' MSL.

WOODLAND, CA

WATTS-WOODLAND (O41)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

AMDT 3 09127 (FAA)

DEPARTURE PROCEDURE: **Rwy 18**, climb heading 185° and ILA R-151 to EMBER INT/ILA 48 DME before proceeding on course. **Rwy 36**, climbing left turn via heading 320° and ILA R-145 to ILA VORTAC before proceeding on course.

NOTE: **Rwy 18**, tree 2478' from DER, 283' right of centerline, 100' AGL/249' MSL. Vehicle on road 192' from DER, on centerline, 15' AGL/144' MSL. **Rwy 36**, tree 453' from DER, 69' left of centerline, 100' AGL/224' MSL. Vehicle on road 350' from DER, on centerline, 15' AGL/134' MSL. Tree 4489' from DER, 1688' left of centerline, 100' AGL/234' MSL.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017



INSTRUMENT APPROACH PROCEDURE CHARTS



IFR ALTERNATE AIRPORT MINIMUMS

Standard alternate minimums for non-precision approaches and approaches with vertical guidance [NDB, VOR, LOC, TACAN, LDA, SDF, VOR/DME, ASR, RNAV (GPS) or RNAV (RNP)] are 800-2. Standard alternate minimums for precision approaches (ILS, PAR, or GLS) are 600-2. Airports within this geographical area that require alternate minimums other than standard or alternate minimums with restrictions are listed below. NA - means alternate minimums are not authorized due to unmonitored facility, absence of weather reporting service, or lack of adequate navigation coverage. Civil pilots see FAR 91. IFR Alternate Minimums: Ceiling and Visibility Minimums not applicable to USA/USN/USAF. Pilots must review the IFR Alternate Minimums Notes for alternate airfield suitability.

NAME ALTERNATE MINIMUMS

ARCATA-EUREKA, CA
ARCATA (ACV) ILS Z Rwy 32
ILS Y or LOC/DME Rwy 32¹
RNAV (GPS) Rwy 1³
RNAV (GPS) Rwy 14
RNAV (GPS) Rwy 32²
VOR/DME Rwy 14

NA when local weather not available.

¹ILS, Categories A, B, C, D, 700-2.

²Category D, 800-2¹/₄.

³Categories A, B, 900-2; Category C, 900-2¹/₂; Category D, 900-2³/₄.

ATWATER, CA

CASTLE (MER) ILS or LOC/DME Rwy 31¹
RNAV (GPS) Rwy 13
RNAV (GPS) Rwy 31
VOR/DME Rwy 31

NA when local weather not available.

¹NA when control tower closed.

AUBURN, CA

AUBURN MUNI (AUN) RNAV (GPS) Rwy 7
NA when local weather not available.

BISHOP, CA

BISHOP (BIH) LDA/DME Rwy 16¹
RNAV (GPS) Y Rwy 12²
RNAV (GPS) Z Rwy 12³
VOR or GPS-A⁴, 3300-3

¹Categories A, B, 2300-2; Categories C, D, 2300-3.

²Categories A, B 2500-2; Category C, 2500-3.

³Categories A, B, 2300-2; Category C, 2300-3.

⁴NA when Bishop altimeter setting not available.

CHICO, CA

CHICO MUNI (CIC) VOR/DME Rwy 31R
NA when control tower closed except for operators with approved weather reporting service.

NAME ALTERNATE MINIMUMS

CONCORD, CA
BUCHANAN FIELD (CCR) RNAV (GPS) Y Rwy 19R
Categories A, B, 1000-2; Category C, 1000-3.

COLUMBIA, CA

COLUMBIA (O22) RNAV (GPS) Rwy 35
Categories A, B, 1100-2; Category C, 1100-3.

CRESCENT CITY, CA

JACK MC NAMARA
FIELD (CEC) RNAV (GPS) Rwy 12
RNAV (GPS) Rwy 36
VOR Rwy 12
VOR/DME Rwy 12
VOR/DME Rwy 36

NA when local weather not available.

FRESNO, CA

FRESNO YOSEMITE
INTL (FAT) ILS or LOC/DME Rwy 29R
LOC Rwy 11L
VOR/DME or TACAN Rwy 11L
VOR/DME or TACAN Rwy 29R
Category E, 900-2³/₄.

GRASS VALLEY, CA

NEVADA COUNTY
AIR PARK (GOO) RNAV (GPS) Rwy 7
NA when local weather not available.
Category D, 800-2¹/₄.

HALF MOON BAY, CA

HALF MOON
BAY (HAF) RNAV (GPS) Y Rwy 12
RNAV (GPS) Y Rwy 30
NA when local weather not available.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017





ALTERNATE MINS

17117

M3



NAME ALTERNATE MINIMUMS
OROVILLE, CA
 OROVILLE MUNI (OVE) **RNAV (GPS) Rwy 2**
VOR-A
 NA when local weather not available.

PALO ALTO, CA
 PALO ALTO (PAO).....**VOR/DME Rwy 31**
 NA when control tower closed.

PETALUMA, CA
 PETALUMA MUNI (O69).... **RNAV (GPS) Rwy 29**
 NA when local weather not available.

PLACERVILLE, CA
 PLACERVILLE (PVF)..... **RNAV (GPS) Rwy 5**
 NA when local weather not available.

RED BLUFF, CA
 RED BLUFF
 MUNI (RBL).....**RNAV (GPS) Rwy 15¹**
RNAV (GPS) Rwy 33
VOR Rwy 33
VOR/DME Rwy 15¹
 NA when local weather not available.
¹Category D, 800-2¼.

REDDING, CA
 REDDING
 MUNI (RDD)..... **ILS or LOC/DME Rwy 34¹²³**
LOC/DME BC Rwy 16²³
RNAV (GPS) Rwy 34³
VOR Rwy 34⁴
¹ILS, Categories A, B, C, D, 700-2; Category E, 900-3. LOC, Category E, 900-3.
²NA when control tower closed.
³NA when local weather not available.
⁴Category C, 800-2¼; Category D, 800-2½.

SACRAMENTO, CA
 SACRAMENTO
 EXECUTIVE (SAC) **ILS or LOC Rwy 2¹**
RNAV (GPS) Rwy 2
VOR Rwy 2
 NA when local weather not available.
¹NA when control tower closed.

SACRAMENTO
 INTL (SMF)..... **ILS or LOC Rwy 16L³**
ILS or LOC Rwy 34L²
RNAV (GPS) Y Rwy 16L¹
RNAV (GPS) Y Rwy 34R¹
¹Category D, 900-2¾.
²NA when local weather not available.
³ILS, LOC Category D, 900-2¾.

NAME ALTERNATE MINIMUMS
SACRAMENTO, CA (CON'T)
 SACRAMENTO
 MATHER (MHR) **ILS or LOC/DME Rwy 22L**
 NA when control tower closed.
 Category E, 800-2½.

SALINAS, CA
 SALINAS MUNI (SNS) **ILS Rwy 31¹**
LOC/DME Rwy 31²
RNAV (GPS) Rwy 13¹²
RNAV (GPS) Y Rwy 31¹²
RNAV (GPS) Z Rwy 31¹
VOR Rwy 13³
¹NA when local weather not available.
²Category D, 800-2¼.
³Category D, 1000-3.

SAN CARLOS, CA
 SAN CARLOS (SQL) **RNAV (GPS) Y Rwy 30¹**
RNAV (GPS) Z Rwy 30²
 NA when local weather not available.
¹Categories A, B, 1300-2.
²Categories A, B, 900-2.

SAN FRANCISCO, CA
 SAN FRANCISCO
 INTL (SFO) **ILS or LOC Rwy 19L²**
ILS or LOC Rwy 28L⁶
ILS or LOC Rwy 28R³
RNAV (GPS) Rwy 10L¹
RNAV (GPS) Rwy 28L⁷
RNAV (GPS) Y Rwy 10R²
RNAV (GPS) Z Rwy 28R⁴
RNAV (RNP) Z Rwy 10R⁵

¹Categories A, B, 1200-2, Categories C, D, 1200-3.
²Categories A, B, 1800-2; Categories C, D, 1800-3.
³ILS, Category A, 700-2; Category B, 1000-2; Category C, 1600-3; LOC, Category B, 1000-2; Category C, 1600-3.
⁴Category B, 1000-2; Category C, 1600-3.
⁵Categories A, B, C, D, 1100-4.
⁶ILS, LOC, Categories A, B, 1100-2; Category C, 1600-3.
⁷Categories A, B, 1100-2; Category C, 1600-3; Category D, 1100-2½.

SAN JOSE, CA
 NORMAN Y MINETA SAN JOSE
 INTL (SJC) **ILS or LOC Rwy 12R**
ILS or LOC Rwy 30L
 NA when control tower closed.

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017



ALTERNATE MINS

17117

M3

SW-2





17117

NAME	ALTERNATE MINIMUMS	NAME	ALTERNATE MINIMUMS
SANTA ROSA, CA			
CHARLES M SCHULZ-SONOMA			
COUNTY (STS).....	ILS or LOC/DME Rwy 32¹²³		
	RNAV (GPS) Rwy 14²⁴		
	RNAV (GPS) Rwy 2²⁴		
	RNAV (GPS) Rwy 32⁴		
	VOR/DME Rwy 14²⁴		

- ¹NA when control tower closed.
- ²NA when local weather not available.
- ³ILS, LOC, Category C, 1000-3; Category D, 1300-3.
- ⁴Category C, 1000-3; Category D, 1300-3.

STOCKTON, CA			
STOCKTON METROPOLITAN			
(SCK)	ILS or LOC Rwy 29R		
NA when control tower closed.			
¹ ILS, Categories C, D, 700-2.			

UKIAH, CA			
UKIAH MUNI (UKI)	RNAV (GPS)-B¹		
	VOR-A²		
¹ Categories A, B, 2000-2; Categories C, D, 2000-3.			
² Categories A, B, 2800-2; Categories C, D, 2800-3.			

VACAVILLE, CA			
NUT TREE (VCB).....	VOR/DME-A		
NA when local weather not available.			

VISALIA, CA			
VISALIA			
MUNI (VIS)	ILS or LOC/DME Rwy 30		
	RNAV (GPS) Rwy 12		
	RNAV (GPS) Rwy 30		
	VOR Rwy 12		
NA when local weather not available.			

WATSONVILLE, CA			
WATSONVILLE			
MUNI (WVI)	RNAV (GPS) Rwy 2		
	VOR/DME-A¹		
NA when local weather not available.			
¹ Categories A, B, 1200-2; Categories C, D, 1200-3.			

27 APR 2017 to 25 MAY 2017

27 APR 2017 to 25 MAY 2017



17117