

WAAS CH 62905 W04B	APP CRS 042°	Rwy Idg TDZE Apt Elev	7500 658 672
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 4L

CHICAGO-O'HARE INTL (ORD)



▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 39°C (102°F). Simultaneous approach authorized with Rwy 4R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MISSED APPROACH: Climb to 1300 then climbing left turn to 4000 direct OBK VOR/DME and hold.

CHICAGO APP CON	O'HARE TOWERS		GND CON (TWR NORTH)	(TWR CENTER)	CLNC DEL
119.0 393.1	128.15 348.0 (Rwy 9L/27R)	133.0 348.0 (10R/28L)	124.125 118.05 (TWR SOUTH)	121.75 121.9 (OBND) (IBND)	121.6
	120.75 121.15 126.9 132.7 348.0 (CENTER)		226.675 (ALL TWRs)	134.15	

ATIS
135.4
282.225

RADAR REQUIRED



CATEGORY	A	B	C	D
LPV DA		858/40	200 (200-¾)	
LNAV/VNAV DA		1117-1½	459 (500-1½)	
LNAV MDA	1180/55	522 (600-1¼)	1180-1½	522 (600-1½)
CIRCLING	1220-1	548 (600-1)	1220-1½ 548 (600-1½)	1240-2 568 (600-2)

