



INSTRUMENT APPROACH PROCEDURE CHARTS



IFR ALTERNATE AIRPORT MINIMUMS

Standard alternate minimums for non-precision approaches and approaches with vertical guidance [NDB, VOR, LOC, TACAN, LDA, SDF, VOR/DME, ASR, RNAV (GPS) or RNAV (RNP)] are 800-2. Standard alternate minimums for precision approaches (ILS, PAR, or GLS) are 600-2. Airports within this geographical area that require alternate minimums other than standard or alternate minimums with restrictions are listed below. NA - means alternate minimums are not authorized due to unmonitored facility, absence of weather reporting service, or lack of adequate navigation coverage. Civil pilots see FAR 91. IFR Alternate Minimums: Ceiling and Visibility Minimums not applicable to USA/USN/USAF. Pilots must review the IFR Alternate Minimums Notes for alternate airfield suitability.

NAME ALTERNATE MINIMUMS
BABELTHUAP, KOROR, PS

BABELTHUAP/
KOROR (ROR)..... NDB Rwy 9¹
RNAV (GPS) Rwy 9
RNAV (GPS) Rwy 27

NA except standard for operators with approved weather reporting service.

¹Categories A, B, 900-2; Category C, 900-2½; Category D, 900-2½.

GUAM, GQ

GUAM INTL (GUM)..... ILS or LOC Rwy 6L¹
ILS or LOC Rwy 6R¹
RNAV (GPS) Y Rwy 6R²
RNAV (GPS) Y Rwy 24L³
RNAV (GPS) Y Rwy 24R⁵
RNAV (RNP) Z Rwy 24L⁴
RNAV (RNP) Z Rwy 24R⁶
VOR/DME or TACAN Rwy 24R⁵

¹ILS, LOC, Categories A, B, 1200-2; Categories C, D, 1200-3.

²Category D, 800-2½.

³Categories A, B, 900-2; Category C, 900-2½; Category D, 900-3.

⁴Categories A, B, C, D, 900-3.

⁵Categories A, B, 900-2; Category C, 900-2½; Category D, 900-2½.

⁶Categories A, B, C, D, 800-2½.

NAME ALTERNATE MINIMUMS
HONOLULU, HI

DANIEL K. INOUYE
INTL (HNL)..... LDA Rwy 26L¹
LOC Rwy 4R¹
LOC Rwy 8L¹
RNAV (GPS) Rwy 4L²
RNAV (GPS) Rwy 8R²
RNAV (GPS) Y Rwy 4R¹
RNAV (GPS) Y Rwy 8L²
VOR or TACAN Rwy 4R¹
VOR or TACAN-A¹
VOR or TACAN-B¹

¹Category C, 800-2½; Category D, 1400-3.

²Category C, 800-2½; Category D, 1400-3; Category E, 2000-3.

KAHULUI, HI

KAHULUI (OGG)..... ILS or LOC Rwy 2³
NDB Rwy 2¹⁴
RNAV (GPS) Rwy 20
RNAV (GPS) Rwy 23
RNAV (GPS) Y Rwy 2
VOR Rwy 20
VOR/DME or TACAN Rwy 20

Category D, 1200-3.

¹⁴NA when control tower closed.

²Category C, 800-2½.

³Category D, 1200-3; Category E, 1800-3.

⁴Category C, 800-2½; Category D, 1200-3.

KAILUA-KONA, HI

KONA INTL AT
KEAHOLE (KOA) ILS or LOC/DME Rwy 17¹
LOC/DME BC Rwy 35²
RNAV (GPS) Y Rwy 17²
RNAV (GPS) Y Rwy 35²
RNAV (GPS) Z Rwy 35²
VOR/DME or TACAN Rwy 17²
VOR/DME or TACAN Rwy 35²

¹NA when control tower closed.

²NA when local weather not available.

12 OCT 2017 to 07 DEC 2017

12 OCT 2017 to 07 DEC 2017





ALTERNATE MINS

17285

M2



NAME ALTERNATE MINIMUMS
KAMUELA, HI
 WAIMEA-
 KOHALA (MUE) **VOR/DME-A**
VOR/DME Rwy 4¹

Categories A, B, 1100-2, Category C, 1100-3,
 Category D, 1300-3.

¹Categories A, B, 900-2, Category C, 900-2½,
 Category D, 1300-3.

KAPOLEI, OAHU ISLAND, HI
 KALAELOA (JOHN RODGERS
 FIELD) (JRF) **NDB Rwy 4R¹**
RNAV (GPS) Rwy 4R²

¹Category C, 800-2¼; Category D, 800-2½.

²NA when local weather not available.

KAUNAKAKAI, HI
 MOLOKAI (MKK) **RNAV (GPS)-B²**
VOR or TACAN-A¹

¹Categories A, B, 1400-2; Categories C, D,
 1400-3.

²Category C, 1300-3; Category D, 1500-3.

KOSRAE, FM
 KOSRAE (TTK) **NDB/DME-A¹²**
RNAV (GPS) Rwy 5³
RNAV (GPS) Rwy 23⁴

¹NA when NDB (UKS) not monitored or local
 weather not available. Both NDB (UKS)
 monitored and local weather available Monday
 through Saturday from 2100 UTC to 0500 UTC
 (0800 local to 1600 local).

²800-3.

³NA except standard for operators with approved
 weather reporting service.

⁴NA except categories A,B, standard, Category
 C, 800-2¼, Category D 800-2½, for operators
 with approved weather reporting service.

LANAI CITY, HI
 LANAI (LNY) **VOR or TACAN or GPS-A**
 NA when local weather not received except for
 operators with approved weather reporting
 service.

LIHUE, HI
 LIHUE (LIH) **ILS or LOC Rwy 35¹**
RNAV (GPS) Rwy 17²
RNAV (GPS) Y Rwy 21²
RNAV (GPS) Y Rwy 35³
VOR/DME or TACAN Rwy 21²

¹ILS, LOC, NA when control tower closed;
 LOC, Category E, NA.

²Category B, 900-2; Category C, 1000-2¾;
 Category D, 1000-3.

³Category C, 800-2¼; Category D, 800-2½.

NAME ALTERNATE MINIMUMS
MAJURO ATOLL, RM
 MARSHALL
 ISLANDS INTL (MAJ) **RNAV (GPS) Rwy 7**
RNAV (GPS) Rwy 25
 NA when local weather not available.

MIDWAY ATOLL, MQ
 HENDERSON FIELD (MDY) **NDB Rwy 6**
NDB Rwy 24
RNAV (GPS) Rwy 6
RNAV (GPS) Rwy 24
 NA except standard for operators with approved
 weather reporting service.

PAGO PAGO, AQ
 PAGO PAGO INTL (PPG) **NDB-C¹**
VOR-D²

¹Category D, 800-2¼.

²Categories A, B, 1200-2; Categories C, D,
 1200-3.

POHNPEI ISLAND, FM
 POHNPEI INTL (PNI) **NDB-A³**
NDB or GPS-B¹²
NDB or GPS-C¹²
NDB/DME Rwy 9¹, 800-3
RNAV (GPS) Rwy 27²
RNAV (GPS) X Rwy 9³

¹NA when local weather not available.

²Category D, 800-2¼.

³Categories A, B, 1000-2; Categories C, D,
 1000-3.

ROTA ISLAND, CQ
 BENJAMIN TAISACAN
 MANGLONA INTL (GRO) **RNAV (GPS) Rwy 9**
RNAV (GPS) Rwy 27
NDB Rwy 9¹
NDB Rwy 27

NA except standard for operators with
 approved weather reporting service.

¹Categories A, B, 1200-2; Categories C, D,
 1200-3.

SAIPAN ISLAND, CQ
 FRANCISCO C ADA/
 SAIPAN INTL (GSN) **NDB Y Rwy 7**
 Category D, 800-2¼.

TINIAN ISLAND, CQ
 TINIAN INTL (TNI) **RNAV (GPS) Rwy 8**
RNAV (GPS) Rwy 26

Category D, 800-2¼.

NA when local weather not available.

12 OCT 2017 to 07 DEC 2017

12 OCT 2017 to 07 DEC 2017



ALTERNATE MINS

17285

M2

PAC





ALTERNATE MINS

M3



17285

NAME	ALTERNATE MINIMUMS	NAME	ALTERNATE MINIMUMS
------	--------------------	------	--------------------

WENO ISLAND, FM

CHUUK INTL (TKK) **NDB/DME Rwy 4¹**
NDB or GPS-A¹
NDB or GPS-B¹
RNAV (GPS) Rwy 4²

¹800-3.

²NA except standard for operators with approved weather reporting service.

YAP ISLAND, FM

YAP INTL (T11)..... **NDB Rwy 25¹**
NDB/DME Rwy 25²

¹Categories A, B, 900-2; Category C, 900-2³/₄; Category D, 900-3.

²Categories A, B, 900-2; Category C, 900-2¹/₂; Category D, 900-2³/₄.

12 OCT 2017 to 07 DEC 2017

12 OCT 2017 to 07 DEC 2017



ALTERNATE MINS

M3

PAC



17285



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

INSTRUMENT APPROACH PROCEDURE CHARTS



IFR TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

Civil Airports and Selected Military Airports

ALL USERS: Airports that have Departure Procedures (DPs) designed specifically to assist pilots in avoiding obstacles during the climb to the minimum enroute altitude, and/or airports that have civil IFR takeoff minimums other than standard, are listed below. Takeoff Minimums and Departure Procedures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in MSL.

DPs specifically designed for obstacle avoidance are referred to as Obstacle Departure Procedures (ODPs) and are textually described below, or published separately as a graphic procedure. If the ODP is published as a graphic procedure, its name will be listed below, and it can be found in either this volume (civil), or the applicable military volume, as appropriate. Users will recognize graphic obstacle DPs by the term "(OBSTACLE)" included in the procedure title; e.g., TETON TWO (OBSTACLE). If not specifically assigned an ODP, SID, or radar vector as part of an IFR clearance, an ODP may be required to be flown for obstacle clearance, even though not specifically stated in the IFR clearance. When doing so in this manner, ATC should be informed when the ODP being used contains a specified route to be flown, restrictions before turning, and/or altitude restrictions.

Some ODPs, which are established solely for obstacle avoidance, require a climb in visual conditions to cross the airport, a fix, or a NAVAID in a specified direction, at or above a specified altitude. These procedures are called Visual Climb Over Airport (VCOA). To ensure safe and efficient operations, the pilot must verbally request approval from ATC to fly the VCOA when requesting their IFR clearance.

At some locations where an ODP has been established, a diverse vector area (DVA) may be created to allow radar vectors to be used in lieu of an ODP. DVA information will state that headings will be as assigned by ATC and climb gradients, when applicable, will be published immediately following the specified departure procedure.

Graphic DPs designed by ATC to standardize traffic flows, ensure aircraft separation and enhance capacity are referred to as "Standard Instrument Departures (SIDs)". SIDs also provide obstacle clearance and are published under the appropriate airport section. ATC clearance must be received prior to flying a SID.

CIVIL USERS NOTE: Title 14 Code of Federal Regulations Part 91 prescribes standard takeoff rules and establishes takeoff minimums for certain operators as follows: (1) For aircraft, other than helicopters, having two engines or less – one statute mile visibility. (2) For aircraft having more than two engines – one-half statute mile visibility. (3) For helicopters – one-half statute mile visibility. These standard minima apply in the absence of any different minima listed below.

MILITARY USERS NOTE: Civil (nonstandard) takeoff minima are published below. For military takeoff minima, refer to appropriate service directives.

NAME	TAKEOFF MINIMUMS
------	------------------

BABELTHUAP, KOROR, PS

BABELTHUAP/KOROR (ROR) (PTRO)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 09015 (FAA)

TAKEOFF MINIMUMS: **Rwy 27**, 400-1 or std. with a min. climb of 296' per NM to 500.

DEPARTURE PROCEDURE: **Rwy 9**, climb runway heading to 700 then as cleared.

NAME	TAKEOFF MINIMUMS
------	------------------

GUAM, GG

GUAM INTL (GUM) (PGUM)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 15176 (FAA)

TAKEOFF MINIMUMS: **Rwy 6L**, 400- 1¼ or std. w/min. climb of 380' per NM to 800. **Rwy 6R**, 400- 1¼ or std. w/min. climb of 520' per NM to 900. **Rwy 24L**, std. w/min. climb of 280' per NM to 1700. **Rwy 24R**, std. w/min. climb of 285' per NM to 1700.

DEPARTURE PROCEDURE: **Rwy 6L, 6R**, climb heading 063° to 1100 before turning right.

TAKEOFF OBSTACLE NOTES: **Rwy 6L**, trees beginning 2280' from DER, 690' left of centerline, up to 40' AGL/427' MSL. Trees beginning 562' from DER, 115' right of centerline, up to 40' AGL/443' MSL. Tree 5729' from DER, 1887' right of centerline, 40' AGL/546' MSL. **Rwy 6R**, trees beginning 1224' from DER, 38' left of centerline, up to 40' AGL/389' MSL. Trees beginning 4054' from DER, 331' left of centerline, up to 40' AGL/442' MSL. Pole 3707' from DER, 933' right of centerline, 10' AGL/456' MSL. Tree 4227' from DER, 265' right of centerline, 40' AGL/443' MSL. Ol bldg 6150' from DER, 1953' right of centerline, 40' AGL/701' MSL. Tree 6729' from DER, 1186' right of centerline, 40' AGL/546' MSL. Tree 7934' from DER, 1781' right of centerline, 40' AGL/659' MSL.

12 OCT 2017 to 07 DEC 2017

12 OCT 2017 to 07 DEC 2017



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

L1

PAC



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

HANA, HI

HANA (HNM) (PHHN)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
ORIG 05244 (FAA)
DEPARTURE PROCEDURE: Use LINDBERG
DEPARTURE.

HILO, HI

HILO INTL (ITO) (PHTO)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 6 05356 (FAA)
DEPARTURE PROCEDURE: Use PARIS DEPARTURE.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 16147 (FAA)
Rwy 3, 8, heading as assigned by ATC. **Rwy 21**,
heading as assigned by ATC; requires minimum climb of
300' per NM to 1300. **Rwy 26**, heading as assigned by
ATC; requires minimum climb of 420' per NM to 2800.

HONOLULU, HI

DANIEL K INOUYE INTL (HNL) (PHNL)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 8A 17117 (FAA)
DEPARTURE PROCEDURE: use HONOLULU
DEPARTURE.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 16035 (FAA)
Rwy 4L/R, heading as assigned by ATC; requires
minimum climb of 490' per NM to 2100, do not exceed 180
KTS until established on assigned heading. **Rwy 8L**,
heading as assigned by ATC; requires minimum climb of
360' per NM to 1700. **Rwy 8R**, heading as assigned by
ATC; requires minimum climb of 240' per NM to 700. **Rwy**
22L/R, heading as assigned by ATC; requires
minimum climb of 320' per NM to 3700. **Rwy 26L**, heading
as assigned by ATC; requires minimum climb of 360' per
NM to 3700. **Rwy 26R**, heading as assigned by ATC;
requires minimum climb of 430' per NM to 4400.

KAHULUI, HI

KAHULUI (OGG) (PHOG)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 7 14149 (FAA)
TAKEOFF MINIMUMS: **Rwy 23**, NA-ATC.
DEPARTURE PROCEDURE: **Rwy 2**, climb on a heading
316° CW 052° from DER to 10600 before proceeding
on course. **Rwy 5**, climb on a heading 312° CW 040°
from DER to 10700 before proceeding on course. **Rwy**
20, climb on heading 185° from DER to 11000 before
proceeding on course.
TAKEOFF OBSTACLE NOTES: **Rwy 2**, bush and trees
beginning 190' from DER, 363' left of centerline, up to
60' AGL/79' MSL. Bushes and obstruction light on
building beginning 339' from DER, 289' right of
centerline, up to 20' AGL/25' MSL. **Rwy 5**, tree 2359'
from DER, 512' left of centerline, 56' AGL/75' MSL.
Fence 20' from DER, 304' right of centerline, 11'
AGL/31' MSL. Bushes, trees and fence beginning 228'
from DER, 300' right of centerline, up to 76' AGL/95'
MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 16147 (FAA)
Rwy 2, 5, 20, heading as assigned by ATC.

KAILUA-KONA, HI

KONA INTL AT KEAHOLE (KOA) (PHKO)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 5 11237 (FAA)
DEPARTURE PROCEDURE: **Rwy 17**, climb on heading
174° to 500 then climbing right turn heading 357° and
KOA R-327 to MYNAH INT for assigned route. **Rwy**
35, eastbound climb on heading 354° to intercept MUE
R-246 for assigned route; northwest bound climb
heading 354° to 500 then climbing left turn to assigned
route.
TAKEOFF OBSTACLE NOTES: **Rwy 17**, obstruction
light on AMOM at DER, 350' right of centerline, 25'
AGL/62' MSL. **Rwy 35**, tree 1606' from DER, 7211' right
of centerline, 15' AGL/94' MSL.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 15288 (FAA)
Rwy 17, 35, heading as assigned by ATC.

KALAUPAPA, HI

KALAUPAPA (LUP) (PHLU)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
ORIG 11069 (FAA)
DEPARTURE PROCEDURE: Use KALAUPAPA ONE
DEPARTURE.

12 OCT 2017 to 07 DEC 2017

12 OCT 2017 to 07 DEC 2017



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

PAC



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

KAMUELA, HI

WAIMEA-KOHALA (MUE) (PHMU)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

AMDT 1 05076 (FAA)

TAKEOFF MINIMUMS: **Rwy 4**, 400-2 or std. with a min. climb of 240' per NM to 3100.

DEPARTURE PROCEDURE: **Rwy 4**, climb via heading 041° to 3100 then climbing right turn via heading 080° and MUE VOR/DME R-057 to 6000 to VELLA INT, then as assigned. **Rwy 22**, climb via heading 233° and MUE VOR/DME R-234 to 5000 to JASON INT, then as assigned.

TAKEOFF OBSTACLE NOTES: **Rwy 4**, windsock 158' from DER, 299' right of centerline, 25' AGL/2702' MSL. Fence 2754' from DER, 323' right of centerline, 12' AGL/2741' MSL. Tree 5200' from DER, 179' right of centerline, 50' AGL/2817' MSL. Tree 5331' from DER, 110' left of centerline, 50' AGL/2829' MSL. Tree 1.3 NM from DER, 739' right of centerline, 50' AGL/2864' MSL. Tree 1.3 NM from DER, 1741' left of centerline, 50' AGL/2889' MSL. Antenna 1.8 NM from DER, 1094' left of centerline 152' AGL/2992' MSL. Rising terrain beginning 1.5 NM from DER, 3.9 NM left of centerline, up to 13796' MSL. **Rwy 22**, cactus at DER, 191' left of centerline, 10' AGL/2668' MSL. Tree at DER, 353' right of centerline, 50' AGL/2687' MSL. Bush 673' from DER, 186' left of centerline, 30' AGL/2673' MSL. Pole 1058' from DER, 124' left of centerline, 20' AGL/2683' MSL. Rapidly rising terrain beginning 1.5 NM from DER, 4209' left of centerline, up to 5513' MSL.

KAPOLEI, OAHU ISLAND, HI

KALAELOA (JOHN RODGERS FIELD) (JRF)
(PHJR)

TAKEOFF MINIMUMS AND (OBSTACLE)

DEPARTURE PROCEDURES

ORIG 09295 (FAA)

DEPARTURE PROCEDURE: DME Required. **Rwys 4L, 4R, 11**, climb heading 200° to intercept HNL VORTAC R-241 to GECKO/HNL 22.4 DME before proceeding on course. **Rwys 22L, 22R**, climb heading 224° to intercept HNL VORTAC R-241 to GECKO/HNL 22.4 DME before proceeding on course. **Rwy 29**, climb heading 210° to intercept HNL VORTAC R-241 to GECKO/HNL 22.4 DME before proceeding on course.

TAKEOFF OBSTACLE NOTES: **Rwy 11**, tree 1533' from DER, 831' left of centerline, 60' AGL/70' MSL. **Rwy 22L**, vehicles on road 305' from DER, 195' left of centerline, 15' AGL/26' MSL. **Rwy 29**, tree 1794' from DER, 573' left of centerline, 60' AGL/99' MSL.

KAUNAKAKAI, HI

MOLOKAI (MCK) (PHMK)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

AMDT 6 14149(FAA)

DEPARTURE PROCEDURE: use KAUNAKAKAI
DEPARTURE.

DIVERSE VECTOR AREA (RADAR VECTORS)

AMDT 1 15288 (FAA)

Rwy 17, heading as assigned by ATC. **Rwy 23**, heading as assigned by ATC; requires minimum climb of 460' per NM to 2000.

KOSRAE, FM

KOSRAE (TTK) (PTSA)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

ORIG-A 09071 (FAA)

CAUTION: Ships with masts to 200' traverse harbor entrance located on west side of runway.

DEPARTURE PROCEDURE: **Rwy 5**, left turn. **Rwy 23**, right turn, climb to 2000 or above before turning east.

LANAI CITY, HI

LANAI (LNY) (PHNY)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES

AMDT 5 09239(FAA)

TAKEOFF MINIMUMS: **Rwy 3**, 400-1 or std. w/ min. climb of 370' per NM to 2700 or 2500-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 3**, climb heading 033° to 1720 before turning left. Climb heading 300° or 180° to intercept route or airway, then continue as cleared. Maintain maximum 210 kts until turn is completed or for climb in visual conditions cross LNY VORTAC eastbound at or above 3700. **Rwy 21**, climb heading 213° to assigned altitude. Eastbound - climb westbound to cross LNY VORTAC eastbound at or above 2700 and climb as cleared. Westbound - climb direct LNY VORTAC then via assigned route.

TAKEOFF OBSTACLE NOTES: **Rwy 3**, multiple poles, trees, and terrain beginning 2108' from DER, 1011' left of centerline, up to 200' AGL/2202' MSL. **Rwy 21**, lighted windsock 8' from DER, 191' right of centerline, 30' AGL/1323' MSL.

12 OCT 2017 to 07 DEC 2017

12 OCT 2017 to 07 DEC 2017



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

PAC



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

LIHUE, HI

LIHUE (LIH) (PHLI)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 8 00279 (FAA)

TAKEOFF MINIMUMS: **Rwy 21**, 2400-3. Use DIANE
DEPARTURE PROCEDURE.

DEPARTURE PROCEDURE: **Rwys 3, 35**, to V15, climb
runway heading to 500 then climbing right turn, heading
125°, then as assigned. **Rwy 17**, to V15, climb runway
heading to 500 then climbing left turn, heading 045°, then
as assigned. To LIH-150 climb runway heading to 500
then climbing left turn, heading 120°, then as assigned.
Rwy 21, to V15, climb runway heading to 550 then
climbing left turn, heading 090°, to intercept LIH R-110,
maintain 5000, direct BOOKE INT or as assigned. To LIH-
148, climb runway heading to 550, then climbing left turn,
heading 120°, to intercept LIH R-148, maintain 3000,
direct NAPUA INT or as assigned.

DIVERSE VECTOR AREA (RADAR VECTORS)
AMDT 1 15288 (FAA)

Rwys 3, 17, heading as assigned by ATC. **Rwy 21**,
heading as assigned by ATC; requires minimum climb of
400' per NM to 4500. **Rwy 35**, heading as assigned by
ATC; requires minimum climb of 230' per NM to 700.

MAJURO ATOLL, RM

MARSHALL ISLANDS INTL (MAJ) (PKMJ)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
ORIG 10098 (FAA)

TAKEOFF OBSTACLE NOTES: **Rwy 7**, antenna on
building 215' from DER, 446' left of centerline, 48' AGL/54'
MSL. Obstruction light on AMOM 44' from DER, 269' left of
centerline, 33' AGL/39' MSL. Obstruction light on WSK 10'
from DER, 245' right of centerline, 23' AGL/29' MSL. Tree
934' from DER, 243' left of centerline, 39' AGL/45' MSL.
Bush 555' from DER, 187' right of centerline, 17' AGL/23'
MSL. **Rwy 25**, obstruction light on WSK 11' from DER,
246' left of centerline, 23' AGL/29' MSL. Post 51' from
DER, 252' right of centerline, 8' AGL/14' MSL. Tree 996'
from DER, 39' left of centerline, 31' AGL/37' MSL. Tree
563' from DER, 5' right of centerline, 20' AGL/26' MSL.
Bushes beginning 207' from DER, from 124' left to 207'
right of centerline, up to 14' AGL/20' MSL. Vehicle on
roadway 130' from DER, 241' right of centerline, 15'
AGL/20' MSL.

PAGO PAGO, AQ

PAGO PAGO INTL (PPG) (NSTU)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
ORIG-A 09071 (FAA)

TAKEOFF MINIMUMS: **Rwy 23**, std. w/ min. climb of 320'
per NM to 800, or 2700-3 for climb in visual conditions.

Rwy 26, NA-obstacles.

DEPARTURE PROCEDURE: **Rwys 5, 8**, climbing right turn
southbound between TUT R-090 clockwise to R-180 to
2800, then proceed on course. **Rwy 23**, climbing left turn
heading 150° southbound between TUT R-090 clockwise
to R-180 to 2800, then proceed on course. For climb in
visual conditions: cross Pago Pago Intl Airport at or above
2600 before proceeding on course.

TAKEOFF OBSTACLE NOTES: **Rwy 5**, bush 1' from DER,
237' right of centerline, 3' AGL/12' MSL. Bush 379' from
DER, 362' left of centerline, 14' AGL/23' MSL. Ship 998'
from DER, 57' right of centerline, 150' AGL/150' MSL. **Rwy 8**,
bush 689' from DER, 360' left of centerline, 15' AGL/23'
MSL. Ship 1435' from DER, 304' left of centerline, 150'
AGL/150' MSL. **Rwy 23**, multiple trees beginning 352'
from DER, 173' left of centerline, up to 20' AGL/132' MSL.
Multiple trees beginning 881' from DER, 296' right of
centerline, up to 20' AGL/172' MSL. Multiple trees and
poles beginning 1.6 NM from DER, 38' right of centerline,
up to 367' AGL/554' MSL. Tree 2.3 NM from DER, 2126'
left of centerline, 20' AGL/387' MSL.

POHNPEI ISLAND, FM

POHNPEI INTL (PNI) (PTPN)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 3 17117 (FAA)

TAKEOFF MINIMUMS: **Rwy 27**, 300-1½ or std. w/min.
climb of 215' per NM to 300, or alternatively, with standard
takeoff minimums and a normal 200'/NM climb gradient,
takeoff must occur no later than 1400' prior to DER.

DEPARTURE PROCEDURE: **Rwy 9**, Climb on a heading
between 264° CW 083° from DER to 2600 before
proceeding on course. **Rwy 27**, Climb on a heading
between 264° CW 083° from DER to 2600 before
proceeding on course.

TAKEOFF OBSTACLE NOTES: **Rwy 27**, fence 92' from
DER, left to right of centerline, up to 9' AGL/15' MSL. Tree
1.2 NM from DER, 1175' left of centerline, 62' AGL/203'
MSL.

CAUTION: **Rwy 27**, ships with maximum height of 150' MSL
may traverse Pohnpei channel 400' off DER, closing
airport at times.

12 OCT 2017 to 07 DEC 2017

12 OCT 2017 to 07 DEC 2017



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

PAC



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

ROTA ISLAND, CQ

BENJAMIN TAISACAN MANGLONA INTL
(GRO) (PGRO)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 2 14037 (FAA)

DEPARTURE PROCEDURE: **Rwy 9**, climb heading 090° to 1400 before turning. **Rwy 27**, climb heading 270° to 2200 before turning southbound.

TAKEOFF OBSTACLE NOTES: **Rwy 9**, tree 514' from DER, 418' left of centerline, up to 30' AGL/638' MSL. **Rwy 27**, tree 1203' from DER, 581' left of centerline, up to 30' AGL/618' MSL.

SAIPAN ISLAND, CQ

FRANCISCO C ADA/SAIPAN INTL (GSN)
(PGSN)

TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
ORIG-A 09071 (FAA)

DEPARTURE PROCEDURE: **Rwys 7, 25**, climb on runway heading to 1600 before climbing on course.

TINIAN ISLAND, CQ

TINIAN INTL (TNI) (PGWT)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 1 09239 (FAA)

TAKEOFF OBSTACLE NOTES: **Rwy 8**, trees beginning 694' from DER, 507' left of centerline, up to 100' AGL/363' MSL. Multiple trees beginning 569' from DER, 471' right of centerline, up to 100' AGL/389' MSL. **Rwy 26**, multiple trees beginning 743' from DER, 508' right of centerline, up to 100' AGL/363' MSL.

WENO ISLAND, FM

CHUUK INTL (TKK) (PTKK)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 2 10042(FAA)

DEPARTURE PROCEDURE: **Rwy 4**, climb heading 041° to 1100 before proceeding on course. **Rwy 22**, climb heading 221° to 1500 before proceeding on course.

TAKEOFF OBSTACLE NOTES: **Rwy 4**, bush 205' from DER, 203' right of centerline, 7' AGL/17' MSL. **Rwy 22**, bush 5' from DER, 241' right of centerline, 14' AGL/24' MSL. Bush 221' from DER, 85' right of centerline, 7' AGL/17' MSL. **CAUTION:** Ships with superstructure to 150' traverse channels west of runway 4/22.

YAP ISLAND, FM

YAP INTL (T11) (PTYA)
TAKEOFF MINIMUMS AND (OBSTACLE)
DEPARTURE PROCEDURES
AMDT 2 94342 (FAA)

DEPARTURE PROCEDURE: **Rwy 7**, climbing right turn to 1500 via 090° bearing from YP NDB/DME, then climb on course. **Rwy 25**, climb to 500, then climb on course.

12 OCT 2017 to 07 DEC 2017

12 OCT 2017 to 07 DEC 2017



TAKEOFF MINIMUMS, (OBSTACLE) DEPARTURE PROCEDURES, AND DIVERSE VECTOR AREA (RADAR VECTORS)



17285

PAC