

LOC/DME I-PWM 109.9 Chan 36	APP CRS 110°	Rwy Idg 7200 TDZE 76 Apt Elev 76
---	------------------------	---




ILS or LOC RWY 11

PORTLAND INTL JETPORT (PWM)

▲ For inoperative ALSF-2, increase S-LOC 11 Cat C/D visibility to 1 1/2 mile. Increase FINUS fix minimums S-LOC 11 Cat C/D visibility to RVR 5500.

▲ MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct ENE VOR/DME and hold.

ATIS 119.05	PORTLAND APP CON * 119.75 269.35	PORTLAND TOWER * 120.9 0 (CTAF) 257.8	GND CON 121.9	CLNC DEL 121.9	UNICOM 122.95
-----------------------	--	---	-------------------------	--------------------------	-------------------------



CATEGORY	A	B	C	D
S-ILS 11	276/18 200 (200-1/2)			
S-LOC 11	700/24	624 (700-1/2)	700-1 3/8	624 (700-1 3/8)
C CIRCLING	700-1	624 (700-1)	740-1 3/4	860-2 1/2
FINUS FIX MINIMUMS				
S-LOC 11	440/24	364 (400-1/2)	440/35	364 (400-3/8)
C CIRCLING	620-1	544 (600-1)	740-1 3/4	860-2 1/2
			664 (700-1/4)	784 (800-2 1/2)

NE-1, 30 JAN 2020 to 27 FEB 2020

NE-1, 30 JAN 2020 to 27 FEB 2020